



### FLEXYLED SHE6B PRO

flexible linear LED roll without cable



Code	Length	Watt	Volt	CCT
1590701B1/SHE	10m	14,4 W/m	24 VDC	2700 K
1590701B/SHE	10m	14,4 W/m	24 VDC	3000 K
1590701N/SHE	10m	14,4 W/m	24 VDC	4000 K



### FLEXYLED SHE6B PRO PW

flexible linear LED module with cable

Code	Length	Watt	Volt
on request	on request	14,4 W/m	24 VDC



values referring to FLEXYLED SHE6B PRO 1000mm 4000 K

<b>Colour appearance</b>	super warm white	warm white	natural white
<b>Colour temperature</b>	2700 K	3000 K	4000 K
<b>Luminous flux</b>	1420 lm/m	1420 lm/m	1420 lm/m
<b>Luminous efficiency</b>	99 lm/W	99 lm/W	99 lm/W
<b>CRI</b>	Ra 80	Ra 80	Ra 80

## FLEXYLED SHE6B PRO

### Flexible linear LED module

FLEXYLED SHE6B PRO is a dimmable single-colour light source developed on a 6mm-wide linear flexible module with 180 LED/m (Osram), designed for installation in profiles with a removable diffuser. The module, which can be divided at 33.3 mm (6 LED) intervals, is supplied with an adhesive base. FLEXYLED SHE6B PRO is available in 10 m long rolls without a power cable, compatible with the CH6 connection system. Modules with customised length, 2000 mm power cable and Micro24 male connector (pre-wired PW version) are available on request. Power supply not included. To be ordered separately.

