STICKS LIKE SH*T

HIGH STRENGTH, ALL WEATHER SMP ADHESIVE

TECHNICAL SHEET 01/07/2025

SMART ADVANTAGES

- Hybrid-based adhesive with superior bond strength
- Universal bonding for interior and exterior use
- Adheres perfectly without primer on most, even damp, surfaces
- Neutral curing system, almost odourless
- Good resistant to UV, weather, moisture and mold

DESCRIPTION

Sticks Like Sh*t adhesive is a high-performance, all weather, instant grab adhesive Silyl Modified Polymer (SMP) based adhesive. The single component, SM Polymer formulation has a superior bond strength, even on smooth, non-absorbent surfaces.
Sticks Like Sh*t is water and solvent free, with minimal shrinkage and low odour. It offers outstanding performance across wide variety of construction applications and typically does not require a primer.

USES

Sticks Like Sh*t bonds to most surfaces including wood, concrete, brick, plaster, glass, ceramics, metals, rigid PVC, GRP insulation boards, and foam polystyrene.

PRODUCT CHARACTERISTICS

Appearance	Warm White
Form	Thixotropic paste
Composition	Moisture curing SMP

TYPICAL PERFORMANCE DATA

Temperature Resistance	-40°C to +90°C



Application Temperature	+5°C to +40°C
Application Rate	500-800 g/min
Skin Time *	10 minutes @ +23°C/50% RH
Cure Rate	2 mm/24 hours @ +23°C/50% RH
Full Cure	24 hours, depending on bead width, temperature and humidity
Density	1.60g/ml
Shore A Hardness	60
Tensile Strength	2.05 N/mm2
Elongation At Break	200%
Coverage per 3mm Diameter Bead (approx.)	44m
Coverage per 5mm Diameter Bead (approx.)	14m

**Depends on ambient temperature and relative humidity*

APPLICATION

IMPORTANT: Before using Sticks Like Sh*t refer to the relevant Safety Data Sheet, available at bostik.com.au. For any application or detail not covered, please contact Technical Services on 1800 267 845.

PRECAUTION: **Sticks Like Sh*t** will not bond Polyethylene, Polypropylene or Teflon. It must not be used to bond mirrors if the mirror is backed with plastic safety film. Do not bond mirrors to painted

surfaces, as the decorative finish will be unable to support the load.

Sticks Like Sh*t should not be used on surfaces contaminated by bitumen, and it is not suitable for continuously damp conditions. It is recommended in overhead applications to always use in conjunction with mechanical fixings. Yellowing can occur in predominantly dark conditions.

PREPARATION

- Surfaces must be sound, clean and free from any contaminants such as dust, oil, grease and any loose material. Damp surfaces must be checked for weak or loose material on the surfaces that the presence of damp might hide.
- Cut off the dome at the top of the cartridge taking care not to damage the thread. Cut the nozzle to the desired width and angle. Screw the nozzle onto the cartridge.
- Insert the cartridge into a cartridge gun and repeatedly squeeze the trigger until the adhesive appears.

PRIMING

Sticks Like Sh*t generally does not require priming, if unsure please contact our team for advice.

DIRECTIONS OF USE

- Apply parallel beads of adhesive to one of the surfaces, align and bring the surfaces together before the product has skinned.
- Beads 5mm in diameter are generally sufficient. For close fitting surfaces the bead may be reduced to 3mm diameter.
- The degree of separation of the beads of **Sticks Like Sh*t** will depend upon the rigidity and weight of the panel, board or sign being bonded.
- A perimeter bead should not be applied as this can increase curing times.
- For rigid sheets, 100 – 150mm separation between beads is generally sufficient for high loading but may be increased if the load is low (such as lightweight wallboards and foam polystyrene) where 200mm – 500mm is acceptable.
- For less rigid boards the separation may need to be quite small, and it is important to choose the correct bead size to ensure good contact on the mating surfaces.
- Clamp or support the materials until sufficient time has elapsed.

PAINTABILITY

Sticks Like Sh*t is paintable with water based and most 2 component paints. Synthetic paints can dry slower. It is recommended to test compatibility with any paints prior to applications.

CLEANING

- Uncured product may be removed using cloths lightly dampened with white spirit, after carefully scraping off the bulk.
- Cured product requires mechanical removal.

STORAGE & SHELF LIFE

Store for up to 18 months from the date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight. Protect from frost.

HEALTH & SAFETY

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request or at bostik.com.au. All recommendations and suggestions are for guidance only, as conditions of use are outside of our control.

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.

SKU	SIZE	CARTON QTY	PALLET QTY
30631207	290ml	12	1152

Bostik Australia
51-71 High St, Thomastown
VIC 3041
P: 1800 267 845
bostik.com.au

BOSTIK HOTLINE
1800 BOSTIK (267 845)



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers, and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers, or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out-of-date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com.au