

## **Pressure is Productivity**

# **Prospair Series**Waterwell Compressor

















# **DOOSAN**. Portable Power

#### **Features:**

- Dual regulation of 300 / 315
- Best in class fuel consumption
- Cost effective drilling in its class
- Compact and centralized drain
- Rugged enclosures with aesthetically and ergonomically designed
- Silent version, eco-friendly
- Designed for operation in an ambient of 54° C
- Zero maintenance battery
- Pre cleaners with twin entry filters
- Low on maintenance

#### **Specifications:**

MODEL	PA1150C
MAX. FREE AIR DELIVERY* (CFM)	1150
DRILLING PRESSURE (PSIG)	300/315
UNLOADING PRESSURE (PSIG)	330
COMPRESSOR TYPE	TWO STAGE
COOLING SYSTEM	OILINJECTION
COMPRESSOR OIL	XHP 405
OIL CAPACITY (LITRES)	90
MAX. OPERATING TEMPERATURE (DEG C)	54
MIN. OPERATING TEMPERATURE (DEG C)	5
ENGINE SPECIFICATIONS	
MAKE	CUMMINS
MODEL	NTA855C
BHP (HP)	427
STROKE/No. OF CYLINDERS	4 STROKE / 6 CYLINDERS
RATED SPEED (RPM)	1900
IDLE RPM (RPM)	1200
MAXIMUM RPM	1970
DIMENSIONS	
OVERALL LENGTH (MM)	3615
OVERALL WIDTH (MM)	1700
OVERALL HEIGHT (MM)	1675 / 1950
DRY WEIGHT (KG)	4600

### DOOSAN.

#### **Portable Power**


### Doosan Bobcat India Pvt. Ltd.

2<sup>nd</sup> & 3<sup>rd</sup> Floor, Durga Arcade,

Site no 5, MCHS layout, Jakkur,

Yelhanka Hobli, Bangalore - 560064, India. Tel.No: 080-67231001, Toll Free: 1800 103 2869

Email: ap.yogananda@doosan.com Website: www.doosanportablepower.com



<sup>\*</sup> In Accordance to ISO 1217 1996 Annexure E

<sup>&</sup>gt; Pictorial dimensions & specifications are for visual representation only, and can change continuously