DOOSAN. Portable Power

SHP810 The >> NEXT-Gen Machine



MAKE POWER MOVES .

FEATURES



SHP series of Doosan has compact footprint in industry, customers voice sequenced with compact footprint which enables lower investment on mounting and maximizes utility space on their equipment. Door sizes ensures ease in reaching to critical parts and space to stack more rods for operating higher depths. Machine dimensions and weight supports mounting for operating in Narrow spaces too.

Package is designed for low noise requirement which ensures ease of operation in densely populated areas, thicker enclosure up to 3 mm and foam makes the package suitable for operating in densely populated areas.

With new programming of jaguar V 1 version ensures faster drilling in its class with best fuel efficiency. Package is designed to work in all class of applications of water well from 4.75" to 7" dia, for abrasive blasting, pigging, anchoring, piling and utility applications. One machine for several applications

Lifting Hook

Suitably located CG, single point

lifting can easily be achieved.



Door Lock

Door locks are provided to prevent theft.

Rubber Beading

Doors are provided with rubber beading to further reduce the vibrations, noise and water entry.

Sight Glass

Oil level can be checked easily from the sight glass.

FEATURES



Air Filter

Package provided with 3 stage air filtrations to operate in all types of dusty environments. Inbuilt pre-cleaners ensure better air quality for operation and enhances life of components, engine air filters are provided with choke switch.

Cabin Light

Cabin lights provided for night operation.

Central Drain

Central drain ensures ease of servicing during maintenance and ensures uptime.



Engine

High Power and torque are available at lesser RPM with low noise & better load acceptance, cast iron cylinder block makes it more robust hence reduces the vibration and noise, reduces the downtime by monitoring key parameters through sensors.

Batteries with Isolator Switch

Maintenance free batteries with battery isolator is a standard offering. Batteries can work from 52°C to -10°C, no more top up required.



Controller

Doosan smart controller with one touch to start and provides user friendly operations.

FEATURES



Package is designed to operate between extreme weather conditions which is powered by tier 2 compliant engine for less hazard while operating in densely populated areas.



Cool box design is one of the premium features adapted by Doosan Portable Power over decades which ensures better life of the package and enables to work at higher temperatures.







Doosan Smart Controller

Doosan Smart Controller with one touch to start and provides user friendly operations with different screens for showing key parameters, troubleshooting and maintenance due. This Smart Controller comes with 3.8" monochrome transflective LCD screen (320 X 240 pixels), Real-time clock with Li-ion battery backup. Build with Polycarbonate material and with IP67 configuration and capable of operating between -40°C to 85°C, Can withstand high levels of vibrations and shock. Standard display provides user friendly Analog gauge interface with key compressor parameters. With jaguar V 1 program version which ensures package to operate like mechanical engine package.







6		
SERVICE REMINDERS		
COMPRESSOR OIL		
INTERVAL	1000 HRS	
REMAINING	1999 HRS	
RESET		
	E − +.	
00000		
\mathbf{O}	$\mathcal{O}\mathcal{O}\mathcal{O}$	







EASY MAINTENANCE



Even the best equipment needs regular maintenance. Doosan Portable Power makes it easy to care for your compressor with easy access to all the parts. If you want a machine that lasts with minimal effort, Doosan Portable Power is the right choice for you.



SPECIFICATIONS



Model	SHP810	
Compressor		
Maximum free air delivery *	810 cfm	
Working Pressure	275 / 295 psi	
Unloading pressure	310 psi	
Compressor Oil	XHP 405	
Oil Capacity (Refill)	90 Liters	
Max. Operating temperature	52°C	
Min. Operating temperature	- 10º C	
Engine		
Make	Volvo	
Model	TAD843	
Power	325 hp	
No. of Cylinders	4 Stroke / 6 Cylinders	
Rated Speed	1900 rpm	
Idle Speed	1250 rpm	
Dimensions		
Overall Length	3150 mm	
Overall Width	1600 mm	
Overall Height	1790 mm	
Dry Weight	3350 kg	

* In Accordance to ISO217 1996 Annexure E

DOOSAN NETWORK



🛞 www.doosanportablepower.com/in/en



Doosan Bobcat India Pvt. Ltd. 2nd & 3rd Floor , Durga Arcade, Site no 5, MCHS layout, Jakkur, Yelahanka Hobli, Bangalore - 560064, India. Tel.No: 080-67231015, Toll free : 1800 103 2869 Email : ap.yogananda@doosan.com