MAKE POWER MOVES.

Doosan Portable Light Tower



Experience Doosan Portable Power and our industry-leading support and service. Whatever the job, we have the solution. From our comprehensive range of reliable light towers.



DOOSAN. Portable Power

Features:

- Designed for dusty applications.
- Compact, ensures maximization in transport.
- Dual engine option for 4000 watts range.
- Towers can be raised and lowered within 60 seconds.
- Self locking winches to ensure operator safety.
- Opticals and towers can be rotated by 360 deg.
- Opticals are with aluminium luminaries and provided with drain hole for glare free light.
- Flicker free metal halide lamps covers 7.5 acres.
- Curly cord cable, opens and retracts based on tower operation.
- Brushless maintenance free alternators.
- Power In and out option available.
- Suitably sized fuel tank to ensure longer running hours.
- Plastic fuel tank ensure no corrosion and leakage.
- Maximum towing speed of 4okm/hr.
- Fork lift option for movement.
- One Stop shop for aftermarket support.

Specifications:

Model	LSCK4
LUMINAIRES & TOWER	
Luminaries (Total Wattage)	4000 W
No. of Lamps	4 nos , 1000 W each
Type of Lamp	Metal Halide
Type of Optical	Dome
Mast Height (meters)	9
Protection Type	IP65
ENGINE	
Make	Kubota
Engine Model	D1105
Rating	11 HP @ 1500 RPM
ALTERNATOR	
Alternator Make	NSM
Alternator Model	K132B
Alternator Type	Single Phase, 4 Pole
Insulation	H class
Frequency	50Hz
FUEL TANK & RUNNING HOURS	
Fuel Tank Capacity (Liters)	102
Continuous Running Hours	66
DIMENSIONS & WEIGHT	
Length (mm)	4430
Width (mm)	1400
Height (mm)	1730
Overall Weight (Kgs)	700



Blue Metal Quarry



Defence



Dam



Road



Bridges



Mining



General Construction

DOOSANPortable Power

Doosan Bobcat India Pvt. Ltd.
2nd & 3rd Floor, Durga Arcade,
Site no 5, MCHS layout, Jakkur,
Yelhanka Hobli, Bangalore - 560064, India.
Tel.No: 080-67231015, Toll free: 1800 103 286
Email: ap.yogananda@doosan.com

Website: www.doosanportablepower.com/in/en

Authorized Dealer:

OOSAN/LSCK/JUNE/2021