



Rental Condition & Delivery Report for Mini Track Loaders

Customer:		Rental Contract #:	
Model #:		Unit #:	
Attachment(s):			

Equipment Condition (note any damage and include pictures):

<input type="checkbox"/> Fluid Levels	<input type="checkbox"/> Tilt, Lift Cylinders and Lift Arm Support Device
<input type="checkbox"/> Hydraulics (Pump, hoses, etc.)	<input type="checkbox"/> Safety Decals / Operation & Maintenance Manual
<input type="checkbox"/> Electrical (operating/warning lights, battery, etc.)	<input type="checkbox"/> Reverse Stop Panel
<input type="checkbox"/> Rollers, Idlers & Tracks	<input type="checkbox"/> Neutral Start System Functional
<input type="checkbox"/> Bob-Tach Functional	<input type="checkbox"/> Parking Brake

Comments/Notes:

Prepare to Perform (Safety Acknowledgements)

_____ **Customer Initial Here**



1. I understand the machine operation and maintenance procedures.
2. Additional training resources are available at www.training.bobcat.com.
3. Always check for underground utility lines before digging.
4. I understand how to use and how to attach and remove the attachment(s).
5. I understand the function of Reverse Stop Panel.
6. This machine has safety signs (decals), an Operation & Maintenance Manual and an AEM Safety Manual.
7. NEVER use the Mini Loader in an environment with explosive dust or gases or with flammable material near exhaust.
8. Always provide adequate ventilation when using the Mini Loader in an enclosed area. Exhaust gases can kill.
9. The Bobcat Mini Loader Safety video can be viewed online in English and Spanish by scanning the code below.

Operation Instructions

_____ **Customer Initial Here**

1. Operate ONLY from operator's position behind the machine
2. Controls must be in NEUTRAL to start engine.
3. This machine has a Rating Operating Capacity (ROC) for carrying loads. Do not exceed the ROC.
4. Keep heavy end of mini loader uphill when operating on slopes and CARRY LOAD LOW.
5. NEVER go under or reach under lift arms unless supported by an approved lift arm support device.
6. Keep the bucket level when raising lift arms to prevent material from falling out of the bucket.
7. To Leave the Loader:
 - Lower the lift arms and put attachment flat on the ground.
 - Put all controls in NEUTRAL.
 - Engage parking brake.
 - STOP the engine.

Scan this code to Learn More!

I UNDERSTAND THE ABOVE SAFETY ACKNOWLEDGEMENTS AND OPERATION INSTRUCTIONS.

X _____
Customer Signature

DATE _____