



Rental Condition & Delivery Report for Compact Loaders

Customer:		Rental Contract #:	
Model #:		Unit #:	
Attachment(s):			

Equipment Condition (note any damage and include pictures):

- | | |
|--|---|
| <input type="checkbox"/> Fluid Levels | <input type="checkbox"/> Tilt and Lift Cylinders, Lift Arm Support Device |
| <input type="checkbox"/> Hydraulics (Pump, hoses, etc.) | <input type="checkbox"/> Safety Decals and Operator's Handbook |
| <input type="checkbox"/> Electrical (operating/warning lights, battery, etc.) | <input type="checkbox"/> Operating Controls/Interlocks (including BICS™) |
| <input type="checkbox"/> Axle, Rims and Tires <u>or</u> Rollers, Idlers & Tracks | <input type="checkbox"/> Horn and Back Up Alarm |
| <input type="checkbox"/> Seat, Seat Belt and Seat Bar | <input type="checkbox"/> Parking Brake |
| <input type="checkbox"/> Bob-Tach Functional | <input type="checkbox"/> Cab/Cab Mounting Hardware |

Comments/Notes:

Prepare to Perform (Safety Acknowledgements) _____ **Customer Initial Here**

- I understand the machine operation and maintenance procedures.
- This machine has safety signs (decals) and an Operator's Handbook.
- I am aware that Owner's and Safety Manuals are available.
- Additional training resources are available at www.training.bobcat.com.
- I know how to use and how to attach and remove the attachment(s).
- The rear window can be used as an alternate emergency exit.
- Single Point Lift, flashing lights, fire extinguisher and other options are available for job use.
- A Special Applications Kit is available to restrict material from entering cab openings if job use requires this.
- The Bobcat Skid-Steer Loader Safety video can be viewed online in English and Spanish by scanning the code below.



Operation Instructions _____ **Customer Initial Here**

- Operate **ONLY** from the operator seat. Keep feet on pedals or foot rests.
- ALWAYS** fasten seat belt before operating.
- This machine has a Rated Operating Capacity (ROC) for carrying loads. Do not exceed the ROC.
- Keep the heavy end of loader uphill when operating on slopes and **CARRY LOAD LOW**.
- NEVER** go under or reach under lift arms unless supported by an approved lift arm support device.
- To Leave the Loader:
 - Lower the lift arms and put attachment flat on the ground.
 - Engage parking brake.
 - STOP** the engine.
 - Raise seat bar and move all controls to neutral.

Scan this code to Learn More!



I UNDERSTAND THE ABOVE SAFETY ACKNOWLEDGEMENTS AND OPERATION INSTRUCTIONS.

X _____ **DATE** _____
Customer Signature