



COMPACT EQUIPMENT TIRES



PNEUMATIC LOADER TIRES



Standard-Duty Loader Tires

Designed for maximum traction and grip, the center lug of the Bobcat® standard-duty tire adds extra traction. These tires are created for long wear during normal machine-hour applications, such as agriculture, rental, landscaping and general construction. The special rim guard and thick sidewalls provide outstanding protection against punctures. They're constructed with a unique blend of natural and synthetic rubber.

- **Durable tread compound** prevents downtime and increases productivity
- **Extra-heavy sidewall** provides superior damage and puncture resistance
- **Special rim guard** protects the tire and wheel
- **Industry-leading tread depth** provides superior traction from high void-to-lug ratio



Heavy-Duty Loader Tires

Bobcat heavy-duty tires increase protection against punctures and cracks with extra-thick sidewalls. They feature bead guards to shield against rim and sidewall punctures. The combination of superior self-cleaning rubber and a high ply rating makes these tires ideal for rough, high-hour applications such as rental, construction, landscaping and industrial jobs.

- **Durable sidewall and rim shield protector** provide high resistance to flats and punctures
- **Proven tread compound** is wear-resistant to protect from chunking and separation
- **Special bead guard** offers great tire and rim protection
- **Superior tread design** offers three-step self-cleaning and excellent traction



Severe-Duty Loader Tires

When your job demands an aggressive, long-lasting tread, choose the Bobcat severe-duty tire. It's designed to take on more abuse than a conventional tire and provide superior self-cleaning characteristics.

The deep tread depth significantly increases service life while reducing downtime from cuts and punctures. Bobcat severe-duty tires are proven performers in construction, recycling, industrial, rental and other tough applications.

- **Unique tread pattern** operates in severe applications and provides excellent self-cleaning qualities
- **High ply ratings** increase service life while reducing downtime due to cuts and punctures
- **Sixty-eight percent solid-to-void tread ratio** performs well on aggressive surfaces
- **Strong sidewall protection** provides extraordinary hours of service and reduces downtime



Severe-Duty All-Terrain Loader Tires

A non-directional tire with an aggressive, extra-deep tread and wide sidewall that provides superior impact resistance. This tire features a large footprint with a massive lug-to-void ratio. It has a zig-zag tread pattern for optimal traction and handling on mixed surfaces and in severe-duty applications.

- **Tread depth** is perfect for severe applications
- **Stepped tread design** provides excellent cleanout for improved traction
- **Superior sidewall protection** provides exceptional hours of service and minimal downtime
- **High ply ratings** increase service life while reducing downtime due to cuts and punctures



Turf and Sand Loader Tires

Maintain your lush lawn by using Bobcat turf and sand tires on your next job. While other tires may gouge into and damage lawns, this tire is engineered to provide superior flotation characteristics to minimize harm and still offer excellent traction. These turf-friendly tires will not damage grass or roots, and they are great in applications such as golf courses, sugar sand, nurseries, sports grounds and cemeteries.

- **Specially designed tread** engineered to be extra ground conscious
- **Wide sidewalls** provide extra flotation on grass and sand
- **Flat profile and specially designed tread** for maximum traction and maximum flotation
- **Durable tread compound** for long life



Super-Float Loader Tires

The super-wide tread and sidewalls of super-float tires are designed to perform in soft or wet soil conditions. Super-float tires eliminate the need for an expensive and cumbersome track system. If your job requires extra flotation, super-float tires will keep you moving in applications including parks, cemeteries, golf courses, nurseries, beaches and compost yards.

- **Eighty-five percent more footprint** for turf protection
- **Low and even pressure distribution** for minimal ground disturbance
- **Super-wide sidewalls** provide extra flotation in soft or wet soil
- **Durable tread compound** for long life



Snow Tires

“Tough, versatile and agile” perfectly describes Bobcat snow tires. The narrow base provides the power and traction you require in harsh winter conditions without the need for studs, making the Bobcat snow tire the ultimate tire on ice and snow.








- **Narrow base** for extra stability and traction
- **Unique tread** designed for increased power and grip on snow and ice
- **Special cold weather compound** that remains flexible in colder temperatures
- **Load rating** designed for your Bobcat equipment



WHERE THE RUBBER HITS THE ROAD

Choosing the best tire is important for machine traction, flotation, wear and overall performance. Tires with the correct height, width and ply rating for your equipment will maintain proper operating efficiency and ensure support of maximum loads. Depend on genuine Bobcat tires for performance, reliability and superior results in all of your tough jobs.

COMPACT LOADER TIRES

TIRE	TREAD	MODEL	TIRE SIZE	PART NO.	OUTSIDE DIAMETER
Standard Duty		Skid-Steer	5.7 x 12	7519881	23.0 in. (584 mm)
		Skid-Steer	8.5 x 12	6652525	23.0 in. (584 mm)
		Skid-Steer	10 x 16.5	6729896	31.0 in. (787 mm)
Heavy Duty		Skid-Steer	5.7 x 12	6987698	22.5 in. (571.5 mm)
		Skid-Steer	8.5 x 15	6987702	27.0 in. (686 mm)
		Skid-Steer	8.5 x 15	6667890	27.0 in. (686 mm)
		Skid-Steer	10 x 16.5	7322705	31.0 in. (787 mm)
		Skid-Steer	12 x 16.5	7249602	33.0 in. (838 mm)
		Skid-Steer	14 x 17.5	7333095	36.0 in. (914 mm)
Severe Duty		Skid-Steer	10 x 16.5	6730106	31.0 in. (787 mm)
		Skid-Steer	12 x 16.5	6730108	33.0 in. (838 mm)
		Skid-Steer	14 x 16.5	7139189	36.0 in. (914 mm)
Severe-Duty All-Terrain		Skid-Steer	10 x 16.5	6987706	31.0 in. (787 mm)
		Skid-Steer	12 x 16.5	6987709	33.0 in. (838 mm)
		Skid-Steer	14 x 17.5	7305720	36.0 in. (914 mm)
Turf		Skid-Steer	8.5 x 12	7109709	23.0 in. (584 mm)
		Skid-Steer	15.5 x 16.5	6678044	33.0 in. (838 mm)
Super-Float		Skid-Steer	12 x 16.5	7211382	31.0 in. (787 mm)
		Skid-Steer	15.5 x 16.5	6730109	33.0 in. (838 mm)
Snow		Skid-Steer	7.5 x 16	7386752	32.2 in. (818 mm)
		Skid-Steer	7.5 x 16	7394702*	32.2 in. (818 mm)
		Skid-Steer	7.5 x 16	7389350*	32.2 in. (818 mm)

* Indicate tire/rim assembly part number. Please see your local Bobcat dealer for your tire and rim replacement parts.



TIRE WIDTH	RIM DIAMETER	PLY RATING	MAX. LOAD	TREAD DEPTH	TIRE WEIGHT
5.7 in. (145 mm)	12.0 in. (305 mm)	4	1450 lb. @ 60 psi	17/32.0 in. (13.5 mm)	15.3 lb. (7 kg)
8.5 in. (216 mm)	12.0 in. (305 mm)	4	1470 lb. @ 35 psi	14/32.0 in. (11 mm)	26 lb. (12 kg)
10.0 in. (254 mm)	16.5 in. (419 mm)	8	4145 lb. @ 55 psi	18/32.0 in. (14 mm)	44.5 lb. (20.2 kg)
6.0 in. (152 mm)	12.0 in. (305 mm)	4	1450 lb. @ 60 psi	19/32.0 in. (15 mm)	20.9 lb. (9.5 kg)
8.5 in. (216 mm)	15.0 in. (381 mm)	6	3924 lb. @ 45 psi	33/32.0 in. (26 mm)	37 lb. (16.8 kg)
8.5 in. (216 mm)	15.0 in. (381 mm)	8	2890 lb. @ 60 psi	15/32.0 in. (12 mm)	35 lb. (16 kg)
10.0 in. (254 mm)	16.5 in. (419 mm)	10	3930 lb. @ 55 psi	19/32.0 in. (15 mm)	52 lb. (24 kg)
12.0 in. (305 mm)	16.5 in. (419 mm)	12	5340 lb. @ 60 psi	22/32.0 in. (17 mm)	81 lb. (36.8 kg)
14.0 in. (356 mm)	17.5 in. (445 mm)	14	8850 lb. @ 80 psi	24/32.0 in. (19 mm)	102 lb. (46 kg)
10.0 in. (254 mm)	16.5 in. (419 mm)	10	3500 lb. @ 45 psi	44/32.0 in. (35 mm)	75 lb. (34 kg)
12.0 in. (305 mm)	16.5 in. (419 mm)	12	4201 lb. @ 40 psi	44/32.0 in. (35 mm)	95 lb. (43 kg)
14.0 in. (356 mm)	17.5 in. (445 mm)	14	5260 lb. @ 35 psi	44/32.0 in. (35 mm)	130 lb. (59 kg)
10.0 in. (254 mm)	16.5 in. (419 mm)	10	4700 lb. @ 75 psi	39/32.0 in. (29 mm)	74 lb. (33 kg)
12.0 in. (305 mm)	16.5 in. (419 mm)	12	6300 lb. @ 80 psi	43/32.0 in. (34 mm)	103 lb. (47 kg)
14.0 in. (356 mm)	17.5 in. (445 mm)	14	8550 lb. @ 80 psi	43/32.0 in. (34 mm)	146 lb. (66 kg)
8.5 in. (216 mm)	12.0 in. (305 mm)	6	1440 lb. @ 34 psi	18/32.0 in. (14 mm)	19 lb. (9 kg)
15.5 in. (394 mm)	16.5 in. (419 mm)	10	4730 lb. @ 32 psi	18/32.0 in. (14 mm)	83 lb. (38 kg)
12.0 in. (305 mm)	16.5 in. (419 mm)	10	4460 lb. @ 55 psi	19/32.0 in. (15 mm)	61 lb. (28 kg)
15.5 in. (394 mm)	16.5 in. (419 mm)	12	4990 lb. @ 35 psi	26/32.0 in. (21 mm)	94 lb. (43 kg)
8.7 in. (221 mm)	16.0 in. (406 mm)	12	3195 lb. @ 87 psi	18/32.0 in. (14 mm)	49 lb. (22 kg)
8.7 in. (221 mm)	16.0 in. (406 mm)	12	3195 lb. @ 87 psi	18/32.0 in. (14 mm)	49 lb. (22 kg)
8.7 in. (221 mm)	16.0 in. (406 mm)	12	3195 lb. @ 87 psi	18/32.0 in. (14 mm)	49 lb. (22 kg)



COMPACT LOADER TIRES

TIRE	TREAD	MODEL	PNEUMATIC EQUIVALENT	PART NO.	BASE	RIM COLOR	BOLT CIRCLE	OUTSIDE DIAMETER
Solid Flex		Skid-Steer Loader	5.7 x 12	7365906	Right	Orange	4.5 in. (114 mm)	21.7 in. (550 mm)
		Skid-Steer Loader	5.7 x 12	7365907	Left	Orange	4.5 in. (114 mm)	21.7 in. (550 mm)
		Skid-Steer Loader	5.7 x 12	7365903	Right	Gray	4.5 in. (114 mm)	21.7 in. (550 mm)
		Skid-Steer Loader	5.7 x 12	7365904	Left	Gray	4.5 in. (114 mm)	21.7 in. (550 mm)
		Skid-Steer Loader	8.5 x 15	7023562	Left	Orange	6.0 in. (150 mm)	27.0 in. (685 mm)
		Skid-Steer Loader	8.5 x 15	7023563	Right	Orange	6.0 in. (150 mm)	27.0 in. (685 mm)
		Skid-Steer Loader	10 x 16.5	6988512	Left	Orange	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	10 x 16.5	6988513	Right	Orange	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	10 x 16.5	7295717	Left	Orange	8.0 in. (203 mm)	31.0 in. (787 mm)
		Skid-Steer Loader	10 x 16.5	7295718	Right	Orange	8.0 in. (203 mm)	31.0 in. (787 mm)
		Skid-Steer Loader	10 x 16.5	7295725	Left	Orange	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	10 x 16.5	7295726	Right	Orange	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	10 x 16.5	7246212	Left	Orange	8.0 in. (203 mm)	31.0 in. (787 mm)
		Skid-Steer Loader	10 x 16.5	7246213	Right	Orange	8.0 in. (203 mm)	31.0 in. (787 mm)
		Skid-Steer Loader	10 x 16.5	7296992	Left	Gray	8.0 in. (203 mm)	31.0 in. (787 mm)
		Skid-Steer Loader	10 x 16.5	7296993	Right	Gray	8.0 in. (203 mm)	31.0 in. (787 mm)
		Skid-Steer Loader	12 x 16.5	7246214	Left	Orange	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7246215	Right	Orange	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7296998	Left	Gray	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7296999	Right	Gray	8.0 in. (203 mm)	33.0 in. (838 mm)
		All-Wheel Loader	12 x 16.5	7312251	Left	Orange	10.75 in. (270 mm)	33.0 in. (838 mm)
		All-Wheel Loader	12 x 16.5	7312252	Right	Orange	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7296996	Left	Gray	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7296997	Right	Gray	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	6988515	Left	Orange	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	6988516	Right	Orange	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7024823	Left	Orange	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7024824	Right	Orange	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	14 x 17.5	7024853	Left	Orange	10.75 in. (270 mm)	37.0 in. (925 mm)
		Skid-Steer Loader	14 x 17.5	7024854	Right	Orange	10.75 in. (270 mm)	37.0 in. (925 mm)
		Skid-Steer Loader	14 x 17.5	7312253	Left	Orange	10.75 in. (270 mm)	36.0 in. (914 mm)
		Skid-Steer Loader	14 x 17.5	7312254	Right	Orange	10.75 in. (270 mm)	36.0 in. (914 mm)
Skid-Steer Loader	14 x 17.5	7297000	Left	Gray	10.75 in. (270 mm)	36.0 in. (914 mm)		
Skid-Steer Loader	14 x 17.5	7297001	Right	Gray	10.75 in. (270 mm)	36.0 in. (914 mm)		

TIRE WIDTH	RIM DIAMETER	TREAD DEPTH	WEIGHT
5.31 in. (135 mm)	12.0 in. (305 mm)	2.0 in. (51 mm)	93 lb. (42 kg)
5.31 in. (135 mm)	12.0 in. (305 mm)	2.0 in. (51 mm)	93 lb. (42 kg)
5.31 in. (135 mm)	12.0 in. (305 mm)	2.0 in. (51 mm)	93 lb. (42 kg)
5.31 in. (135 mm)	12.0 in. (305 mm)	2.0 in. (51 mm)	93 lb. (42 kg)
8.0 in. (200 mm)	15.0 in. (381 mm)	2.0 in. (51 mm)	141 lb. (64 kg)
8.0 in. (200 mm)	15.0 in. (381 mm)	2.0 in. (51 mm)	141 lb. (64 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
9.0 in. (232 mm)	20.0 in. (508 mm)	2.7 in. (68 mm)	233 lb. (106 kg)
9.0 in. (232 mm)	20.0 in. (508 mm)	2.7 in. (68 mm)	233 lb. (106 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
9.3 in. (237 mm)	20.0 in. (508 mm)	1.3 in. (33 mm)	233 lb. (106 kg)
9.3 in. (237 mm)	20.0 in. (508 mm)	1.3 in. (33 mm)	233 lb. (106 kg)
9.3 in. (237 mm)	20.0 in. (508 mm)	1.3 in. (33 mm)	233 lb. (106 kg)
9.3 in. (237 mm)	20.0 in. (508 mm)	1.3 in. (33 mm)	233 lb. (106 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
11.3 in. (287 mm)	20.0 in. (508 mm)	1.6 in. (39 mm)	293 lb. (133 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	271 lb. (123 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	271 lb. (123 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	271 lb. (123 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	271 lb. (123 kg)
14.0 in. (355 mm)	20.0 in. (508 mm)	3.5 in. (88 mm)	436 lb. (198 kg)
14.0 in. (355 mm)	20.0 in. (508 mm)	3.5 in. (88 mm)	436 lb. (198 kg)
12.6 in. (320 mm)	20.0 in. (508 mm)	1.7 in. (42 mm)	373 lb. (169 kg)
12.6 in. (320 mm)	20.0 in. (508 mm)	1.7 in. (42 mm)	373 lb. (169 kg)
12.6 in. (320 mm)	20.0 in. (508 mm)	1.7 in. (42 mm)	373 lb. (169 kg)
12.6 in. (320 mm)	20.0 in. (508 mm)	1.7 in. (42 mm)	373 lb. (169 kg)







SOLID LOADER TIRES

Solid Flex Tires

- **Built for long life** in daily applications requiring a solid tire
- **Durable tread compound** for long life and decreased downtime and maintenance
- **Specifically engineered sidewalls and apertures** that prevent cutting and snagging and provide improved comfort
- **Non-marking orange tread option** is ideal when no marking is wanted on hard surfaces



COMPACT LOADER TIRES

TIRE	TREAD	MODEL	PNEUMATIC EQUIVALENT	PART NO.	BASE	RIM COLOR	BOLT CIRCLE	OUTSIDE DIAMETER
Solid Flex Cushion		Skid-Steer Loader	10 x 16.5	46897637	Left	Black	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	10 x 16.5	46897638	Right	Black	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	12 x 16.5	46897598	Left	Black	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	46897599	Right	Black	8.0 in. (203 mm)	33.0 in. (838 mm)
Solid Non-Directional Cushion		Skid-Steer Loader	10 x 16.5	46897639	ND	Orange	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	12 x 16.5	46897601	ND	Orange	8.0 in. (203 mm)	33.0 in. (845 mm)
Solid Severe-Duty Non-Directional		Skid-Steer Loader	10 x 16.5	7313443	ND	Orange	8.0 in. (203 mm)	31.0 in. (787 mm)
		Skid-Steer Loader	12 x 16.5	7313441	ND	Orange	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7313442	ND	Orange	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	14 x 17.5	7313440	ND	Orange	10.75 in. (270 mm)	36.0 in. (914 mm)
Solid Flex Offset		Skid-Steer Loader	10 x 16.5	7295725	Left	Orange	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	10 x 16.5	7295726	Right	Orange	8.0 in. (203 mm)	30.0 in. (762 mm)
Solid Flex Non-Marking		Skid-Steer Loader	10 x 16.5	7022983	Left	Gray	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	10 x 16.5	7022984	Right	Gray	8.0 in. (203 mm)	30.0 in. (762 mm)
		Skid-Steer Loader	12 x 16.5	7022985	Left	Gray	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7022986	Right	Gray	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7277216	Left	Gray	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7277217	Right	Gray	10.75 in. (270 mm)	33.0 in. (838 mm)
Solid Flex Super Smooth		Skid-Steer Loader	10 x 16.5	7312257	ND	Orange	8.0 in. (203 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	12 x 16.5	7312256	ND	Orange	10.75 in. (270 mm)	33.0 in. (838 mm)
		Skid-Steer Loader	14 x 17.5	7313439	ND	Orange	10.75 in. (270 mm)	36.0 in. (914 mm)



TIRE WIDTH	RIM DIAMETER	TREAD DEPTH	WEIGHT
10.0 in. (250 mm)	20.0 in. (508 mm)	1.26 in. (32 mm)	187 lb. (85 kg)
10.0 in. (250 mm)	20.0 in. (508 mm)	1.26 in. (32 mm)	187 lb. (85 kg)
12.0 in. (300 mm)	20.0 in. (508 mm)	1.3 in. (33 mm)	294 lb. (133.4 kg)
12.0 in. (300 mm)	20.0 in. (508 mm)	1.3 in. (33 mm)	294 lb. (133.4 kg)
9.5 in. (241 mm)	16.0 in. (406 mm)	1.2 in. (30.6 mm)	213 lb. (97 kg)
11.6 in. (294 mm)	20.0 in. (508 mm)	1.45 in. (36.8 mm)	337 lb. (153 kg)
9.0 in. (237 mm)	20.0 in. (508 mm)	2.0 in. (51 mm)	247 lb. (112 kg)
11.0 in. (287 mm)	20.0 in. (508 mm)	2.0 in. (51 mm)	295 lb. (135 kg)
11.0 in. (287 mm)	20.0 in. (508 mm)	2.0 in. (51 mm)	295 lb. (135 kg)
13.0 in. (326 mm)	20.0 in. (508 mm)	2.0 in. (51 mm)	388 lb. (176 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
10.0 in. (250 mm)	16.0 in. (406 mm)	2.7 in. (68 mm)	198 lb. (90 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	273 lb. (124 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	273 lb. (124 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	273 lb. (124 kg)
12.0 in. (300 mm)	16.0 in. (406 mm)	3.3 in. (85 mm)	273 lb. (124 kg)
9.0 in. (237 mm)	20.0 in. (508 mm)	0 in. (0 mm)	247 lb. (112 kg)
11.0 in. (287 mm)	20.0 in. (508 mm)	0 in. (0 mm)	313 lb. (142 kg)
13.0 in. (326 mm)	20.0 in. (508 mm)	0 in. (0 mm)	403 lb. (183 kg)

SOLID LOADER TIRES



Solid Severe-Duty Non-Directional Loader Tires

- **Tread depth** is ideal for severe applications
- **Aggressive non-directional unique tread design** allows tire to be interchangeable from left or right on your loader
- **Sidewall aperture design** provides improved rider comfort
- **Durable tread compound** improves ride quality and reduces cracking



Solid Super Smooth Loader Tires

- **Sidewall aperture design** provides improved rider quality and comfort
- **Specifically engineered sidewalls** that prevent cutting and snagging
- **Built for long life** in daily applications requiring a solid tire
- **Durable tread compound** for long life and decreased downtime and maintenance



ARTICULATING TRACTOR TIRES

The articulating tractor tire is designed with an open non-directional tread pattern, which provides great traction and superior wear characteristics on a variety of surfaces. The tread's wide footprint and high rubber-to-void ratio provides excellent stability, puncture resistance, wear resistance and long tire life.

TIRE	MODEL	PART NO.	OUTSIDE DIAMETER	TIRE WIDTH	RIM DIAMETER	PLY RATING	MAX. LOAD	TIRE WEIGHT
Standard	AT450	4167168-01	20.6 in. (523 mm)	11.2 in. (284.5 mm)	10 in. (254 mm)	6	1345 lb.	22.8 lb. (10.3 kg)



COMPACT TRACTOR TIRES

Agricultural Tires

Agricultural tires feature deep lugs for optimal traction and self-cleaning in soft soil and mud. They deliver more power to the ground when towing heavy loads or pulling implements.

Industrial Tires

Designed for maximum traction and versatility for a wide range of applications, industrial tires provide long wear and outstanding protection against punctures. With wider tread than agricultural tires and deeper lugs than turf tires, industrial tires keep operators moving in all ground conditions.

Turf Tires

Turf tires offer excellent traction while minimizing damage and repairs to lawns and finished surfaces.



TIRE	MODEL	PART NO.	BASE	OUTSIDE DIAMETER	TIRE WIDTH	RIM DIAMETER	PLY RATING	TIRE WEIGHT
Ag	1021, 1025	7460210	Front	18 in. (454.7 mm)	8.5 in. (215.9 mm)	10 in. (254 mm)	4	12.5 lb. (5.7 kg)
		7460211	Rear	25.2 in. (660.4 mm)	12 in. (305 mm)	12 in. (305 mm)	4	30.6 lb. (13.8 kg)
	2025, 2035, 2040, 2525, 2535, 2540	7473331	Front	29.2 in. (742 mm)	7 in. (178 mm)	16 in. (406 mm)	6	30.9 lb. (14 kg)
		7473330	Rear	43.7 in. (1110 mm)	11.2 in. (284.5 mm)	24 in. (610 mm)	6	77 lb. (35 kg)
	4045, 4050, 4055, 4058, 5545, 5550, 5555, 5558	7473434	Front	31 in. (790 mm)	8 in. (203 mm)	16 in. (406 mm)	6	36 lb. (16 kg)
		7473433	Rear	47.6 in. (1210 mm)	16 in. (406 mm)	24 in. (610 mm)	8	115 lb. (52 kg)
Industrial	1021, 1025	7460206	Front	18 in. (454.7 mm)	8.5 in. (215.9 mm)	10 in. (254 mm)	4	13 lb. (6 kg)
		7460207	Rear	26 in. (660.4 mm)	12 in. (305 mm)	12 in. (305 mm)	4	29 lb. (13 kg)
	2025, 2035, 2040, 2525, 2535, 2540	7473213	Front	25.7 in. (653 mm)	8.5 in. (215.9 mm)	25 in. (635 mm)	6	24.4 lb (11 kg)
		7473215	Rear	40 in. (1016 mm)	15 in. (381 mm)	19.5 in. (495 mm)	6	104.5 lb. (47.4 kg)
	4045, 4050, 4055, 4058, 5545, 5550, 5555, 5558	7473430	Front	30 in. (770 mm)	10 in. (254 mm)	16.5 in. (419 mm)	6	40 lb (18 kg)
		7473429	Rear	48.9 in. (1241 mm)	17.5 in. (444.5 mm)	24 in. (610 mm)	6	129 lb (58.6 kg)
Turf	1021, 1025	7460208	Front	18 in. (454.7 mm)	8.5 in. (215.9 mm)	10 in. (254 mm)	4	11 lb. (5 kg)
		7460209	Rear	25.2 in. (640 mm)	12 in. (305 mm)	12 in. (305 mm)	4	25.6 lb. (11.6 kg)
	2025, 2035, 2040, 2525, 2535, 2540	7473327	Front	27 in. (686 mm)	8.5 in. (215.9 mm)	15 in. (381 mm)	6	29.5 lb. (13.4 kg)
		7473326	Rear	41 in. (1064 mm)	17.5 in. (444.5 mm)	20 in. (508 mm)	4	101 lb. (46 kg)
	4045, 4050, 4055, 4058, 5545, 5550, 5555, 5558	7473335	Front	30.5 in. (775 mm)	10 in. (254 mm)	16.5 in. (419 mm)	8	55 lb. (25 kg)
		7473334	Rear	48.8 in. (1240 mm)	17.5 in. (444.5 mm)	24 in. (610 mm)	8	153 lb. (69.5 kg)

COMPACT WHEEL LOADER TIRES

The Bobcat compact wheel loader (CWL) versatile block tread design enables high performances on snow-covered or sandy terrains. The tread pattern is an optimized on/off road pattern with shoulder lugs for traction in the fields, and the basic directional lug design, divided by separated blocks, provides a good grip on soft surfaces. In addition, the high number of blocks and rubber-to-void tread ratio enable long tread wear life and low rolling resistances during transport operation on hard surfaces. Uniform ground pressure distribution and tread wear are provided by a steel-belted carcass structure, which provides the most efficient puncture protection.

TIRE	MODEL	PART NO.	OUTSIDE DIAMETER	TIRE WIDTH	RIM DIAMETER	MAX. LOAD	TIRE WEIGHT
Standard	L65, L75	7331619	38.1 in. (969 mm)	14.2 in. (361 mm)	18 in. (457 mm)	4800 lb. (2177 kg)	106 lb. (48.2 kg)
	L85	7331628	40.3 in. (1024 mm)	16.1 in. (409 mm)	18 in. (457 mm)	5680 lb. (2576 kg)	115 lb. (52.5 kg)
	L65, L75, L85	7331594	39.4 in. (1001 mm)	13.5 in. (342.9 mm)	18 in. (457 mm)	4940 lb. (2240 kg)	110 lb. (49.8 kg)
	L65, L75, L85, L95	7331578	42.4 in. (1076 mm)	16 in. (406 mm)	20 in. (508 mm)	6000 lb. (2721 kg)	135 lb. (61.4 kg)
Ag	L95	7253906	43 in. (1085 mm)	17.4 in. (442 mm)	20 in. (508 mm)	7667 lb. (3477 kg)	143 lb. (65 kg)



SMALL ARTICULATED LOADER TIRES

Standard Tires

Standard tires give you good traction for a variety of challenging jobs.

Tractor Tires

Tractor tires give you a more aggressive tread that powers your machine through soft or wet ground.

Turf Tires

Turf tires provide the best combination of smooth maneuverability and turf-friendly traction for sensitive ground.



Standard tire

Turf tire

TIRE	MODEL	PART NO.	TIRE SIZE	OUTSIDE DIAMETER	TIRE WIDTH	RIM DIAMETER	PLY RATING	MAX. LOAD	TIRE WEIGHT
Standard	L23	7519881	5.7 x 12	23 in. (584 mm)	5.7 in. (145 mm)	12 in. (305 mm)	4	1450 lb. (658 kg)	17 lb. (8 kg)
Tractor	L28	7345776	12 x 12	26 in. (660 mm)	12 in. (305 mm)	12 in. (305 mm)	8	3000 lb. (1361 kg)	35 lb. (16 kg)
Turf	L23, L28	7346387	8.5 x 12	23 in. (584 mm)	8.5 in. (216 mm)	12 in. (305 mm)	10	2380 lb. (1080 kg)	24 lb. (11 kg)
		7345984	10.5 x 12	23 in. (584 mm)	10.5 in. (267 mm)	12 in. (305 mm)	8	2138 lb. (970 kg)	23 lb. (10.5 kg)
		7345775	12 x 12	26 in. (660 mm)	12 in. (305 mm)	12 in. (305 mm)	8	3053 lb. (1385 kg)	33 lb. (15 kg)



TELEHANDLER TIRES

Agricultural/Industrial Tires

These tires feature deep lugs for the best traction, stability and balance crucial for the performance and proper operation of your telehandler.



TIRE	MODEL	PART NO.	OUTSIDE DIAMETER	TIRE WIDTH	RIM DIAMETER	PLY RATING	MAX. LOAD	WEIGHT
Ag/Industrial	V519, TL519, TL619	7253906	43 in. (1085 mm)	17.4 in. (442 mm)	20 in. (508 mm)	16	7667 lb. (3477 kg)	161 lb. (73 kg)
	V518, V623, V723, VR518, VR530C, VR723	7160222	42 in. (1067 mm)	16 in. (406 mm)	20 in. (508 mm)	15	7385 lb. (3350 kg)	157 lb. (71 kg)
	V518, V723, VR518, VR530C, VR723	7225564	43 in. (1085 mm)	15.9 in. (403 mm)	20 in. (508 mm)	14	7050 lb. (3198 kg)	161 lb. (73 kg)
	V638, V723, V923, VR530C, VR638, VR723, TL723, TL923	7230672	49 in. (1245 mm)	15.8 in. (401 mm)	24 in. (610 mm)	20	8818 lb. (4000 kg)	198 lb. (89 kg)



TOOLCAT UTILITY WORK MACHINE TIRES

Float Tires

The wide sidewalls of the float tires are designed to perform in soft or wet soil conditions.

Shown on machine to the right.

Standard Tires

These versatile tires perform great in a variety of applications.

Turf Tires

Turf tires protect the ground from damage during landscaping jobs.

Snow Tires

Snow tires provide the power and traction required in harsh winter conditions.



TIRE	MODEL	PART NO.	OUTSIDE DIAMETER	TIRE WIDTH	RIM DIAMETER	PLY RATING	MAX. LOAD	TIRE WEIGHT
Turf	5600	6682461	27 in. (686 mm)	10.5 in. (267 mm)	15 in. (381 mm)	10	2200 lb. (998 kg)	38 lb. (17 kg)
Float	5600, 5610	7211382	31 in. (787 mm)	12 in. (305 mm)	16.5 in. (419 mm)	10	4460 lb. (2023 kg)	61 lb. (28 kg)
Standard	5600, 5610, UW53, UW56	7023289	27 in. (686 mm)	10.5 in. (267 mm)	15 in. (381 mm)	8	3130 lb. (1420 kg)	43 lb. (19 kg)
		7023288	29 in. (737 mm)	10.5 in. (267 mm)	15 in. (381 mm)	10	4470 lb. (2028 kg)	47 lb. (21 kg)
Turf	5600, 5610, UW53, UW56	7166360	29 in. (737 mm)	12.5 in. (318 mm)	15 in. (381 mm)	8	2150 lb. (975 kg)	48 lb. (22 kg)
Snow Tire		7425595	29.7 in. (754.4 mm)	7 in. (178 mm)	15 in. (381 mm)	10	2335 lb. (1059 kg)	32 lb. (14.5 kg)
Snow Tire Assy		7425593	29.7 in. (754.4 mm)	7 in. (178 mm)	15 in. (381 mm)	10	2335 lb. (1059 kg)	62 lb. (28.6 kg)



UTILITY VEHICLE TIRES

All-Terrain

Keep moving in soft and wet soil conditions with Bobcat mud tires. This tire provides good float, aggressive and wide tread, and increased durability.



All-Season

Aggressive staggered block pattern improves surface contact and helps with soft and uneven terrain traction, boosting driver control. It effectively self-cleans rocks stuck between the tread and eliminates mud and snow to prevent them from blocking surface contact.

Shown on machine to the right.

General Purpose

Great tread depth and more rubber on the contact surface provide increased traction, improved puncture resistance and longer tire life. The shoulder design minimizes turf damage.



Mud

Durable in extreme conditions with heavy loads, these tires provide confidence in deep mud. Aggressive tread patterns are designed for any trail, whether in the woods or the desert.



TIRE	MODEL
All-Terrain	3200, 3400, 3400XL, 3600, 3650, UV34, UV34XL
Mud	3400, 3400XL, 3600, 3650, UV34, UV34XL
General Purpose	3400, 3400XL, 3600, 3650, UV34, UV34XL
All-Season	UV34, UV34XL



PART NO.	BASE	OUTSIDE DIAMETER	TIRE WIDTH	RIM DIAMETER	PLY RATING	MAX LOAD	TIRE WEIGHT
7027146	Front	25 in. (635 mm)	10 in. (254 mm)	12 in. (305 mm)	4	1005 lb. (455.8 kg)	21.2 lb. (9.6 kg)
7027147	Rear	25 in. (635 mm)	11 in. (279 mm)	12 in. (305 mm)	4	1055 lb. (478.5 kg)	22 lb. (9.98 kg)
7307679	Front	26 in. (660 mm)	9 in. (229 mm)	12 in. (305 mm)	8	970 lb. (440 kg)	26.2 lb. (12 kg)
7307680	Rear	26 in. (660 mm)	11 in. (279 mm)	12 in. (305 mm)	8	1179 lb. (535 kg)	31 lb. (14 kg)
7027654	Front	25 in. (635 mm)	10 in. (254 mm)	12 in. (305 mm)	4	1675 lb. (759.8 kg)	22 lb. (10 kg)
7027655	Rear	25 in. (635 mm)	11 in. (279 mm)	12 in. (305 mm)	4	1786 lb. (810 kg)	23.6 lb. (10.7 kg)
7360380	Front/Rear	26 in. (660 mm)	10 in. (254 mm)	12 in. (305 mm)	8	1390 lb. (630 kg)	28 lb. (13 kg)









Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.



Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2025 Bobcat Company. All rights reserved.

BOBCAT COMPANY • 250 EAST BEATON DRIVE • WEST FARGO, ND 58078 • BOBCAT.COM

DOOSAN

P005 (03/25)
EP-1M-0325-19736-F