



# PUSHER PLOWS & AUTOMATIC WING PLOW FOR LOADERS & SKID-STEERS

“

MORE JOBS. **DONE FASTER.**





## EXPAND YOUR OPERATIONS

WESTERN® snow removal attachments are built for unrivaled plowing versatility to help you get more jobs done faster.

Here are some benefits of using loaders during winter storms:

- Easily accepts attachments
- Highly maneuverable
- Handles large quantities of snow
- Enhanced visibility from elevated cab
- Highly visible on the work site

Keep these factors in mind to determine compatibility with your loader:

- Type of loader
- Coupler or mount type
- Horsepower
- Maximum operating weight

**MORE JOBS. DONE FASTER.**



## WHAT'S BEST FOR YOUR SITUATION

Leveraging your fleet for snow removal means it's up to you to help keep the world moving through winter's worst—and that means ensuring you have the type of plow your equipment and work needs. Because the less you worry about whether or not you have the right equipment, the more time you have to clear lots. At Western Products, we have a plow model for every commercial need and application, designed and engineered to be compatible with the types of loaders your operation uses.

### TRACE™ EDGE TECHNOLOGY

The terrain-response advanced cutting edge found on the PILE DRIVER™ pusher models is comprised of independent, 2' sections that raise, oscillate, and trip—delivering a clean scrape and reducing the amount of salt required.



### MODULAR DESIGN

Strategic engineering of the 14' and 16' PILE DRIVER™ and PILE DRIVER XL pusher models allows for easy removal of the 2' blade extensions on either side. This reduces the width of the 14' unit to 10' and the width of the 16' unit to 12', allowing you to get the most out of your pusher investment.



### 75 YEARS OF EXPERTISE

Western Products offers a full line of CONTRACTOR GRADE® snowplows for commercial snow plowing. As a leader in the snow and ice control industry, we're proud to empower your team and fleet with dedicated local dealer support, detailed after-sales documentation, and service parts.



### U.S. MANUFACTURING

WESTERN® plows are manufactured in the U.S.—many right in Milwaukee, WI—and use the same hydraulics manufacturing line that outfits WESTERN truck plows. This allows us to control the design and quality for a superior product, and easy access to maintenance parts.

# PILE DRIVER™ XL

## HYDRAULIC-WING PUSHER PLOWS

### UNMATCHED PLOWING VERSATILITY.

The PILE DRIVER XL hydraulic-wing pusher plow lets you maximize the performance of your operator. Hydraulically actuated 3' wings are independently controlled, allowing for countless plowing configurations within the 180-degree arc of travel. This allows maximum width for plowing wide open spaces, and optimal configurations when working in narrow spaces or around obstacles. The TRACE™ edge moves more snow with every pass, requiring less salt.



# PILE DRIVER™

## FIXED-WING PUSHER PLOWS

### GO BIG WITH SNOW REMOVAL.

The PILE DRIVER fixed-wing pusher plow moves more snow with every pass due to TRACE edge technology that contours to the plowable surface. This requires less salt and reduces total cost of ownership by allowing you to replace only the 2' cutting edge sections that show wear. Maximize performance and cost of ownership.



FEATURES	DESCRIPTION	FEATURES	DESCRIPTION
<b>BLADE WIDTH</b>	8', 10', 12', 14**, 16**	<b>BLADE WIDTH</b>	8', 10', 12', 14**, 16**
<b>BLADE HEIGHT</b>	30", 36", 42"	<b>BLADE HEIGHT</b>	30", 36", 42"
<b>BLADE CONSTRUCTION</b>	Powder-Coated Steel	<b>BLADE CONSTRUCTION</b>	Powder-Coated Steel
<b>WING TYPE</b>	3' Hydraulically Controlled Wing with TRACE™ Wing Technology	<b>WING TYPE</b>	3' Fixed Wing with Reversible Bolt-On Shoe for Extended Life
<b>WING MOVEMENT</b>	Infinitely variable along 180-degree path of travel	<b>WING MOVEMENT</b>	—
<b>VEHICLE COMPATIBILITY</b>	Skid-Steer, Tractor & Wheel Loader	<b>VEHICLE COMPATIBILITY</b>	Skid-Steer, Tractor & Wheel Loader
<b>CUTTING EDGE TECHNOLOGY</b>	TRACE — Terrain Response Advanced Cutting Edge	<b>CUTTING EDGE TECHNOLOGY</b>	TRACE — Terrain Response Advanced Cutting Edge
<b>CUTTING EDGE MATERIAL</b>	High-Carbon Steel with Carbide Inserts	<b>CUTTING EDGE MATERIAL</b>	High-Carbon Steel with Carbide Inserts
<b>MOUNT TYPE</b>	Skid-Steer Attach Plate, Coupler	<b>MOUNT TYPE</b>	Skid-Steer Attach Plate, Coupler

\*\*14' can become 10' and 16' can become 12' by removing the 2' extensions on either side of the pusher box. Tools are required and should be done at a dealership or in a shop.

### PILE DRIVER XL INDEPENDENT WING MOVEMENT – 180 DEGREES OF INFINITE WING POSITIONS



# PRODIGY™

## WINGED SNOWPLOW

### LESS TRAINING. LESS TIME.

Get all of the benefits of a winged plow with the simple control of a straight blade with the WESTERN® PRODIGY automatic winged snowplow. The wings automatically adjust from scoop mode to windrow position when angled to provide the most efficient plowing configuration for the job. This model adds versatility to your fleet without spending time training operators on how to use new equipment, keeping productivity and profitability high.



FEATURES	DESCRIPTION
<b>BLADE WIDTH</b>	Scoop: 8'7"   Wings Pinned: 9'8"
<b>BLADE HEIGHT</b>	29.5"
<b>BLADE CONSTRUCTION</b>	Powder-Coated Steel
<b>WING TYPE</b>	14.2" Wing with ½" Steel Cutting Edge
<b>WING MOVEMENT</b>	Automatic Wing Movement
<b>VEHICLE COMPATIBILITY</b>	Skid-Steer
<b>CUTTING EDGE TECHNOLOGY</b>	Full Blade Trip
<b>CUTTING EDGE MATERIAL</b>	0.5" x 6" steel
<b>MOUNT TYPE</b>	Oscillating Skid-Steer Mount

### PRODIGY PLOWING CONFIGURATIONS





# FIND THE PLOWS THAT BEST FIT YOUR LOADER

Quick Match lets you easily identify which WESTERN® plows will fit your vehicle, based on your vehicle's unique specifications. For future reference and comparison purposes, you can save your selected plow in our system database, print out the information or email it to your inbox. Find the WESTERN snowplows that will help you get more jobs done by visiting [westernplows.com/quick-match](http://westernplows.com/quick-match).



## PILE DRIVER™ XL HYDRAULIC-WING PUSHER PLOWS

PLOW TYPE	PUSHER						
<b>MOLDBOARD OPTIONS</b>	Powder-Coated Steel						
<b>BLADE WIDTH</b>	8' (2.44 m)	10' (3.05 m)	8' (2.44 m)	10' (3.05 m)	12' (3.66 m)	14' (4.27 m)*	16' (4.88 m)*
<b>BLADE WIDTH (WINGS EXTENDED)</b>	14' (4.27 m)	16' (4.88 m)	14' (4.27 m)	16' (4.88 m)	18' (5.49 m)	20' (6.10 m)	22' (6.71 m)
<b>APPROX. WEIGHT (WITHOUT MOUNT)</b>	2,533 lb (1,148.9 kg)	2,770 lb (1,256.5 kg)	2,628 lb (1,192.0 kg)	2,822 lb (1,280.0 kg)	3,197 lb (1,450.1 kg)	3,666 lb (1,662.9 kg)	3,855 lb (1,748.6 kg)
<b>HORSEPOWER COMPATIBILITY</b>	45+ hp (Skid-Steer)	60+ hp (Skid-Steer)	40+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	50+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	100+ hp (Wheel Loader & Backhoe)	140+ hp (Wheel Loader & Backhoe)	140+ hp (Wheel Loader & Backhoe)
<b>BLADE HEIGHT</b>	30" (76.20 cm)	30" (76.20 cm)	36" (91.44 cm)	36" (91.44 cm)	42" (106.68 cm)	42" (106.68 cm)	42" (106.68 cm)
<b>SIDE PLATE WIDTH</b>	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)
<b>SIDE PLATE HEIGHT</b>	30" (76.20 cm)	30" (76.20 cm)	36" (91.44 cm)	36" (91.44 cm)	42" (106.68 cm)	42" (106.68 cm)	42" (106.68 cm)
<b>MOLDBOARD RADIUS</b>	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)	46" (116.84 cm)	46" (116.84 cm)	46" (116.84 cm)
<b>APPROX. SNOW CAPACITY</b>	75 ft³ (2.12 m³)	94 ft³ (2.66 m³)	108 ft³ (3.06 m³)	135 ft³ (3.82 m³)	219 ft³ (6.20 m³)	255 ft³ (7.22 m³)	281 ft³ (7.96 m³)
<b>CUTTING EDGE TECHNOLOGY</b>	TRACE™ — Terrain Response Advanced Cutting Edge						
<b>CUTTING EDGE MATERIAL</b>	High-Carbon Steel with Carbide Inserts						
<b>MOUNT TYPE</b>	Skid-Steer Attach Plate	Skid-Steer Attach Plate	Skid-Steer Attach Plate / Coupler	Skid-Steer Attach Plate / Coupler	Coupler	Coupler	Coupler

\*14' can become 10' and 16' can become 12' by removing the 2' extensions on either side of the pusher box. Tools are required and should be done at a dealership or in a shop.

## PILE DRIVER™ FIXED-WING PUSHER PLOWS



PLOW TYPE	PUSHER						
<b>MOLDBOARD OPTIONS</b>	Powder-Coated Steel						
<b>BLADE WIDTH</b>	8' (2.44 m)	10' (3.05 m)	8' (2.44 m)	10' (3.05 m)	12' (3.66 m)	14' (4.27 m)*	16' (4.88 m)*
<b>APPROX. WEIGHT (WITHOUT MOUNT)</b>	2,127 lb (964.63 kg)	2,249 lb (1,019.95 kg)	2,221 lb (1,007.26 kg)	2,377 lb (1,078.00 kg)	2,644 lb (1,199.09 kg)	2,907 lb (1,318.37 kg)	3,170 lb (1,437.64 kg)
<b>HORSEPOWER COMPATIBILITY</b>	45+ hp (Skid-Steer)	60+ hp (Skid-Steer)	40+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	50+ hp (Tractor) & 60+ hp (Wheel Loader & Backhoe)	100+ hp (Wheel Loader & Backhoe)	140+ hp (Wheel Loader)	140+ hp (Wheel Loader)
<b>BLADE HEIGHT</b>	30" (76.2 cm)	30" (76.2 cm)	36" (91.44 cm)	36" (91.44 cm)	42" (106.68 cm)	42" (106.68 cm)	42" (106.68 cm)
<b>SIDE PLATE WIDTH</b>	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)
<b>SIDE PLATE HEIGHT</b>	30" (76.2 cm)	30" (76.2 cm)	36" (91.44 cm)	36" (91.44 cm)	42" (106.68 cm)	42" (106.68 cm)	42" (106.68 cm)
<b>MOLDBOARD RADIUS</b>	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)	46" (116.84 cm)	46" (116.84 cm)	46" (116.84 cm)
<b>APPROX. SNOW CAPACITY</b>	75 ft³ (2.14 m³)	94 ft³ (2.68 m³)	108 ft³ (3.06 m³)	135 ft³ (3.82 m³)	219 ft³ (6.19 m³)	255 ft³ (7.2 m³)	291 ft³ (8.3 m³)
<b>CUTTING EDGE TECHNOLOGY</b>	TRACE™ — Terrain Response Advanced Cutting Edge						
<b>CUTTING EDGE MATERIAL</b>	High-Carbon Steel with Carbide Inserts						
<b>MOUNT TYPE</b>	Skid-Steer Attach Plate	Skid-Steer Attach Plate	Skid-Steer Attach Plate / Coupler	Skid-Steer Attach Plate / Coupler	Coupler	Coupler	Coupler

\*14' can become 10' and 16' can become 12' by removing the 2' extensions on either side of the pusher box. Tools are required and should be done at a dealership or in a shop.

## PRODIGY™ WINGED SNOWPLOW



PLOW TYPE	WINGED
<b>MOLDBOARD</b>	Powder-Coated Steel
<b>BLADE WIDTH</b>	Scoop: 8'7" (2.62 m); Wings Pinned: 9'8" (2.95 m)
<b>BLADE HEIGHT</b>	29.5" (74.93 cm)
<b>BLADE THICKNESS</b>	14 ga
<b>TRIP SPRINGS</b>	4
<b>VERTICAL RIBS</b>	8
<b>LIFT CYLINDER</b>	1.5" x 8" (3.81 cm x 20.32 cm)
<b>ANGLING RAMS</b>	1.5" x 10" (3.81 cm x 25.40 cm)
<b>PLOWING WIDTH (FULL ANGLE)</b>	Full Angle: 7'10" (2.39 m); Scoop: 8'7" (2.61 m)
<b>APPROX. WEIGHT (WITHOUT MOUNT)</b>	911 lb (413 kg)
<b>CUTTING EDGE</b>	0.5" x 6" (1.27 cm x 15.24 cm)
<b>MOUNT TYPE</b>	Skid-Steer Attach Plate



TWO WINTER  WARRANTY


Western Products | P.O. Box 245038 | Milwaukee, WI 53224-9538

[westernplows.com](http://westernplows.com)



Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. Other patents pending. Western Products offers a limited warranty for all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: CONTRACTOR GRADE®, PILE DRIVER™, PRODIGY™, TRACE™, and WESTERN®.

©2024 Douglas Dynamics, LLC  
All rights reserved.

 A DIVISION OF DOUGLAS DYNAMICS, LLC

Printed in U.S.A.  
Form No. 32419 - AUG24