

**POWER PUSHER™**  
FIXED WING PUSHER PLOWS  
WITH TRACE™ EDGE TECHNOLOGY

**SNOWEx®**





**Push forward like never before** with the POWER PUSHER™ family of fixed wing pusher plows. These units have been improved through real-world feedback to ensure they can handle massive amounts of snow with every pass. Available in 8', 10', 12', 14', and 16' widths and three heights, these units are compatible with skid-steers, wheel loaders, tractors, and backhoe loaders. The POWER PUSHER fixed wing pusher plows are backed by the best-in-class SnowEx® dealer network available throughout the country for service and support.

#### TRACE™ EDGE TECHNOLOGY

The patented terrain-response advanced cutting edge is comprised of independent, 2' sections that raise, oscillate, and trip to accommodate contours and obstacles in the plowable surface. Working together, the sections remove more snow, reducing the amount of salt required. Greasing locations allow the operator to keep the components well lubricated for maximum performance.

#### SELF-LEVELING SIDE PLATES & REVERSIBLE SKIS

The side plates ensure the TRACE edge remains in direct contact with the plowable surface. The reversible, bolt-on ski allows you to use both sides of the metal before replacing. The design features new bolt locations on top of the ski to reduce the likelihood of scraping the surface or curbs.

#### REINFORCED BOX STRUCTURE

Steel braces reinforce the pusher wings for enhanced strength and stability, allowing the POWER PUSHER plow to push and stack more snow with every pass.

#### ¾" CUTTING EDGE WITH CARBIDE INSERTS

Each 2' cutting edge section comes standard with a ¾" carbide insert that extends the life of a high-carbon blade up to 20 times. Each section uses the same part number.

#### COMMON ATTACHMENT PLATE

A common attachment plate with floating coupler allows compatibility with skid-steers, wheel loaders, backhoes, and tractors. The floating coupler absorbs the vehicle's negative down pressure, protecting against premature wear of the cutting edge and pusher components.

#### EASY OPERATION

Operation of the POWER PUSHER plow is conveniently tied into the loader's controls. Simply raise and lower the lift arm and angle the attachment plate to position the pusher in the correct orientation.

DIMENSIONS					OPERATIONAL			CONSTRUCTION			
BLADE WIDTH	BLADE HEIGHT	SIDE PLATE WIDTH	SIDE PLATE HEIGHT	MOLDBOARD RADIUS	CUTTING EDGE TECH	CUTTING EDGE MATERIAL	APPROX. SNOW CAPACITY	APPROX. WEIGHT*	MOUNT TYPE	MACHINE APPLICATION	VEHICLE HORSEPOWER COMPATIBILITY
8' (2.44 m)	30" (76.2 cm)	36" (91.44 cm)	30" (76.2 cm)	27" (68.58 cm)	TRACE - Terrain Response Advanced Cutting Edge  High-carbon steel with carbide inserts		75 cu ft (2.12 cu m)	2,658 lb (1205.65 kg)	Skid Attach Plate	Skid-Steer	45+ hp
10' (3.05 m)	30" (76.2 cm)	36" (91.44 cm)	30" (76.2 cm)	27" (68.58 cm)			94 cu ft (2.68 cu m)	2,895 lb (1313.15 kg)	Skid Attach Plate	Skid-Steer	60+ hp
12' (3.66 m)	30" (76.2 cm)	36" (91.44 cm)	30" (76.2 cm)	27" (68.58 cm)			113 cu ft (3.20 cu m)	3,075 lb (1394.8 kg)	Skid Attach Plate / Coupler	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	40+ hp (Tractor) 60+ hp (Wheel Loader)
14' (4.27 m)	30" (76.2 cm)	36" (91.44 cm)	30" (76.2 cm)	27" (68.58 cm)			132 cu ft (3.73 cu m)	3,442 lb (1561.27 kg)	Skid Attach Plate / Coupler	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	40+ hp (Tractor) 60+ hp (Wheel Loader)
16' (4.88 m)	30" (76.2 cm)	36" (91.44 cm)	30" (76.2 cm)	27" (68.58 cm)			151 cu ft (4.28 cu m)	3,676 lb (1667.41 kg)	Skid Attach Plate / Coupler	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors	40+ hp (Tractor) 60+ hp (Wheel Loader)
8' (2.44 m)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	27" (68.58 cm)			108 cu ft (3.06 cu m)	2,753 lb (1248.74 kg)	Skid Attach Plate / Coupler	Skid-Steer / Tractor / Wheel Loader	40+ hp (Tractor) 60+ hp (Wheel Loader)
10' (3.05 m)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	27" (68.58 cm)			135 cu ft (3.82 cu m)	2,947 lb (1336.74 kg)	Skid Attach Plate / Coupler	Skid-Steer / Tractor / Wheel Loader	50+ hp (Tractor) 60+ hp (Wheel Loader & Backhoe)
12' (3.66 m)	42" (106.68 cm)	36" (91.44 cm)	42" (106.68 cm)	46" (116.84 cm)			219 cu ft (6.20 cu m)	3,322 lb (1506.83 kg)	Coupler	Wheel Loader	100+ hp
14' (4.27 m)	42" (106.68 cm)	36" (91.44 cm)	42" (106.68 cm)	46" (116.84 cm)			255 cu ft (7.22 cu m)	3,791 lb (1719.57 kg)	Skid Attach Plate / Coupler	Wheel Loader	140+ hp
16' (4.88 m)	42" (106.68 cm)	36" (91.44 cm)	42" (106.68 cm)	46" (116.84 cm)			291 cu ft (8.24 cu m)	3,980 lb (1805.3 kg)	Coupler	Wheel Loader	140+ hp

TrynEx International | Madison Heights, Michigan 48071

[snowexproducts.com](http://snowexproducts.com)

TrynEx International reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. TrynEx International or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings. This product is manufactured under the following US Patents: 12,497,744. Other patents pending. TrynEx International offers a limited warranty for all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: TRACE™, POWER PUSHER®, SnowEx®.

**2 WINTER WARRANTY**