

DS-D5032QE



- LED backlit technology with full HD 1920 x 1080
- 32" LED backlight monitor
- 16.7 million colors display images perfectly
- Multiple interfaces: HDMI, VGA, audio in
- Built-in speaker
- Wide viewing angle: Horizontal 178°, Vertical 178°
- 24/7 operation
- LED backlit technology with full HD 1920×1080
- 16.7 million color, display picture perfectly
- HDMI support up to 1080P
- Multiple inputs: HDMI, VGA
- Build-in speaker, Audio 5W*2
- Auto signal input Detection
- Smart engine for Phase/Image position/Color calibration
- Plastic casing
- Narrow front Bezel



▪ Specification

	Model	DS-D5032QE
General	Loudspeaker	5W*2
	VESA	M4, 100mm*100mm
	Dimensions(W*H*D)	727mm*474mm*64mm(with base)/727mm*424mm*64mm(28.62" × 18.66" × 2.52")
	Packing Dimensions(W*H*D)	804mm*500mm*136 mm(31.65" × 19.69" × 5.35")
	Gross Weight	6.763Kg(14.9 lb.)
	Net Weight	5.09Kg(11.2 lb.)
	Storage Temperature	-20°C to 60°C
	Power Supply	AC100~240V,50/60Hz
	Working Temperature	0°C to 40 °C
	Working Humidity	20 - 80%RH (No Condensation)
	Storage Humidity	10 - 90%RH (No Condensation)
	Standby Power Consumption	<0.5W
	Power Consumption	<54W
	Color of Casing	Black
Interfaces	HDMI Input	1
	VGA Input	1
	Audio Input	1
	RJ45(RS232)	1
Accessories	Power Cord	1
	HDMI cable	1
	User Manual	1
	Remote Control	1
Monitor	Backlight	LED Backlight
	Screen Size	31.5 inch
	Pixel Pitch	0.36375mm * 0.36375mm
	Max Resolution	1920 * 1080@60Hz
	Brightness	300 cd/m2(typ.)
	Contrast	1200:1(typ.)
	Response Time	8ms
	Color	16.7M
	Active Area	698.4(H)*392.85 (V) mm
	Viewing Angle	178°(H)/178°(V)
Bracket	Pedestal	1
	Wall Mounted	Optional