

DS-D5024FN



- LED backlit technology with full HD 1920×1080
- Wide view angle: 178°(H)/178°(V)
- User-friendly operation menu
- High reliable components for 7×24 working
- 1 channel HDMI 1.3 input interface
- Three image modes to adapt different environment
- Support software spread-spectrum technology to reduce EMI radiation
- VESA stand bracket



• Specification

	Model	DS-D5024FN
General	Loudspeaker	NA
	Dimensions(W*H*D)	540×418×227mm(21.26" × 16.46" × 8.94")
	Packing Dimensions(W*H*D)	618*491*112mm(24.33" × 19.33" × 4.41")
	Gross Weight	4.44 kg (9.8 lb.)
	Net Weight	3.43 kg (7.6 lb.)
	Storage Temperature	-20 to 60 ° C (-4 to 140 ° F)
	Power Supply	100 to 240 VAC, 50/60Hz
	Working Temperature	0 to 40 ° C (32 to 104 ° F)
	Working Humidity	10 to 90 %
	Storage Humidity	5 to 95%
	Wall-mounting Screw	M4
	Wall-mounting Hole	100 ×100 mm
	Standby Power Consumption	≤ 0.5 W
	Power Consumption	100 to 240 VAC, 50/60Hz
	Color of Casing	Black
	Casing Material	Plastic
Interfaces	HDMI Input	1
	VGA Input	1
Accessories	Power Cord	1
	HDMI cable	1
	User Manual	1
Monitor	Backlight	TFT-LED Backlight
	Screen Size	23.8 inch
	Max Resolution	1920 ×1080@60Hz
	Brightness	250 cd/m ²
	Contrast	4000: 1
	Response Time	14ms
	Color	16.7M
	Active Area	527 × 296 mm
	Viewing Angle	Horizontal 178°, vertical 178°