

DS-2CD3721G0-IZSUHK(2.7-13.5mm)



- High quality imaging with 2 MP resolution
- Efficient H.265+ compression technology
- Clear imaging against strong back light due to 120 dB true WDR technology
- -Z: motorized vari-focal lens for easy installation and monitoring
- -S: audio and alarm interface available
- Water and dust resistant (IP67) and vandal proof (IK10)
- Robust structure design with full metal materials



▪ Specification

Selection Parameter	
Min. Illumination	0.028 Lux
Local Storage	128 GB
Protection Level	IP67
Wi-Fi Support	No
Case Type	Dome
Resolution	2MP
Lens Type	Varifocal Lens
Video Compression	H.265+,H.265,H.264+,H.264
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @(F2.0, AGC ON);,B/W: 0.001 Lux @(F1.2, AGC ON), 0.0028 Lux @(F2.0, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Wide Dynamic Range	120 dB
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 355°, tilt: 0° to 75°, rotation: 0° to 355°
Lens	
Focus	-Z: Auto,Without -Z: Manual
Lens Type	2.7 to 13.5 mm
FOV	Horizontal FOV: 99.6° to 35°, vertical FOV: 53.5° to 20°, diagonal FOV: 118.6° to 40.2°
Aperture	F2.0
Lens Mount	Φ14
Aperture Type	Fixed
Illuminator	
IR Range	Up to 30 m
Wavelength	850nm
Video	
Max. Resolution	1920 × 1080
Main Stream	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720),60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub Stream	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240),60Hz: 30fps (640 × 480, 640 × 360, 320 × 240) 1080P@12fps
Third Stream	1fps (352 × 240, 320 × 240)
Video Compression	Main stream: H.265/H.264,Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
H.264+	Main stream supports, Sub stream supports
H.265+	Main stream supports, Sub stream supports
Scalable Video Coding (SVC)	H.264 and H.265 encoding support
Region of Interest (ROI)	1 fixed region for main stream
Audio	
Environment Noise Filtering	Yes
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Network	
Simultaneous Live View	Up to 6 channels
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
User/Host	Up to 32 users,3 levels: Administrator, Operator and User
Network Storage	Support built-in microSD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR
Client	iVMS-4200, Hik-Connect, iVMS-5200, iVMS-4500
Web Browser	IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Alarm Trigger	Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Image	
Day/Night Switch	Day/Night/Auto/Schedule/Triggered by alarm in (-S)
Target Cropping	No
DNR	3D DNR
Image Enhancement	BLC/3D DNR,HLC
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser
Interface	
Audio	1 input (line in), 1 output (line out), mono sound
Alarm	2 inputs,2 outputs
Video Output	CVBS
On-board Storage	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Hardware Reset	Yes
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Smart Feature-Set	
Smart Event	Line crossing detection, intrusion detection
General	
Firmware Version	V5.5.6
General Function	One-key reset, anti-flicker, heartbeat, three streams, mirror, password protection, privacy mask, watermark, IP address filter
Startup and Operating Conditions	-30 °C to +60 °C (22 °F to +140 °F), humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, Φ 5.5 mm coaxial plug power,PoE (802.3af, class 3)
Power Consumption and Current	-Z:,12 VDC, 0.8 A, max. 10 W,PoE: (802.3af, 36V-57V), 0.4 A to 0.2 A, max. 12 W,Without -Z:,12 VDC, 0.5 A, max. 6 W ,PoE: (802.3af, 36V-57V), 0.3 A to 0.1 A, max. 8 W
Camera Material	Front cover & Base: metal, bubble: plastic
Camera Dimension	Φ 153.3 × 111.6 mm (Φ 6" × 4.4")
Camera Weight	Camera: approx. 880 g (1.9 lb.),With package: approx. 1300 g (2.9 lb.)
Approval	
Protection	IK10, IP67

▪ Accessory

▪ Optional

DS-1280ZJ-DM55	DS-1473ZJ-155B	DS-1476ZJ-SUS	DS-1471ZJ-155	DS-1473ZJ-155
Junction box	Wall mount	Corner mount	Pendant Mount	Wall mount