

DS-PDWL-E-WE

Wireless Water Leak Detector



- Water-proof design for multiple use applications
- Fully remote configurable through APP
- Multiple enrollment method and easy installation design
- Frequency hopping against jamming for reliable transmission
- External probe included

▪ Specification

Feature	
Digital Processing	Support
Tamper Protection	Front,Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Interface	
LED Indicator	Blue (alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	868 MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1.2 km
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Typical Voltage	3V
Power Supply	Battery powered
Battery Type	CR2450 x 1
Standard Battery Life	Up to 3 years (standby time)
General	
Operation Temperature	-10°C to 55°C (14°F to 131°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Operation Humidity	10% to 90%
IP Rate	IP66
Dimension(WxHxD)	62.4 mm × 62.4 mm × 14.6 mm
Weight	85.5 g
Mounting Method	Wall,Surface
Application Scenario	Indoor standalone/with included probe

▪ Available Model

DS-PDWL-E-WE