

# Outdoor IR Bullet Network Camera

MODEL: VIGI C320I



**H.265+**

2/3/4MP



Human & Vehicle  
Classification



Smart Detection



IP67 Weatherproof



Built-In Microphone




Remote Monitoring

## // Human & Vehicle Classification


Intelligently distinguishes humans and vehicles from other objects, so you receive more accurate event notifications.




## // Smart Detection



**Intrusion  
Detection**



**Line-Crossing  
Detection**



**Object Removal  
Detection**



**Object Abandoned  
Detection**




**Region Entering  
Detection**



**Region Exiting  
Detection**



**Motion  
Detection**



**Camera  
Tampering**

## // SmartVid



### **Smart IR**

Keeps objects from being under-rendered when far away or overexposed when close to camera at night.



### **Wide Dynamic Range**

Adjusts for lighting contrast to minimize shadowing effects and renders images true to life.



### **3D DNR**

Removes abnormal pixelation to provide clearer video and eliminate distortion.

# // Specifications

Camera			
Product Model	VIGI C320I	VIGI C330I	VIGI C340I
Image Sensor	1/3" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/3" Progressive Scan CMOS
Slow Shutter	Yes		
Min. Illumination	Color: 0.01 Lux; 0 Lux with IR		
Day & Night Mechanism	IR Cut Filter		
Day/Night Switch	Unified/ Scheduled/ Auto		
Lens			
Focal length	2.8 mm/4 mm/6 mm	2.8 mm/4 mm/6 mm	2.8 mm/4 mm/6 mm
Aperture	2.8mm: F2.2 4mm: F2.0 6mm: F2.0	2.8mm: F2.2 4mm: F2.0 6mm: F2.0	2.8mm: F2.2 4mm: F2.0 6mm: F2.0
Focus	Fixed		
FOV	2.8mm: 88.2°/48.6°/106.5° (H/V/D) 4mm: 75.2°/40.8°/88.3° (H/V/D) 6mm: 49.8°/27.6°/57.7° (H/V/D)	2.8mm: 97.8°/52.9°/117.9° (H/V/D) 4mm: 82.8°/44.5°/98.1° (H/V/D) 6mm: 54.5°/30.0°/63.2° (H/V/D)	2.8mm: 88.8°/48.9°/106.5° (H/V/D) 4mm: 75.2°/40.8°/88.3° (H/V/D) 6mm: 49.8°/27.6°/57.7° (H/V/D)
Lens Mount	M12	M12	M12
DORI Distance	2.8 mm: Detect: 45 m (149 ft) Observe:19 m (62 ft) Recognize: 9 m (30 ft) Identify: 5 m (15 ft) 4 mm: Detect: 60 m (198 ft) Observe: 25 m (83 ft) Recognize: 12 m (40 ft) Identify: 6 m (20 ft) 6 mm: Detect: 91 m (297 ft) Observe: 38 m (124 ft) Recognize: 18 m (59 ft) Identify: 9 m (30 ft)	2.8 mm: Detect: 49 m (161 ft) Observe: 20 m (67 ft) Recognize: 10 m (32 ft) Identify: 5 m (16 ft) 4 mm: Detect: 65 m (214 ft) Observe: 27 m (89 ft) Recognize: 13 m (43 ft) Identify: 7 m (21 ft) 6 mm: Detect: 98 m (321 ft) Observe: 41 m (134 ft) Recognize: 20 m (64 ft) Identify: 10 m (32 ft)	2.8 mm: Detect: 60 m (197 ft) Observe: 25 m (82 ft) Recognize: 12 m (39 ft) Identify: 6 m (20 ft) 4 mm: Detect: 80 m (262 ft) Observe: 33 m (109 ft) Recognize: 16 m (52 ft) Identify: 8 m (26 ft) 6 mm: Detect: 120 m (394 ft) Observe: 50 m (164 ft) Recognize: 24 m (79 ft) Identify: 12 m (39 ft)
Angle Adjustment (Manual)			
Range	• Pan: 0° to 360° • Tilt: 0° to 90° • Rotation: 0° to 360°		

Illuminator			
IR LED	<ul style="list-style-type: none"><li>• Quantity: 2</li><li>• Range: 50m</li><li>• Wavelength: 850nm</li></ul>		
White LED	N/A		
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off		
Video			
Max. Resolution	2MP (1920 × 1080)	3MP (2304 × 1296)	4MP (2560 × 1440)
Main Stream	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 1920x1080, 1280x960, 1280x720	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2304x1296, 2048x1280, 1920x1080, 1280x720	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2560x1440,2304x1296, 2048x1280, 1920x1080, 1280x720
Sub-Stream	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 704x576, 640x480, 352x288, 320x240	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 704x576, 640x480, 352x288, 320x240	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 640x480, 352x288, 320x240
Bit Rate Control	CBR, VBR		
Video Compression	<ul style="list-style-type: none"><li>• Main Stream: H.265+/H.265/H.264+/H.264</li><li>• Sub-Stream: H.265/H.264</li></ul>		
H.264 Type	High Profile		
H.264+	Main Stream Supported		
H.265 Type	Main Profile		
H.265+	Main Stream Supported		
Video Bit Rate	<ul style="list-style-type: none"><li>• Main Stream: 256 Kbps to 4 Mbps</li><li>• Sub-Stream: 64 Kbps to 512 Kbps</li></ul>		
Image			
Image Settings	<ul style="list-style-type: none"><li>• Mirror</li><li>• Brightness</li><li>• Contrast</li><li>• Saturation</li><li>• Sharpness</li><li>• Exposure</li><li>• WDR</li><li>• White Balance</li><li>• Prevent Overexposure to Infrared Light</li><li>• HLC Adjustable by Client Software</li><li>• Rotation(90°/270°)</li></ul>		

Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	DWDR
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
<b>Audio</b>	
Audio Communication	N/A
Audio Input	Yes
Audio Output	N/A
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
<b>Network</b>	
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6 (VIGI C320I does not support IPv6), ARP
ONVIF	Yes
API	Open Network Video Interface (Profile S)
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Cloud	Yes
Client	VIGI App, VIGI Security Manager, VIGI NVR, Web
Web Browser	<ul style="list-style-type: none"> <li>• Google Chrome® 57 and above</li> <li>• Firefox® 52 and above</li> <li>• Safari® 11 and above</li> <li>• Microsoft® Edge 91 and above</li> </ul>
<b>Alarm and Event Management</b>	
Smart Event	<ul style="list-style-type: none"> <li>• Human &amp; Vehicle Classification</li> <li>• Intrusion Detection</li> <li>• Line-Crossing Detection</li> <li>• Region Entering Detection</li> <li>• Region Exiting Detection</li> <li>• Object Abandoned/Removal Detection</li> <li>• Abnormal Sound Detection</li> <li>• People Detection</li> <li>• Vehicle Detection</li> </ul>

Basic Event	<ul style="list-style-type: none"><li>• Motion Detection</li><li>• Video Tampering Detection</li><li>• Exception ( Illegal Login)</li></ul>		
Alarm Linkage	Message Push		
Linkage Method	N/A		
Output Notification	Message Push		
Interface			
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port		
Alarm	N/A		
Reset Button	N/A		
Power	DC Power Port (VIGI C320I does not have DC power port)		
On-board Storage	N/A		
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera		
Built-in Speaker	N/A		
Audio	N/A		
General			
Operating Temperature	-30–60 °C		
Power Supply	PoE (802.3af/at, class 0)	12V DC ± 5%, 5.5mm Coaxial Power Plug PoE (802.3af/at, class 0)	12V DC ± 5%, 5.5mm Coaxial Power Plug PoE (802.3af/at, class 0)
Power Consumption	PoE: class 0	12V DC: Max 5W PoE: class 0	12V DC: Max 5W PoE: class 0
Ingression Protection	IP67		
Material	Plastic		
Product Dimensions	78.5 × 188.03 × 71.55 mm (3.09 × 7.40 × 2.82 in)		
Certification	CE/BSMI/VCCI/ONVIF		