

2MP ColorHunter HD PT Analog Camera

UAC-P112-AF40-W



Overview

UAC-P112-AF40-W is a 2MP ColorHunter HD PT analog camera with a high-performance 1/2.9-inch CMOS sensor. It supports TVI/AHD/CVI/CVBS, which effectively enhances product adaptability and diversity of networking solutions. With SYV-75-3 or other coaxial cable types, the camera can achieve low-cost, long-distance, and anti-interference megapixel HD video transmission without time delay. It supports audio input, synchronous transmission of audio and video, and provides 24/7 color images. The pan&tilt design allows the camera to rotate horizontally and vertically to achieve a wide range of monitoring.

Features

- 2MP high quality imaging
- TVI/AHD/CVI/CVBS
- Supports white light illumination, 24/7 color images
- Supports 180 horizontal flip, 180 vertical flip
- OSD configuration menu, easy to operate
- IP66 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables
- Supports 0 to 345 pan range, 0 to 90 tilt range
- Supports digital defog

Specifications

Sensor	Description
Pixel	2MP
Sensor Size	1/2.9" CMOS
Min. Illumination	0.005 lux (F1.6, AGC ON) 0 lux (white light on)
Lens	Description
Focus	4.0 mm
Lens Mount	M12
Angle of View (H)	83.8°
Angle of View (V)	42.7°
Angle of View (D)	100.1°
Illuminator	Description
Illuminator Number	Eight white-light illuminators
Illumination Distance	30m
Lifetime	≥20000 hours
Video	Description
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) × 720(V)
Frame Rate	TVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps AHD: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVI: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter Time	PAL: 1/25s-1/50000s, NTSC: 1/30s-1/50000s
Image	Description
Exposure Mode	Four modes: Global(default), BLC, HLC, DWDR
Day/Night	24/7 color images
Digital Noise Reduction	2D/3D
White Balance	Two modes: Auto (default), Manual
WDR	DWDR
Flip	Supports 180°horizontal flip, 180°vertical flip

Digital Defog	Support
PTZ	Description
Pan Range	0° ~ 345°
Pan Speed	1° ~ 40°/s
Tilt Range	0° ~ 90°
Tilt Speed	1° ~ 30°/s
Number of Presets	32
Control Mode	485/BNC
Baud Rate	9600bps/4800bps/2400bps/1200bps
Interface	Description
Power Interface	5.5 mm Power Interface
Video Output	BNC, supports TVI/AHD/CVI/CVBS
RS485	Support
Operating Environment	Description
Temperature	-30 °C ~ 60 °C (-22 °F ~ 140 °F)
Humidity	≤95% RH (non-condensing)
Surge Protection	4KV for power, 4KV for video output interfaces, 6kV for RS485 interface
Ingress Protection	IP66
General	Description
Power	DC12V±25%
Power Consumption	MAX 8.5W
Mount	Wall Mount, Pendant Mount
Dimensions	Φ 118mm*190mm (diameter*height)
Material	Graphene + Plastic
Weight	477g(1.05lb)