

S5700-P SERIES



Supports 24-Port
2.5G PoE++ and 6-Port
10G SFP+ Uplink



Ups to 16-unit
Virtual Stack



Carrier-Level High
Reliability
Full Layer-3 Functions



Varied Service
Characteristics
Versatile IPv6 Solution
Complete Security
Mechanism

Overview

BDCOM S5700-P Series is a BDCOM-developed multigigabit Ethernet PoE switch oriented for the next generation IP metropolitan area network, large campus network, and enterprise network.

BDCOM S5700-P Series series adopts the cutting edge hardware architecture and is equipped with the BDROS operating system with BDCOM's independent intellectual property rights.

On the basis of providing high-performance L2/L3/L4 wire-speed switching services, BDCOM S5700-P Series further integrates various network services such as IPv6 and network security.

Combined with multiple high-reliability technologies such as uninterrupted upgrade, uninterrupted forwarding, graceful restart, and redundancy protection, BDCOM S5700-P Series ensures the long-term stable communication capability of the network. BDCOM S5700-P Series is widely used in high-end WiFi6 deployment, cyber cafes, E-sports

hotels, and high-speed enterprise network.

BDCOM S5700-P Series is widely used in high-end WiFi6 deployment, cyber cafes, E-sports hotels, and high-speed enterprise network.


BDCOM S5700-P Series has 2 models: S5700-8EP4X and S5700-24EP6X.

Highlights

Advanced hardware architecture, cutting edge processing capability

S5700-P Series 1U pizza-box switch realizes the ultra-high port density of 8-Port 2.5G PoE++, 16-Port 2.5G PoE+ and 6-Port 10G SFP+. Equipped with high-performance ASIC switch chips, S5700-P Series can meet the application requirements of various complex scenarios.

Doubled performance: The virtualized system makes full use of every link between physical devices,



Highlights

avoiding the link congestion of the traditional networking model Spanning Tree Protocol, making the best use of devices, doubling the performance, and protecting the original link investment to the greatest extent.

High reliability: Based on advanced distributed processing technology, the efficient cross-physical device link aggregation function separates the logical control plane, service control plane and service data plane, providing uninterrupted Layer 3 routing and forwarding and avoiding business interruption caused by the single failure.

Therefore, the reliability of the virtual system is greatly improved.

Easy management: The entire virtual system realizes unified management of a single IP, and physical devices are visible to users, which simplifies the management of network devices and network topology, greatly improves operation efficiency, and effectively reduces operation and maintenance costs.

Carrier-level high reliability

Based on Hitless Protection System (HPS), the key components of the S5700-P Series, such as power supply modules, are redundant backup and hot-swappable, which supports seamless switchover in case of failure without manual intervention.

S5700-P Series supports STP/RSTP/MSTP, VRRP, ring network protection, dual uplink active/standby link protection, LACP and other simple and efficient redundancy protection mechanisms.

S5700-P Series supports In-Service Software Upgrade (ISSU), ensuring the unremitting data forwarding during system upgrade.

The ultra-high-precision BFD mechanism, through linkage with Layer 2 and Layer 3 protocols, realizes millisecond-level fault detection and service recovery, which greatly improves the reliability of the network system.

Perfect Ethernet OAM mechanism, supporting 802.3ah and 802.1ag, realizes rapid detection and location of faults through real-time monitoring of network operation status.

The high reliability hardware and software of the S5700-P Series meet the fault recovery time requirement of 50ms for carrier-level services, and truly achieve the high reliability (99.999%) of carrier-class core devices.

Innovative BVSS

The BDCOM S5700-P Series supports innovative BDCOM Virtual Switch System (BVSS), which can virtualize multiple physical devices into one logical

device with unparalleled performance, reliability, and management compared to stand-alone physical devices.

Rich service features

Perfect Layer 2 and Layer 3 multicast routing protocols meet the access requirements of IPTV, multi-terminal high-definition video surveillance and video conferencing;

Complete Layer 3 routing protocols and large routing table capacity meet the needs of various network interconnection, and can built up ultra-large campus network, enterprise network and industry private network.

Comprehensive IPv6 solutions

Supports the IPv6 protocol suite, IPv6 neighbor discovery, ICMPv6, path MTU discovery, DHCPv6, etc.

Supports Ping, Traceroute, Telnet, SSH, ACL and so on, meeting IPv6 networks' device management and service control requirements.

Supports IPv6 multicast features such as MLD, MLD Snooping, IPv6 static routing, IPv6 Layer 3 routing protocols such as RIPng, OSPFv3, BGP4+, providing complete IPv6 Layer 2 and Layer 3 solutions.

Supports a wealth of IPv4 to IPv6 transition technologies, including: IPv6 manual tunnel, automatic tunnel, 6to4 tunnel, and ISATAP tunnel to ensure the smooth transition from IPv4 network to IPv6 network.

Perfect security mechanisms

Equipment-level security: The advanced hardware infrastructure design realizes the level-based packet schedule and packet protection, prevents DoS-/TCP-related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions.

Perfect security authentication mechanisms: IEEE 802.1x, Radius and TACACS+.

Enhanced service security mechanism: Supports clear text or MD5 authentication of related routing protocols, and Unicast Reverse Path Forwarding (uRPF), which can effectively control illegal services; supports in-depth detection and filtering of control packets and data packets, thereby effectively isolating illegal data packets and improving the security of the network system.

Highlights

Innovative eco-friendly design

Intelligent power management system: S5700 series adopts advanced power system architecture design to achieve efficient power conversion, unique power monitoring, slow start function, real-time monitoring of the running status, intelligent adjustment, and deep energy saving.

Intelligent fan management system: Intelligent fan design supports automatic speed regulation, effectively reduces the speed, reduces noise, and prolongs the service life of the fan.

Supports energy efficient Ethernet function and complies with the international standard IEEE 802.3az EEE, effectively reducing energy consumption.

Intelligent POE++

S5700-P Series supports IEEE 802.3af/at/bt PoE standard, and supports 90W PoE output.

S5700-P Series supports up to a maximum of 740W PoE power budget;

S5700-P Series supports manual and dynamic PoE power allocation;

S5700-P Series supports PoE non-stop power supply. The PoE power is maintained during a switch reload.

Model



S5700-8EP4X


- 8-Port 2.5G/GE PoE++
- 4-Port 10G/GE SFP+



S5700-24EP6X

- 8-Port 2.5G/GE PoE++
- 16-Port 2.5G/GE PoE+
- 6-Port 10G/GE SFP+

Application Diagram



Specifications

Item		S5700-8EP4X	S5700-24EP6X
Interface	RJ45	8-Port 2.5G/GE PoE++	8-Port 2.5G/GE PoE++ 16-Port 2.5G/GE PoE+
	SFP+	4-Port 10G/GE	6-Port 10G/GE
Console		1-Port RJ45	1-Port RJ45
Switching Capacity		120Gbps	240 Gbps
Forwarding rate		90 Mpps	180 Mpps
Physical Specifications			
Chassis	Dimensions (WxDxH)(mm)	300*240*44	440*280*44
Package	Dimensions (WxDxH)(mm)	576x448x94	576x448x94
Power			
Power supply		AC: 100V-240V, 50/60Hz	AC: 100V-240V, 50/60Hz
PoE budget		370W	740W
Total output BTU (1000BTU/H=293W)		1433.45	2901
Noise@25°C(dBA)		45	45
MTBF(H)		>200,000	>200,000
Forwarding mode		Store-forward	Store-forward
Flash (MB)		16	16
DRAM (MB)		256	512
MAC		16K	32K
Buffer size(MB)		1.5	2
Jumbo frame		9K	9K
Routing table	IPv4	512	8K
	IPv6	128	4K
ARP table	IPv4	2K	12K
	IPv6	2K	2K
Total SVI		63	1K

Features

Multicast

- IGMP v1/v2c/v3
- IGMP Snooping
- IGMP Fast Leave
- Multicast group policy and multicast number limit
- Multicast filtering
- MVR
- IGMP snooping in certain port and VLAN
- Support for transparent passing of multicast traffic without IGMP
- snooping in certain port and VLAN
- PIM-DM/SM/SSM

IPv4

- Static routing, RIP v1/v2, OSPF, BGP
- Policy Based Routing(PBR)
- ECMP
- BFD for static routing, RIP, OSPF, BGP

DHCP

- DHCP server, client, relay, snooping

MPLS

- MCE

IPv6

- IPv4/v6 dual stack
- ICMPv6, DHCPv6, ACLv6 and IPv6 Telnet
- IPv6 neighbor discovery
- Path MTU discovery
- MLD V1
- MLD snooping
- IPv6 Static Routing, RIPng, OSPFv3, BGP4+
- Manual tunnel, ISATAP tunnel, 6-to-4 tunnel

QoS

- Traffic classification of port/ L2~4 protocol headers/VLAN/ CoS/DSCP
- CAR traffic control
- 802.1P/DSCP priority mapping and remark
- Multiple queuing algorithms such as SP, WRR or SP+WRR
- Tail-Drop, WRED
- Traffic supervision and traffic shaping
- 8 queues per port

Security

- DDoS attack prevention, TCP-SYN/UDP/ARP Flood attack prevention
- IEEE 802.1x authentication, multiple-user authentication, guest vlan
- L2~L4 ACL
- Anti-DOS/IP spoofing/TCP/ping/ SYN/ICMP flood attacks
- Broadcast/multicast/unknown-unicast storm-control
- Port isolation
- Port Security, MAC address limitation, IP+MAC+port binding
- DHCP Snooping, DHCP Option 82
- DAI(Dynamic ARP Inspection)
- IPSG(IP Source Guard)
- IEEE 802.1x certification
- MAC-based authentication
- AAA
- Radius, TACACS+
- Multiple user privileges

Reliability

- 802.3ad Static/LACP link aggregation,
- EAPS
- G.8032 ERPS
- ISSU
- VRRP
- GR for OSPF and BGP
- BFD for OSPF and BGP
- BVSS virtual stacking system

Management

- CLI: Console, Telnet, SSHv1/2
- Web-GUI: HTTP, HTTPS/SSL
- SNMP v1/v2c/v3, RMON, SNMP alarm/inform/traps
- Upload and download of FTP/TFTP/SFTP files
- Debugging
- Syslog for alarm/notification/ command/debug
- Web-GUI: HTTP, HTTPS/SSL
- NTP
- SPAN, RSPAN (1:1 and N:1 mirror)
- LLDP, LLDP-MED
- sFLOW
- ZTP(Zero Touch Provisioning)
- Optical DDM
- Ethernet cable diagnosis
- 802.3ah, 802.1ag

Environment

- Operating temperature/humidity: 0℃ -50℃ , 10%-90% non-condensing
- Storage temperature/humidity: -20℃ -70℃ , 5%-95% non-condensing