

DS-PDEB1-EG2-WE Wireless Emergency Button

The panic button is an effective wireless product for emergency. It is flexible to be fixed in any hidden places.

Key Features

- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Effective emergency button
- Frequency hopping against jamming for reliable transmission





Specification

Feature	
Button	1
Tamper Protection	Front,Rear
Environment Temperature	Support
Indicator	
Signal Strength Indicator	Support
Interface	
LED Indicator	Blue(Alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	868MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1.2Km
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	3 years in work status (being triggered 20 times per day)
Power Supply	Battery Powered
Battery Type	CR2450 x 1
Typical Voltage	3V
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	63.8mm × 63.8mm × 17.9mm
Weight	45.5g
Mounting Method	Wall
Application Scenario	Indoor
	Green Keymat For Medical Application

Available Model

DS-PDEB1-EG2-WE