

## DS-K1T981MF Iris Recognition Terminal



The terminal adopts deep learning algorithm, which helps to recognize the face and iris with higher accuracy. It can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas.

- Max. 50,000 faces capacity, Max. 10,000 irises capacity, Max. 100,000 cards capacity, Max. 5000 fingerprint capacity, and Max. 150,000 events capacity
- Iris recognition with 8-inch LCD touch screen; 2 MP wide-angle lens for face recognition and 5 MP single lens for iris recognition; built-in M1 card reading module
- Two-way audio with client software
- Supports TCP/IP, and Wi-Fi
- Configuration via the web client
- Face recognition distance: 0.3 m to 3 m; iris recognition distance: 40 cm to 70 cm
- Face recognition duration < 0.2 s/User and accuracy rate  $\geq 99\%$ ; iris recognition duration < 1 s
- Supports face with mask recognition

## • Specification

<b>Display</b>	
Screen size	8 inch
Operation method	Capacitive touch screen
Type	LCD
<b>Video</b>	
Lens	3 (2 for face recognition, 1 for iris recognition)
Resolution	For face recognition: 2 MP For iris recognition: 5 MP
FOV	For face recognition: HFOV = 44°; VFOV = 88°; DFOV = 108° For iris recognition: HFOV = 19.9°; VFOV = 14.5°; DFOV = 24.5°
<b>Audio</b>	
Audio quality	Noise suppression and echo cancellation
<b>Network</b>	
Wired network	Support
Wi-Fi	Support, 2.4 G, 802.11b/g/n
<b>Interface</b>	
Network interface	1 RJ-45, 10/100/1000 M self-adaptive
Lock control	1
Exit button	1
Door contact input	1
Alarm input	2
Alarm output	1
TAMPER	1
RS-485	1 RS-485 (Half duplex, HIKVISION)
Wiegand	1 Wiegand(Hik 26bit,Hik 34bit)
USB	1
<b>Capacity</b>	
Iris capacity	10,000
<b>Authentication</b>	
Iris recognition distance	40 to 70 cm
Iris registration duration	< 5 s
Iris recognition duration	< 1 s
Card type	M1 card
Card reading frequency	13.56 MHz
<b>General</b>	
Power supply	12 VDC, 3 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	10 to 90% (no condensing)
Dimensions	126 mm × 232 mm × 27 mm (5.0" × 9.1" × 1.1")
Installation	Wall mounting
Language	English, Spanish (South America), Thai, Arabic, Russian, Portuguese (Brazil)
Platform	Hik-ProConnect and HikCentral Professional
<b>Function</b>	
Face anti-spoofing	Support

Time synchronization

## ▪ Available Model

DS-K1T981MF

## ▪ Dimension

