# **Reolink**

#### Argus 4

#### 180° Blindspot-free. 4K Wi-Fi 6 Ready.

- 4K UHD 180°Blindspot-free View
- Wi-Fi 6 Ready, Smooth 4K Streaming
- $\boldsymbol{\cdot}$  Enhanced Smart Detection with Accurate Alerts
- Easy Installation Anywhere



### **Specifications**

| Video & Audio         |  |
|-----------------------|--|
| Image Sensor          | 1/2.7" CMOS sensor   |
| Resolution            | 5120x1440 (8 megapixels) @15fps  |
| Lens                  | f=2.8mm , fixed  |
| Video Compression     | H.264/H.265  |
| Field of View         | Horizontal: 180°<br>Vertical: 50°  |
| Pan/Tilt Angle        | N/A  |
| Infrared Night Vision | Up to 30 meters ;<br>LED: 6pcs/20mil/850nm (Auto-<br>switching with IR-cut filter) |
| Color Night Vision    | With spotlights: 3pcs/2W/6500K   |
| Spotlight             | Spotlight: 5pcs/2W/6500K/<br>3000Lumens  |
| Frame Rate            | Main stream: 10fps - 15fps (default:<br>15fps)                                     |
| PIR Angle             | H:170°   |

| PIR Distance           | 10m ( 2-2.5m Installation Height<br>Recommended )   |
|------------------------|---|
| Audio                  | Built-in Microphone and Speaker   |
| Power                  |   |
| Battery                | DC 5V/2A 3.6V 5000mAh ( battery<br>capacity ) rechargeable battery18Wh<br>(Power capacity ) |
| Solar                  | Reolink Solar Panel 2 (6W)  |
| Bluetooth Standard     |   |
| Bluetooth Standard     | Bluetooth V5.0  |
| Interface              |   |
| Power Port             | USB Type-C port   |
| SD Card Slot           | Supports Max. 512GB microSD card  |
| Reset Button           | YES   |
| Audio In/Out           | Built-in microphone and speaker   |
| Wi-Fi                  |   |
| Wireless Standard      | IEEE 802.11 a/b/g/n/ac/ax   |
| Operating Frequency    | 2.4GHz/5GHz   |
| Wireless Security      | WPA/WPA2/WPA3   |
| Software               |   |
| OS Supported           | PC: Windows, Mac OS; Smartphone:<br>iOS, Android  |
| Protocols & Standards  | SSL, TCP/IP, UDP, UPNP, SMTP, NTP,<br>P2P, FTP  |
| User Access            | Max. 12 simultaneous streams (2 main<br>& 10 sub streams)                                   |
| Other Features         |   |
| Smart Alarm            | Motion detection AI detection(Person/<br>Vehicle/Animal)                                    |
| PIR Detecting Distance | Adjustable, up to 10m (33ft)  |
| PIR Detecting Angle    | 170° horizontal   |

| Recording Modes          | Motion Recording  |
|--------------------------|---|
| Time Lapse               | YES   |
| Smart Home Compatibility | Google Assistant  |
| Home Hub Compatibility   | YES   |
| Cloud Storage            | Supports Reolink Cloud (available in selected countries)                                  |
| Working Environment      |   |
| Operating Temperature    | -10°C~55°C (14°F~131°F)   |
| Operating Humidity       | 20% ~ 85%   |
| Weatherproof             | IP66  |
| Mechanical               |   |
| Dimensions               | 128*87*80mm   |
| Weight Battery Included  | 400g  |
| Warranty                 |   |
| Limited Warranty         | 2-year limited warranty. For support,<br>visit https://support.reolink.com/hc/en-<br>us/. |

## **Gallery & Specs**



- 1. Day light sensor
- 2. Spotlight1
- 3. Infrared LED
- 4. Infrared LED
- 5. Spotlight 2
- 6. Microphone
- 7. PIR sensor



- 1. Reset button
- 2. MicroSD card slot
- 3. Silicone cover
- 4. Loudspeakers
- 5. USB-C connection