

DHI-HY-C132

Conventional Heat Detector



- · Meets all requirements of latest EN54
- Two-wire, polarity-free realizes convenient wiring
- Completes EMC test, it has strong anti-electromagnetic interference ability, high stability and reliability
- Differential temperature intelligent detection algorithm satisfies a variety of complex scenarios
- · Non-loosening screws on base terminal for easy installation
- · Contacts material is highly acid-resistant and rust-resistant

System Overview

DHI-HY-C132 Conventional Heat Detector is a mated product of the Conventional Fire Alarm Control Panel. Integrated with two-wire and polarity-free technology, this detector analyzes ambient temperature by rate of rise & fixed temperature algorithm to trigger alarms.

Functions

Temperature alarm

With rate of rise & fixed temperature algorithm, when the temperature reaches the preset alarm threshold, the detector sends alarm signal, satisfying a variety of complex scenarios.

Non-addressable

Without encoding, easy debugging and operating.

Scene


It is suitable for kitchens, smoking rooms, boiler rooms, generator rooms and other high-humidity places, where is not suitable to use photoelectric smoke detectors.

Technical Specification		
Working Voltage	DC16V-DC28V	
Rated Power	3.408mW	
Current	Standby current: ≤ 120μA Alarm current: ≤ 170μA	
Alarm Mode	Visual alarm	
Coverage Area	$H \le 4 \text{ m } (13.12 \text{ ft}): 50 \text{ m}^2$ $4 \text{ m} (13.12 \text{ ft}) \le H \le 12 \text{ m} (39.37 \text{ ft}): 30 \text{ m}^2$	
Operating Temperature	-10°C to +50°C (+14°F to +122°F)	
Operating Humidity	≤ 95% RH (no condensation)	
Dimensions (with base)	Φ100 mm × 50 mm (Φ 3.00" × 2.13")	
Weight (with base)	81 g (0.18 lb)	
Installation	Ceiling Mount	
Compliance Standard	EN 54-5: 2017/A1:2018	

Installation



Dimensions (mm/inch)



Ordering Information			
Туре	Part Number	Description	
Conventional Heat Detector	DHI-HY-C132	Conventional Heat Detector	