

SC-3032

32" LED Monitor



Product Feature

- Signal Input: 1366x768
 - Multi-channel signals input, with stereo speaker.
 - Adopt the newest LCD blue ray technology, 3D digital comb filtering and 3D noise reduction technology.
 - Color 16.7M (8-bit), image natural and exquisite.
 - 5ms response time, no delaying.
 - Internal power supply with low consumption, service life above 60,000 hours.
 - Adopt adaptive power supply, meet variable countries requirement.
 - Use ABS plastic body, desktop base included.
-

	Model	SC-3032
Panel Specification	Panel size:	32" TFT LED
	Resolution:	1366x768
	Aspect ratio:	16:9
	Brightness (cd/m ²):	260(typ)
	Refresh rate:	60Hz
	Contrast ratio:	3000:1
	Visual angle:	178°/178°
	Response time:	5ms
	Color:	16.7M(8-bit)
Input Interface	VGA:	VGA×1
	HDMI input:	HDMI×2
	RCA input:	RCA×3
	USB input:	USB×2
VESA	Wall mounting hole size:	200×100mm
Audio	Audio:	Built-in speaker
Operating Environment	Working temperature:	0°C~50°C
	Storage temperature:	-20°C~60°C
	Working humidity:	5%~90%
Power Consumption	Power supply:	AC100V-240V ≤45W
	Standby consumption:	≤3W
Package	Dimension(mm):	820(W)×540(H)×138(D); 2PCS/CTN: 845(W)×565(H)×300(D)mm
	Gross weight(kg):	4.7kg 1pcs; 10.65kg 2pcs
	Accesssory include	1* power cable 1* HDMI cable, 1* quick guide, 1* desktop bracket, 1*remote control
Industry Standards	Quality standard	Passed RoHS FCC CE China 3C China Energy Saving Patent certificate Patent Right
	Installation method	Desktop base, wall mount
	Housing material	ABS plastic
	Housing color	Black
OSD	Menu language	Support English, Spanish, Turkish, Russian... more than 20 languages