

#morethanbrightideas

SIRENA



XLF ARROW


Dispositivi a LED con freccia direzionale

LED devices with directional arrow

- Dispositivi a led con freccia direzionale sviluppati con 1 LED (XLF ARROW S) o con 1 LED RGBA (XLF ARROW RGB)
- Disponibile in configurazione modulo singolo per basi MLINE*, o nella versione per basi TLINE*, oppure in configurazione pre-assemblata su semaforo industriale TLINE.
- Cupola in policarbonato opaline neutra ad alta resistenza agli impatti - IK08
- Grado di protezione IP66, certificazione UL TYPE 4X (IP69K con utilizzo del collare di sicurezza)
- Temperatura di funzionamento: -40°C /+55°C
- Diversi effetti luminosi (luce fissa, lampeggio singolo 1F, triplo 3F, effetto strobo 5F, random (lampeggio casuale), con luminosità regolabile su 3 livelli, attraverso pulsante.
- Led devices with directional arrow developed with 1 LED (XLF ARROW S) or with 1 RGBA LED (XLF ARROW RGB)
- Available in single module configuration for MLINE bases*, or for TLINE bases*, or in pre-assembled configuration for TLINE industrial traffic lights
- Clear opaline polycarbonate dome with high impact resistance - IK08
- Protection grade: IP66, UL TYPE 4X certification (IP69K with safety collar)
- Operating temperature: -40°C /+55°C
- Several light effects (steady light, single flash 1F, triple 3F, strobe effect 5F, random effect, with adjustable luminous intensity on 3 levels, through button.

*da ordinare separatamente

*to be ordered separately



XLF S ARROW



XLF RGBARROW



XLF S ARROW

90772 ● 90773 ●

XLF S ARROW TLINE

90774 ● 90775 ●

TLINE 2 XLF S DIRECT ARROW

24V ACDC 90776 ●●

120/240V AC 90777 ●●

XLF RGB ARROW

90770 ○○○○○○

XLF RGB ARROW TLINE

90771 ○○○○○○

Per maggiori informazioni, visita il nostro sito
To discover more, visit our website

sirena.it