


Profile deflection



$f_{①} = \frac{F \times L^3}{3 E \times I \times 10^4}$ $f_{②} = \frac{F \times L^3}{48 E \times I \times 10^4}$ $f_{③} = \frac{F \times L^3}{192 E \times I \times 10^4}$	Profile deflection due to force F for static load cases ①②③
$f_{①} = \frac{m' \times g \times L^4}{8 E \times I \times 10^4}$ $f_{②} = \frac{5 \times m' \times g \times L^4}{384 E \times I \times 10^4}$ $f_{③} = \frac{m' \times g \times L^4}{384 E \times I \times 10^4}$	Profile deflection due to the profile's own weight
$\sigma_{①} = \frac{(m' \times g \times L + F) \times L}{W \times 10^3}$ $\sigma_{②} = \frac{(m' \times g \times L + F) \times L}{4 W \times 10^3}$ $\sigma_{③} = \frac{(m' \times g \times L + F) \times L}{8 W \times 10^3}$	Control of max. occurring bending stress $\sigma_{b \max}$
$\sigma_{b \max} < \sigma_{b \text{ zul.}}!$ $\sigma_{b \text{ zul.}} = \frac{R_{p0,2}}{S_{F \text{ erf.}}}$	$S_{F \text{ req}}$: Safety value required to avoid deformation (flow) $\sigma_{b \text{ zul.}}$: Max. permissible bending stress

f (mm)	W (cm³)
F (N)	E = 70000 N/mm²
L (mm)	m' (kg/mm); m' = m/1000; m (p. 2-3 ... 2-6)
I (cm⁴)	g = 9.81 m/s² ≈ 10 m/s²