

Laboratory

Incubator

DI 30 (Digital Display)

TI 30 (Touch Screen)

DI 55 (Digital Display)

TI 55 (Touch Screen)

DI 80 (Digital Display)

TI 80 (Touch Screen)

DI 120 (Digital Display)

TI 120 (Touch Screen)

Connect & Go

Incubator TI 80 - Touch Screen

DragLab incubator ideal solution for media growth and incubation requirements for research, pharmaceuticals, medicine and food chemistry, the forced air heating control system is specially optimized to keep temperature homogenous and exactly at the setpoint value.



Fully controlled environment With DragLab Incubation system

DragLab laboratory incubators has proven its efficiency and accuracy in optimum air circulation inside the fully controlled chamber even when it is fully loaded, all models which presented with different volume sizes are available with an automatized air fan for homogeneous temperature distribution, driven by unique heating system optimally geared to forced air circulation by smart technology to match the intended use. Equipped with a user-friendly software for easy control of many parameters including the temperature and timer. The clear dashboard shows the target and actual display, the status of the device as well as an overview of all events and alarm messages.

Application:

- Clinical microbiology & monitoring
- Biotechnology, cell culture and media preparation
- Testing, analysis and research laboratories
- Microbiology and Bacteriology sample preparation
- Food and beverage production
- Industry and Research
- Cosmetics, skincare products production.
- Pharmaceutical manufacturing and drug formulation.
- Material testing

A vertical bar with black, red, and yellow segments.

Quality and Expertise




DragLab is certified to ISO 9001:2015, reflecting our unwavering commitment to quality and excellence. We continuously optimize our production processes, ensuring that every step is efficient and effective. Through ongoing development and innovation, we strive to meet and exceed industry standards. Our customer-centric approach prioritizes the needs and satisfaction of our clients, driving us to maintain rigorous quality assurance protocols. This dedication ensures that laboratory equipment manufactured by DragLab consistently meets the highest standards of quality and reliability.

DragLab Laboratory Devices are meticulously designed and manufactured from high-quality materials to meet the most rigorous requirements of our customers. Our commitment to excellence and innovation drives continuous development and improvement, informed by daily usage and ongoing technological advancements. 'Quality and Expertise' is not just about creating impressive product designs; it reflects our company's policy of prioritizing high preparedness and customer-centric service as our fundamental objective. This dedication extends to all DragLab products, which comply with current European standards and bear the CE mark.



Incubator TI 80 - Touch Screen

DRAGLAB innovative drying ovens used in research and industries and medicine for a variety of applications, combine efficiency and performance with exceptionally high levels of precision and short heating-up time features on the list of benefits offered.



Features:

Ventilation System:

Airflow with forced air circulation by a fan.

Capacity:

80 litter useful chamber volume.

Display:

Initiative Touch screen display with user-friendly software

Control:

Programmable PID microprocessor.

Temperature:

Temperature control ranges from +20 °C to 100 °C.

Timer:

Timer control ranges from 1 minute to 99:59 hour or continues.

Internal shelves:

Two standard shelves for versatile use.

Interior chamber:

Functional stainless steel AISI 304.

Housing:

Electrostatic powder-coated galvanized steel.

Protection:

Automatic thermostatic protection.

Temperature homogeneity:


In accordance with DIN 12880.

Safety:

European directive 2014/35/EU and 2014/30/EU.

Warranty:

2 years warranty worldwide.



Incubator TI 80 - Touch Screen

Specifications:

Temperature	
Working temperature range	min. +20°C ambient up to +100°C
Temperature fluctuation	0.1°C
Temperature accuracy	± 0.3 % (Over full scale)
Temperature unit	Easy to choose Celsius or Fahrenheit
Temperature sensor	1 Pt100 sensor DIN class A in 2-wire-circuit
Control technology	
Language setting	English
Control	Adaptive multifunctional digital PID-microprocessor controller
Display	Initiative Touch Screen display with user friendly software
Timer	Digital backward counter to target time setting
Timer control	Adjustable from 1 minute to 99:59 hour or continues
Delay timer	Programmable time delay function
Function set point wait	The timer does not start until the set temperature reached the set point
Adjustable parameter	Temperature and time, automatic fan adjustable
Standard equipment	
External door	External steel door with compression door lock
Internal door	Inner door made of tempered safety glass
Calibration certificate	Calibration certificate at +100°C (optional)
Interior	Easy-to-clean interior made of stainless steel AISI 304 on all sides
Gasket	Synthetic rubbers gasket
Housing	Electrostatic powder-coated galvanized steel
Insulation	Fully isolated chamber by Rockwool covered by an aluminum sheet to ensure high-temperature stability
Emergency knob	Manual knob in case of emergency
External dimensions	600 (W) X 620 (D) X 730 (H) mm
Shelves	2-shelves chrome plated
Safety	
Auto diagnostic system	Audible alarm for fault analysis
Alarm	Audible, can be switched off, adjustable limit on the independent temperature safety device
Standards	Integrated independent temperature safety device with visual alarm accordance DIN 12880 EN 61010-1 and EN 61010-2-010 in accordance with EU directive 2014/35/EU EN 61326-1:213 and EN 61326-1 in accordance with EU directive 2014/30/EU
Class	Class I electrical equipment in accordance with EU Directive 2014/35/EU
Protection Class	IP20 according to EN 60529

Incubator TI 80 - Touch Screen

Specifications:

Interior

Internal dimensions	430 (W) X 435 (D) X 430 (H) mm
Chamber	Easy to clean Stainless steel material no.: EN 1.4301 (AISI 304)
Useful volume	80 liter
Standard shelves	2-shelves chrome plated
Max. number of shelves	10
Permitted load	150 Kg
Load per shelf	15 Kg

Ventilation

Fan	Forced air circulation by quiet air turbine automatically adjustable
------------	--

Working conditions

Installation	The distance between the wall and the rear of the appliance must be at least 15 cm. The sides distance must be not less than 5 cm. The distance from the ceiling must not be less than 20 cm
Temperature	+5 °C to +55 °C
Humidity	Max. 80% rh

Electrical data

Voltage	230 volts, 50/60Hz
Watt	1500 watt

Shipping information

Customs tariff number	8419 8998
Dimensions approx. incl. carton	650 (W) X 700 (D) X 850 (H) mm
Net weight	55Kg
Gross weight carton	65Kg

Order Information:

Description	Model	Article number
Incubator 80 Lt - Touch panel display - AMBIENT TEMPERATURE: +20 °C to 100 °C - 230V, 50/60Hz	TI 80	1082.000