Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

Mold Protectant Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Lubricant.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Supplier

WINKEL GmbH Lisztstraße 1

53881 Euskirchen - Germany Tel.: +49 2251 77 69 400-401 Fax: +49 2251 77 69 402 E-Mail: info@winkelgroup.de Internet: www.winkelgroup.de

1.4. Emergency telephone number

Emergency

112

Supplier

+49 2251 77 69 400-401

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229 Pressurised container: May burst if heated. Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315 Causes skin irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

Print date: 28.4.2020 Page 1 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]





Signal word: Danger

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P302 + P352 + P364 F ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

2.2.2. Contains:

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS: 64742-49-0, EC: 927-510-4)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

Vapors can form an explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

Print date: 28.4.2020 Page 2 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
isobutane [C, U]	75-28-5 200-857-2 601-004-00-0	25-50	Flam. Gas 1; H220 Press. Gas; H280		01-2119485395-27
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0 927-510-4 -	10-<25	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411		01-2119475515-33
propane ^[U]	74-98-6 200-827-9 601-003-00-5	10-25	Flam. Gas 1; H220 Press. Gas; H280		01-2119486944-21
n-hexane	110-54-3 203-777-6 601-037-00-0	<1	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Repr. 2; H361f STOT RE 2; H373 Aquatic Chronic 2; H411	STOT RE 2; H373: C ≥ 5 %	-

Notes for substances:

Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.

In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)

Press. Gas (Liq.) Press. Gas (Ref. Liq.)

Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

No action shall be taken involving any personal risk or without suitable training.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Keep at rest in a position comfortable for breathing. If symptoms develop and persist, seek medical attention. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Seek medical help immediately. In case of unconsciousness bring patient into stable side position and seek medical attention.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention. Wash contaminated clothes and shoes before reuse.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Print date: 28.4.2020 Page 3 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



Following ingestion

Not likely. Accidental ingestion: Rinse mouth thoroughly with water. Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

Coughing, sneezing, nasal discharge, labored breathing.

Skin contact

Irritating to the skin. Itching, redness, pain.

Eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Ingestion

Not likely.

Accidental ingestion:

May cause abdominal discomfort.

May cause nausea/vomiting and diarrhea.

Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam.

Fire extinguishing powder.

Carbon dioxide (CO₂).

Water spray. Extinguish large fires with water spray or alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂). Various hydrocarbons.

Aldehydes. Soot.

5.3. Advice for firefighters

Protective actions

In case of fire evacuate the area. In case of fire or heating do not breathe fumes/vapours. Vapours can form explosive mixtures with air. In case of fire aerosols can explode and be propelled to considerable distances in different directions. Cool containers at risk with water spray. If possible remove containers from endangered area. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Print date: 28.4.2020 Page 4 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Evacuate the danger zone. Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Avoid contact with skin, eyes and clothing. Do not breathe vapour or mist.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

Stem the spill if this does not pose risks.

6.3.2. For cleaning up

Prevent release into the sewer, water, basements or confined areas. Collect the spray cans and hand them over to an authorized waste disposal contractor. Release of liquid because of damaged aerosol can (release of large quantities): In case of bigger spill, dam the spillage, pump the liquid into appropriate labelled containers, absorb a residue with absorbent material and dispose of according to local regulations. Do not absorb spillage with sawdust or other combustible material. Dispose in accordance with applicable regulations (see Section 13). Clean residue from spill site.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Protect from open fire and other sources of ignition or heat. Pressurized container; protect from sunlight and do not expose to tempratures exceeding 50°C. Do not pierce or burn, even after use. Vapours and air form explosive mixtures. Take precautionary measures against static discharges. Use spark-proof tools.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Avoid release to the environment.

7.1.2. Advice on general occupational hygiene

Consider measures required in Section 8 of this safety data sheet. Use personal protective equipment. Refer to instructions on label and regulations for safety and health at work. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist.

Print date: 28.4.2020 Page 5 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in well closed containers. Keep in cool and well ventilated area. Keep away from sources of ignition - no smoking. Protect against heat and direct sunlight. Keep away from oxidising substances. Keep away from food, drink and animal feeding stuffs.

7.2.2. Packaging materials

The original container of producer.

7.2.3. Requirements for storage rooms and vessels

Do not store in unlabelled containers.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

7.3. Specific end use(s)

Recommendations

_

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)		/alues	Short-term of limit	exposure	Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
n-Hexane (110-54-3)	20	72				
Normal and branched chain alkanes ≥C7 (-)		1200				
Cycloalkanes ≥C7 (-)		800				

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

Print date: 28.4.2020 Page 6 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



8.1.3. DNEL/DMEL values

For components

Name	Туре	Exposure route	Exposure frequency	Value	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Worker	inhalation	long term (systemic effects)	2085 mg/m ³	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Worker	dermal	long term (systemic effects)	300 mg/kg bw/day	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Consumer	inhalation	long term (systemic effects)	447 mg/m ³	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Consumer	dermal	long term (systemic effects)	149 mg/kg bw/day	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Consumer	oral	long term (systemic effects)	149 mg/kg bw/day	

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols. Keep away from foodstuffs, beverages and feed. If technical measures to reduce workers' exposure are not sufficient, and the limit values of hazardous substances in the air are exceeded, it is necessary to use personal protective equipment.

Organisational measures to prevent exposure

If this product contains ingredients with exposure limits, personal, workplace atmosphere monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protection. Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

If there is a risk of eye contact use safety glasses. Safety googles (EN 166).

Hand protection

Protective gloves (EN 374).

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. If the concentration limit values are exceeded, it is necessary to wear appropriate respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

8.2.3. Environmental exposure controls

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

Print date: 28.4.2020 Page 7 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid; aerosol
-	- Colour:	white
-	Odour:	characteristic

Important health, safety and environmental information

-	рН	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	No information.
-	Evaporation rate	No information.
-	Flammability (solid, gas)	No information.
-	Explosion limits (vol%)	1,5 - 10,9 vol % (propellant)
-	Vapour pressure	< 70 hPa at 20 °C
-	Vapour density	No information.
-	Density	Density : 1,009 kg/L at 20 °C (data refers to the liquid portion of the product)
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	No information.
-	Oxidising properties	No information.

9.2. Other information

-	Weight organic solvents	473 g/l (VOC) 77 % (VOC)
-	Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended transport or storage conditions.

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

10.4. Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not expose to heat and direct sunlight. Do not store above 50°C.

Print date: 28.4.2020 Page 8 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



10.5. Incompatible materials

Strong acids.
Oxidants.
Peroxide.

10.6. Hazardous decomposition products

In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Туре	Species	Time	Value	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	dermal	LD ₅₀	rat	24 h	> 2920 mg/kg bw		
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	oral	LD ₅₀	rat		> 5840 mg/kg bw		
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	inhalation (vapours)	LC ₅₀	rat	4 h	> 23300 mg/m ³	OECD 403	
Additional information: The product is not classified for acute toxicity.							

(b) Skin corrosion/irritation

Name	Species	Time	Result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)			Irritating.		
Additional information: Causes skin irritation.					

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark			
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)			Not classified.					
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)			Contact with eyes may cause irritation.					
Additional information: The product is not classified as an irritant to the eyes.								

(d) Respiratory or skin sensitisation

Name	Exposure route	Species	Time	Result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	-			Not classified.		
Additional information: The product is not classified as sensitis	ing.					

(e) (Germ cell) mutagenicity

Name	Туре	Species	Time	Result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Genotoxicity			Negative.		

(f) Carcinogenicity

Name	Exposure route	Туре	Species	Time	Value	Result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)						Substance is not classified as carcinogenic.		

Print date: 28.4.2020 Page 9 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



(g) Reproductive toxicity

Name	Reproductive toxicity type	Туре	Species	Time	Value	Result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Reproductive toxicity		rat			The results of animal studies gave no indication of a fertility impairing effect.		
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Developmental toxicity		rat			Did not show teratogenic effects in animal experiments.		
n-hexane (110-54-3)	Reproductive toxicity					Suspected of damaging fertility.		

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

Name	Exposure route	Туре	Species	Time	Organ	Value	Result	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	inhalation	-					May cause effects on the central nervous system.		high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	inhalation	-					Symptoms: nausea, unconsciousness.		high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	inhalation	-					Symptoms: mucous membrane irritation.		high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	inhalation	-					May cause respiratory irritation.		high vapours concentrations
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	oral	-					May cause irritation of the digestive tract.		
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	-	-					May cause drowsiness or dizziness.		
Additional information: May caus	se drowsiness	or dizz	ziness.						

(i) STOT-repeated exposure

Additional information: STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

Name	Result	Method	Remark					
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	Aspiration into the lungs can cause lung damage.		The exposed person should be kept under medical surveillance for 48 hours.					
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	May be fatal if swallowed and enters airways.							
Additional information: May be fatal if swallowed and enters airways.								

Print date: 28.4.2020 Page 10 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	ErL ₅₀	10 – 30 mg/L	72 h	algae	Pseudokirchneriella subcapitata	OECD 201	
	EbL50	10 – 30 mg/L	72 h	algae	Pseudokirchneriella subcapitata	OECD 201	
	EL ₅₀	3 mg/L	48 h	crustacea	Daphnia magna	OECD 202	
	LL ₅₀	> 13,4 mg/L	96 h	fish	Oncorhynchus mykiss	OECD 203	
	NOELR	6,3 mg/L	72 h	algae	Pseudokirchneriella subcapitata	OECD 201	

12.1.2. Chronic (long-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	NOELR	1 mg/l	21 days	crustacea	Daphnia magna	OECD 211	
	NOELR	1,53 mg/l	28 days	fish	Oncorhynchus mykiss	QSAR Petrotox	

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

For components

Substance (CAS Nr.)	Туре	Rate	Time	Evaluation	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	biodegradability	98 %	28 days	readily biodegradable	OECD 301 F	

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

Print date: 28.4.2020 Page 11 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Harmful to aquatic life with long lasting effects.

Water hazard class (WGK): 3 (Self-assessment), very hazardous for water.

Do not allow to reach ground water, water courses or sewage system.

For components

Substance: hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB).

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Avoid release to the environment. Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Product and container must be disposed of safely.

Waste codes / waste designations according to LoW

16 05 04* - gases in pressure containers (including halons) containing dangerous substances

Packaging

Uncleaned containers should not be perforated, cut or welded. Pressurized container. Do not pierce or burn, even after use. Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

Waste codes / waste designations according to LoW

15 01 11* - metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

_

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS



Print date: 28.4.2020 Page 12 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



14.3. Transport hazard class(es)

2

14.4. Packing group

Not applicable.

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

1 I

Tunnel restriction code

(D)

IMDG EmS

F-D, S-U

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
 - Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
 - 15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-quideline)

Not applicable.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

Print date: 28.4.2020 Page 13 of 15

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS) EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW - see below)

GES - Generic Exposure Scenario GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

LC₅₀ - Lethal Concentration to 50 % of a test population

LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

Product name: Mold Protectant Spray

Creation date: 17.10.2019 · Revision: 9.3.2020 · Version: 1



List of relevant H phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure .

H411 Toxic to aquatic life with long lasting effects.

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Print date: 28.4.2020 Page 15 of 15