



TECHNICAL DATA SHEET

MULTI GREASE SPECIAL WHITE

Description

Multi Grease is a lithium soap and white solid lubricating grease formulated with quality base oils and specially developed additives. It minimizes rust, oxidation and abrasion by providing effective protection on the surfaces it is applied with specially developed anti-wear and anti-corrosion additives. With extreme pressure additives, it provides excellent protection in systems operating under heavy and vibrating loads.

Properties

- ✓ Thanks to the extreme pressure additives it contains, it performs very well in systems operating under heavy and vibrating loads.
- ✓ Easy pumping feature in cold weather conditions provides ease of application in grease guns.
- ✓ It provides high protection against rust, oxidation and abrasion by providing effective protection on the surfaces on which it is applied with specially developed anti-wear and anti-corrosion additives.

Application

It is recommended to be used in industrial application areas with an operating temperature between -20°C and 130°C

Typical Physical and Chemical Properties

Mineral

		Test Method
Color	White	-
Soap Type	Lithium	-
Penetration (1/10 mm)	265-295	ASTM D 217
NLGI Grade	2	-
Dropping Point	190°C	ASTM D 2265
Bearing Rust Test@ 52°C	Pass	ASTM D 1743

Packaging and Storage

The product should be kept in its original packaging in stock, with its mouth closed. The storage period is 24 months.

It is offered for sale in 1 KG and 16 KG buckets and 180 KG drums.

Health and Work Safety

As long as occupational safety and personal cleaning rules are applied, it does not pose a problem in terms of human health and occupational safety. For more detailed information, the Material Safety Sheets (MSDS) should be consulted.

ART. NO. PACKAGING:
W 150 224 1 KG