

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Schneideöl Spray
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against -
- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WINKEL GmbH

- · Lisztstraße 1
- · 53881 Euskirchen Germany
- · Tel.: +49 2251 77 69 400-401
- · Fax: +49 2251 77 69 402
- · EMail: info@winkelgroup.de
- · Internet: www.winkelgroup.de
- · Further information obtainable from: Research & Development: info@winkelgroup.de
- **1.4 Emergency telephone number:** During normal business hours: Tel: +49 2251 77 69 400-401

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS09

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

Trade name: Schneideöl Spray

P280 Wear protective gloves / eye protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Active substance with propellant

· Dangerous components:		
CAS: 106-97-8	butane (containing < 0.1% butadiene (203-450-8), Note K)	10-<25%
EINECS: 203-448-7	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		
CAS: 74-98-6	propane	2,5-<10%
EINECS: 200-827-9	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21		
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8), Note K)	1-<2,5%
EINECS: 200-857-2	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27	` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `	
EC number: 701-068-0	Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl	≥0,25-<1%
Reg.nr.: 01-2119473798-17	STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Eye	
	Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1,	
	H410 (M=10); Acute Tox. 4, H302; STOT SE 3, H335	

· Additional information:

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in chapter 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

Trade name: Schneideöl Spray

· 5.3 Advice for firefighters

(Contd. of page 2)

· Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with	limit values tha	t require monit	toring at th	ie workplace:
--------------------	------------------	-----------------	--------------	---------------

106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

AGW (Germany) Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG

74-98-6 propane

AGW (Germany) Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG

(Contd. on page 4)

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

Trade name: Schneideöl Spray

(Contd. of page 3)

75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)

AGW (Germany) Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG

1809-19-4 dibutyl phosphonate

MAK (Germany) vgl. Abschn. IIb und Xc, als Dampf und Aerosol

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

General ventilation

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

· Hand protection

Wear gloves for the protection against chemicals according to EN 374

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses



Tightly sealed goggles

Body protection:

Use protective suit. (EN-13034/6)

Full skin covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

· Environmental exposure controls Use a suitable container to prevent environmental contamination.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state Aer
- · Colour: According to product specification

(Contd. on page 5)

Version: 34 (replaces version 33) Revision: 31.03.2022 Printing date: 31.03.2022

Trade name: Schneideöl Spray

(Contd. of page 4) · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling -44.5 °C range ·Flammability Not applicable. · Lower and upper explosion limit · Lower: 1,5 Vol % · Upper: 10,9 Vol % -97 °C · Flash point: 365 °C **Ignition Temperature** · Decomposition temperature: Not determined. ·pH Mixture is non-polar/aprotic. · Viscosity: · Kinematic viscosity Not determined. · Dynamic: Not determined ·Solubility Not miscible or difficult to mix. · water: Not determined. · Partition coefficient n-octanol/water (log value) 3600 hPa · Vapour pressure at 20 °C: · Density and/or relative density 0,807 g/cm³ · Density at 20 °C: Not determined. · Relative density Not determined. · Vapour density · 9.2 Other information · Appearance: · Form: Aerosol · Important information on protection of health and environment, and on safety. · Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Solvent content: · Organic solvents: 20,0 % · Solids content: 2,0 % · Change in condition · Evaporation rate Not applicable. · Information with regard to physical hazard classes ·Explosives Void · Flammable gases Void · Aerosols Extremely flammable aerosol. Pressurised container: May burst if heated. · Oxidising gases Void · Gases under pressure Void Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water Void · Oxidising liquids Void · Oxidising solids · Organic peroxides Void · Corrosive to metals Void (Contd. on page 6)

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

Trade name: Schneideöl Spray

(Contd. of page 5)

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

115-86-6 triphenyl phosphate

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability Not easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

Trade name: Schneideöl Spray

(Contd. of page 6)

·European	waste	cata	logue
-----------	-------	------	-------

HP3 Flammable
HP14 Ecotoxic

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1	UN	number	or ID	number
17.1	UII	Humber	$\mathbf{v}_{\mathbf{I}}$	Humber

· ADR, ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR, ADN UN1950 AEROSOLS, ENVIRONMENTALLY

HAZARDOUS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

 \cdot ADN

· ADN/R Class: 2 5F

· IMDG, IATA



• Class 2.1 Gases. • Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant:

· Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user

· Hazard identification number (Kemler code):

· EMS Number: F-D,S-U

· Segregation groups
· Stowage Code

Alkalis

SW1 Protected from so

SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1

Warning: Gases.

litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS:

Category C, Clear of living quarters.

• Segregation Code SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from" class

1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

(Contd. on page 8)

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

Trade name: Schneideöl Spray

	(Contd. of page
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E0
• • • • • •	Not permitted as Excepted Quantity
· Transport category	2
Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 9)

Printing date: 31.03.2022 Version: 34 (replaces version 33) Revision: 31.03.2022

Trade name: Schneideöl Spray

(Contd. of page 8)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	10-<25

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · VOC-CH 20,00 %
- · VOC-EU 161,4 g/l
- · Danish MAL Code 2-1
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

- · Department issuing SDS: Research & Development
- · Contact: ing. J. Sleumer
- · Version number of previous version: 33
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

 $Aquatic\ Chronic\ 2:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long\ -term\ aquatic\ hazard\ -\ Category\ 2$