

Safety Data Sheet

according to Regulation (EC 1272/2008)

SECTION 1- PRODUCT AND COMPANY INFORMATION

Product Name: WINKEL PRO W-F ALUMINUM EPOXY PUTTY (RESIN)

Product form: Mixture Application: Adhesive

Company Identification: Y kpngril o dJ

Nku vvxt0Pt08'F/75::3'Gvvunktej gp1I GTOCP[

TEL - 6; "*2+"4473998; 622623 FAX 6; "*2+"4473998; 624

SECTION 2- HAZARDS IDENTIFICATION

2.1 · Classification of the substance or mixture

Classification according to Regulation (EC 1272/2008)

Adverse physicochemical, human health and environmental effects

Physical hazards Not Classified

Health hazards: Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Eye Dam. 1

Human health The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive

individuals.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008[CLP]

Pictogram



GHS 07



GHS 09

Signal word Warning

Hazard statements H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. EUH205 Contains epoxy constituents. May produce an allergic reaction.

Supplemental label information

Contains EPOXY RESIN (Number average MW <= 700)

Supplementary P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling. precautionary

P272 Contaminated work clothing should not be allowed out of the workplace. statements

> P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards This product does not contain any substances classified as PBT or vPvB.

SECTION 3 - COMPOSITION, INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2. Mixtures

Ingredient	Cas Number	Percent
2,2'-[(1methylethylidene)bis		
(4,1phenyleneoxymethylene)]	1675-54-3	45-50%
bisoxirane		
Pigment (Mixture)-Aluminium Paste	-	30-45%
Magnesium Silica	14807-96-6	1-5%
Fused Silica	60676-86-0	1-5%

SECTION 4 - FIRST AID MEASURES

4.1. Description of first aid measures

General information Avoid contact with eyes. In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues. Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head

should be kept low so that vomit does not enter the lungs. Get medical attention.

Skin contact Remove affected person from source of contamination. Wash skin thoroughly with soap and

water. Get medical attention if irritation persists after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5 - FIRE FIGHTING MEASURE

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Control run-off water by

firefighting containing and keeping it out of sewers and watercourses.

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

for firefighters clothing.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this Personal precautions

safety data sheet. Provide adequate ventilation.

6.2. Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled

Environmental precautions discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7 - HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only in well-ventilated areas. Handle and open container with care. Keep away from heat,

sparks and open flame. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Ingredient comments WEL = Workplace Exposure Limits

2,2'-[(1methylethylidene)bis(4,1phenyleneoxymethylene)] bisoxirane

DNEL Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day

Workers - Inhalation; Short term systemic effects: 12.25 mg/m³

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

Eye/face protection Safety glasses/goggles or face shield advised, particularly when work overhead.

Hand protection Wear rubber or plastic coated gloves, however due to its concept of packaging, the material unmixed

should not be in contact with skin.

Skin protection Wear suitable protective clothing. Wash hand after each work period and before eating.

Provide eyewash station. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace. Promptly remove any clothing that

becomes wet or contaminated.

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected

respirator. Check that the respirator fits tightly and the filter is changed regularly. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard

EN140. Wear a respirator fitted with the following cartridge: Gas filter, type A2.

Respiratory protection

Hygiene measures

SECTION 9 - PHYSICAL DATA 9.1. Information on basic physical and chemical properties

Form: Paste
Appearance / color: Sliver Gray
Odor: LOW

pH(concentrate): Not applicable. Boiling Point/Range($^{\circ}$ C) Not determined.

Flash Point(closed, °C) >250°C

Autoflammability(°C)
Explosive Properties(%)
Vapour Pressure (kPa at 20 °C):
Relative Density(at 20°C)
Water Solubility:

Not determined.
Not known.

<0.1
2.80-2.85
Insoluble.

Fat Solubility: Not determined.

NOTE:

The physical data represented above are typical values and should not be construed as a specification. For additional physical data and details on use, please obtain a technical data sheet for this product.

SECTION 10- STABILITY AND REACTIVITY DATA

Epoxy resins and epoxy resin hardeners react with each other producing heat.

Conditions to avoid: They should not be mixed with each other under uncontrolled conditions or in

a large mass as the ensuing exothermic reaction may produce heat.

Under normal conditions of storage and use, hazardous reactions will not

Possibility of hazardous reactions: Order occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Skin contact

Irritating to skin. May cause sensitisation by skin contact. The product contains a small amount

of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.

Eve contact Irritating to eyes.

Acute and chronic health

hazards

The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive indi

Route of entry Inhalation Ingestion. Skin and/or eye contact

Acute toxicity:

· LD/LC50 values relevant for classification:

1675-54-3 reaction product: 2,2'-[(1methylethylidene)bis

(4,1phenyleneoxymethylene)] bisoxirane

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

· Skin corrosion/irritation:

Causes skin irritation.

Rabbit: irritating to the skin (OECD 404)

· Serious eye damage/eye irritation:

Causes serious eye irritation.

Rabbit: irritating to the eye (OECD 405)

 \cdot Respiratory or skin sensitization:

May cause an allergic skin reaction.

Mouse (Local Lymph Node Assay): Sensitizing to the skin (OECD 429)

- · Germ Cell Mutagenicity: Not classified based on available data.
- · Carcinogenicity: Not classified based on available data.
- · Reproductive Toxicity: Not classified based on available data.
- · Specific Target Organ Toxicity Single Exposure (STOT SE): Not classified based on available data.
- · Specific Target Organ Toxicity Repeated Exposure (STOT RE):

Not classified based on available data.

- · Aspiration Hazard: Not classified based on available data.
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- \cdot on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU

Classification Guidelines for Preparations as issued in the latest version:

Irritant

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/eye irritation: Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity: Not classified based on available information.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Not classified based on available information.

STOT - single exposure: Not classified based on available information.

STOT - repeated exposure: Not classified based on available information.

Aspiration toxicity: Not classified based on available information.

SECTION 12 - ECOLOGICAL INFORMATION

12.1. Toxicity

The product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products: Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable

Contaminated Packaging: Improper disposal or reuse of this container may be dangerous and illegal.

SECTION 14 - TRANSPORT INFORMATION

14.1. International Transport Regulations

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE:

Shipping name:

UN No:

None Allocated

Hazchem Code:

None Allocated

Pkg Group

None Allocated

DG Class:

None Allocated

Subsidiary Risk(s):

None Allocated

EPG:

None Allocated

Classification:

Land transport ADR/RID/GGVS/GGVE: Not considered as dangerous goods.

Inland navigation AND/ADNR: Not considered as dangerous good Transport by sea IMDG/GGVSea: Not considered as dangerous good Air transport ICAO/IATA: Not considered as dangerous good

SECTION 15 - REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment has been carried out.

SECTION 16 - OTHER INFORMATION

Also refer to the safety data sheet(s) for information on other components of this product.

Waste Disposal: Dispose in accordance with Federal, State/Provincial and local regulations.

Date Prepared: 2023-JUNE

Prepare by: Technical Service Department



Safety Data Sheet

according to Regulation (EC 1272/2008)

SECTION 1- PRODUCT AND COMPANY INFORMATION

Product Name: WINKEL PRO WF ALUMINUM EPOXY PUTTY (HARDENER)

Product form: Mixture Application: Adhesive

Company Identification: Y kpngn'I o dJ

Nku vvxt0Pt08'F/75::3'Gwunktej gp1I GTOCP[

TEL - 6; "*2+"4473998; 622623 FAX 6; "*2+"4473998; 624

SECTION 2- HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC 1272/2008)

Adverse physicochemical, human health and environmental effects
Physical hazards
Not Classified

Health hazards: Skin Irrit. 2 - H315 Eye Dam. 1 - H318

Environmental hazards Aquatic Chronic 2 - H411

Human health The product contains an polyaminoamide. May cause sensitisation or allergic reactions in sensitive

individuals

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008[CLP]

Pictogram





GHS 05

GHS 09

Signal word Danger

Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

 $P333 + P313 \; If \; skin \; irritation \; or \; rash \; occurs: \; Get \; medical \; advice/ \; attention.$

Contains Polyaminoamide

Supplementary P261 Avoid breathing vapour/ spray.

precautionary P264 Wash contaminated skin thoroughly after handling.

statements P272 Contaminated work clothing should not be allowed out of the workplace.

P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards This product does not contain any substances classified as PBT or vPvB.

SECTION 3 - COMPOSITION, INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2. Mixtures

 Ingredient
 Cas Number
 Percent

 Magnesium Silica
 14807-96-6
 5-10%

 Fused Silica
 60676-86-0
 35-40%

 Polyaminoamide
 68082-29-1
 45-55%

SECTION 4 - FIRST AID MEASURES

4.1. Description of first aid measures

General information Avoid contact with eyes. In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

InhalationMove affected person to fresh air at once. Get medical attention if any discomfort continues.IngestionRinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head

should be kept low so that vomit does not enter the lungs. Get medical attention.

Skin contact Remove affected person from source of contamination. Wash skin thoroughly with soap and

water. Get medical attention if irritation persists after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5 - FIRE FIGHTING MEASURE

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours.

5.3. Advice for firefighters

Protective actions during Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Control run-off

firefighting water by containing and keeping it out of sewers and watercourses.

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate

for firefighters protective clothing.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this

safety data sheet. Provide adequate ventilation.

<u>6.2. Environmental precautions</u> Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled

Environmental precautions discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste

disposal containers and seal securely. Containers with collected spillage must be properly

labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7 - HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only in well-ventilated areas. Handle and open container with care. Keep away from

heat, sparks and open flame. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away Storage precautions

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Ingredient comments WEL = Workplace Exposure Limits

Polyaminoamide

DNEL Workers - Dermal; Short term systemic effects:-

Workers - Inhalation; Short term systemic effects: -

8.2. Exposure controls

Protective equipment



Appropriate engineering

Hygiene measures

controls

Provide adequate general and local exhaust ventilation.

Safety glasses/goggles or face shield advised, particularly when work overhead. Eye/face protection

Wear rubber or plastic coated gloves, however due to its concept of packaging, the material Hand protection

unmixed should not be in contact with skin.

Skin protection Wear suitable protective clothing. Wash hand after each work period and before eating.

> Provide eyewash station. Keep away from food, drink and animal feeding stuffs, Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace. Promptly remove any

clothing that becomes wet or contaminated.

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection

be based on exposure levels, the hazards of the product and the safe working limits of the Respiratory protection selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Half

mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Wear a respirator fitted with the following cartridge: Gas filter, type

A2.

SECTION 9 - PHYSICAL DATA

9.1. Information on basic physical and chemical properties

Paste Appearance / color: Beige Amine. Melting Point/Range(°C) Not applicable. >230

Flash Point(closed, °C)

Oxidising Propertise: Not determined.

Vapour Pressure (kPa at 20 °C): 0.02

0.98-1.03 Relative Density(at 20°C) Water Solubility: Miscible. Partition Coefficient(no-Not determined.

ctanol/water):

NOTE:

The physical data represented above are typical values and should not be construed as a specification. For additional physical data and details on use, please obtain a technical data sheet for this product.

SECTION 10- STABILITY AND REACTIVITY DATA

Epoxy resins and epoxy resin hardeners react with each other producing heat.

Conditions to avoid: They should not be mixed with each other under uncontrolled conditions or in

a large mass as the ensuing exothermic reaction may produce heat.

Under normal conditions of storage and use, hazardous reactions will not Possibility of hazardous reactions:

occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Skin Contact: Corrosive-causes .May cause senstisation.

Eye Contact: Causes irreversible damage to eye tissue if not removed promptly.

By Inhalation: May cause respiratory irritation.

By Ingestion: May cause irritation of mouth, throat and digestive tract.

Chronic: Prolonged skin contact can result in chemical burns.

SECTION 12 - ECOLOGICAL INFORMATION

12.1. Toxicity

The product contains a substance which is harmful to aquatic organisms and which may

12.2. Persistence and degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products: Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable

Contaminated Packaging: Improper disposal or reuse of this container may be dangerous and illegal.

SECTION 14 - TRANSPORT INFORMATION

14.1. International Transport Regulations

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE:

Shipping name:

UN No:

None Allocated
Hazchem Code:

None Allocated
Pkg Group

None Allocated
DG Class:

None Allocated
Subsidiary Risk(s):

None Allocated
EPG:

None Allocated

Classification:

Land transport ADR/RID/GGVS/GGVE: Not considered as dangerous goods.

Inland navigation AND/ADNR: Not considered as dangerous good Transport by sea IMDG/GGVSea: Not considered as dangerous good Air transport ICAO/IATA: Not considered as dangerous good

SECTION 15 - REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment has been carried out.

SECTION 16 - OTHER INFORMATION

Also refer to the safety data sheet(s) for information on other components of this product.

Waste Disposal: Dispose in accordance with Federal, State/Provincial and local regulations.

Date Prepared: 2023-JUNE

Prepare by: Technical Service Department