

## **TECHNICAL DATA SHEET**

# **Adhesive Spray**




#### Features:

With immediate high adhesion power and multi-faceted application. It ensures sticking of light materials with and between each other. This spray adhesive is suitable for sticking the following materials: Paper, carton and cardboard, Wood, thin plates, Cork, leather, textile, Soft foam (e.g. Moltopren), Hard foam (e.g. Styrofoam), Rubber and foam rubber, Synthetic folios (excluding PVC and polyethylene).

## **Application:**

The information are recommendations based on our experience. Without pretest and improper use, no liability for any damages. Before starting preparations, shake the spray adhesive well. The surfaces to be stuck should be dry, clean and free from all adhesive residues. Apply the adhesive on two sides of the non-absorbing surfaces and leave it to dry for approximately 15 minutes (20°C). After it dries, it should have consistency that it will not elongate, when touched on the adhesive surface- bind the surfaces to be stuck with the highest possible pressure. Apply the adhesive on the single side of absorbing surfaces and immediately stick the surfaces by applying strong pressure. Apply the spray from approximately 20-25 cm distance. To avoid clogging of the nozzle of spray can, turn the spray can upside down after application and spray the adhesive until no adhesive comes out of the spray can.



### **Physical Properties**

Color	Transparent
Odour:	Characteristic
Density (@20°C):	0,7 g/cm³
Ignition temperature:	>200 °C

**Art Nr. Content:** W 150 158 500 ml