

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**
Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

Etikettenlöser

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Cleaning agent.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Supplier

WINKEL GmbH
Lisztstraße 1 53881
Euskirchen - Germany
Tel.: +49 2251 77 69 400-401
Fax: +49 2251 77 69 402
E-Mail: info@winkelgroup.de
Internet: www.winkelgroup.de

1.4. Emergency telephone number

Emergency

112

Supplier

+49 2251 77 69 400-401

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.
Aerosol 1; H229 Pressurised container: May burst if heated.
Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.
Skin Irrit. 2; H315 Causes skin irritation.
Skin Sens. 1; H317 May cause an allergic skin reaction.
Eye Irrit. 2; H319 Causes serious eye irritation.
STOT SE 3; H336 May cause drowsiness or dizziness.
Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P302 + P352 + P362 + P364 IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

propan-2-ol (CAS: 67-63-0, EC: 200-661-7, Index: 603-117-00-0)

orange, sweet, ext. (CAS: 8028-48-6, EC: 232-433-8)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

Vapors can form an explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product description

The substance with CAS no. 8028-48-6 is a UVCB substance. Its main constituents are: (R)-p-mentha-1,8-diene (CAS: 5989-27-5), myrcene (CAS: 123-35-3) and alpha-pinene (CAS: 80-56-8).

3.1. Substances

For mixtures see 3.2.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
propan-2-ol	67-63-0 200-661-7 603-117-00-0	25-50	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336		01-2119457558-25
orange, sweet, ext.	8028-48-6 232-433-8 -	10-<25	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411		01-2119493353-35
butane [C]	106-97-8 203-448-7 601-004-00-0	10-25	Flam. Gas 1; H220 Press. Gas; H280		01-2119474691-32
isobutane [C, U]	75-28-5 200-857-2 601-004-00-0	10-25	Flam. Gas 1; H220 Press. Gas; H280		01-2119485395-27
propane [U]	74-98-6 200-827-9 601-003-00-5	2,5-10	Flam. Gas 1; H220 Press. Gas; H280		01-2119486944-21

Notes for substances:

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.
No action shall be taken involving any personal risk or without suitable training.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Keep at rest in a position comfortable for breathing. If symptoms develop and persist, seek medical attention. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Seek medical help immediately. In case of unconsciousness bring patient into stable side position and seek medical attention.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention. Wash contaminated clothes and shoes before reuse.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

Following ingestion

Not likely. Accidental ingestion: Rinse mouth thoroughly with water. Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.
Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.
Coughing, sneezing, nasal discharge, labored breathing.

Skin contact

Irritating to the skin.
Itching, redness, pain.
May cause sensitisation by skin contact (itching, redness, rashes).

Eye contact

Strongly irritates the eyes.
Redness, tearing, pain.

Ingestion

Not likely.
Accidental ingestion:
May cause abdominal discomfort.
May cause nausea/vomiting and diarrhea.
Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.
May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂).
Fire extinguishing powder.
Alcohol-resistant foam.
Water spray. Extinguish large fires with water spray or alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂). Smoke. Soot.

5.3. Advice for firefighters

Protective actions

In case of fire evacuate the area. In case of fire or heating do not breathe fumes/vapours. Vapours can form explosive mixtures with air. In case of fire aerosols can explode and be propelled to considerable distances in different directions. Cool containers at risk with water spray. If possible remove containers from endangered area. No action shall be taken involving any personal risk or without suitable training.



Product name: **Etikettenlöser**
Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! No action shall be taken involving any personal risk or without suitable training. Evacuate the danger zone. Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Avoid contact with skin, eyes and clothing. Do not breathe vapour or mist.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

Stem the spill if this does not pose risks.

6.3.2. For cleaning up

Prevent release into the sewer, water, basements or confined areas. Collect the spray cans and hand them over to an authorized waste disposal contractor. Release of liquid because of damaged aerosol can (release of large quantities): In case of bigger spill, dam the spillage, pump the liquid into appropriate labelled containers, absorb a residue with absorbent material and dispose of according to local regulations. Do not absorb spillage with sawdust or other combustible material. Dispose in accordance with applicable regulations (see Section 13). Clean residue from spill site.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Protect from open fire and other sources of ignition or heat. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Vapours and air form explosive mixtures. Take precautionary measures against static discharges. Use spark-proof tools.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Avoid release to the environment.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

7.1.2. Advice on general occupational hygiene

Refer to instructions on label and regulations for safety and health at work. Consider measures required in Section 8 of this safety data sheet. Use personal protective equipment. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in well closed containers. Keep in cool and well ventilated area. Keep away from sources of ignition - no smoking. Protect against heat and direct sunlight. Keep away from oxidising substances. Keep away from food, drink and animal feeding stuffs.

7.2.2. Packaging materials

The original container of producer.

7.2.3. Requirements for storage rooms and vessels

Do not store in unlabelled containers.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Propan-2-ol (67-63-0)	400	999	500	1250		
Butane (106-97-8)	600	1450	750	1810	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

8.1.3. DNEL/DMEL values

For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
propan-2-ol (67-63-0)	Worker	inhalation	long term (systemic effects)	500 mg/m ³	
propan-2-ol (67-63-0)	Worker	dermal	long term (systemic effects)	888 mg/kg bw/day	
propan-2-ol (67-63-0)	Consumer	inhalation	long term (systemic effects)	89 mg/m ³	
propan-2-ol (67-63-0)	Consumer	dermal	long term (systemic effects)	319 mg/kg bw/day	
propan-2-ol (67-63-0)	Consumer	oral	long term (systemic effects)	26 mg/kg bw/day	
orange, sweet, ext. (8028-48-6)	Worker	inhalation	long term (systemic effects)	31,1 mg/m ³	
orange, sweet, ext. (8028-48-6)	Worker	dermal	long term (systemic effects)	8,89 mg/kg bw/day	
orange, sweet, ext. (8028-48-6)	Worker	dermal	short term (local effects)	185,8 µg/cm ²	
orange, sweet, ext. (8028-48-6)	Consumer	inhalation	long term (systemic effects)	7,78 mg/m ³	
orange, sweet, ext. (8028-48-6)	Consumer	dermal	long term (systemic effects)	4,44 mg/kg bw/day	
orange, sweet, ext. (8028-48-6)	Consumer	dermal	short term (local effects)	92,9 µg/cm ²	
orange, sweet, ext. (8028-48-6)	Consumer	oral	long term (systemic effects)	4,44 mg/kg bw/day	

8.1.4. PNEC values

For components

Name	Exposure route	Value	Remark
propan-2-ol (67-63-0)	fresh water	140,9 mg/L	
propan-2-ol (67-63-0)	water, intermittent release	140,9 mg/L	fresh water
propan-2-ol (67-63-0)	marine water	140,9 mg/L	
propan-2-ol (67-63-0)	water treatment plant	2251 mg/L	
propan-2-ol (67-63-0)	fresh water sediment	552 mg/kg	dry weight
propan-2-ol (67-63-0)	marine water sediment	552 mg/kg	dry weight
propan-2-ol (67-63-0)	soil	28 mg/kg	dry weight
propan-2-ol (67-63-0)	food chain	160 mg/kg feed	oral
orange, sweet, ext. (8028-48-6)	fresh water	5,4 µg/L	
orange, sweet, ext. (8028-48-6)	marine water	0,54 µg/l	
orange, sweet, ext. (8028-48-6)	water, intermittent release	5,77 µg/l	fresh water
orange, sweet, ext. (8028-48-6)	water treatment plant	2,1 mg/L	
orange, sweet, ext. (8028-48-6)	fresh water sediment	1,3 mg/kg	dry weight
orange, sweet, ext. (8028-48-6)	marine water sediment	0,13 mg/kg	dry weight
orange, sweet, ext. (8028-48-6)	soil	0,261 mg/kg	dry weight

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols. Keep away from foodstuffs, beverages and feed. If technical measures to reduce workers' exposure are not sufficient, and the limit values of hazardous substances in the air are exceeded, it is necessary to use personal protective equipment.

Organisational measures to prevent exposure

If this product contains ingredients with exposure limits, personal, workplace atmosphere monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protection. Remove all contaminated clothes immediately and wash them before reuse.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**
Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. If the concentration limit values are exceeded, it is necessary to wear appropriate respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

-

8.2.3. Environmental exposure controls

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid; aerosol
-	Colour:	silver
-	Odour:	characteristic

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

Important health, safety and environmental information

-	pH	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	No information.
-	Evaporation rate	No information.
-	Flammability (solid, gas)	No information.
-	Explosion limits (vol%)	1,5 – 10,9 vol % (isobutane / propane) 1,5 – 8,5 vol % (butane)
-	Vapour pressure	2,3 hPa at 20 °C (orange, sweet, ext.)
-	Vapour density	No information.
-	Density	Density: 0,809 kg/L at 20 °C (data refers to the liquid portion of the product)
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	No information.
-	Oxidising properties	No information.

9.2. Other information

-	Weight organic solvents	680 g/l (VOC) 100 % (VOC)
-	Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended transport or storage conditions.

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

10.4. Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not expose to heat and direct sunlight. Do not store above 50°C.

10.5. Incompatible materials

Strong oxidising agents. Halogens. Halogenated compounds. Strong inorganic acids. Aldehydes. Peroxide.

10.6. Hazardous decomposition products

In case of fire/explosion vapours/gases that pose a health hazard are released.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
propan-2-ol (67-63-0)	inhalation	LC ₅₀	rat	4 h	> 20 mg/l		
propan-2-ol (67-63-0)	dermal	LD ₅₀	rabbit		> 2000 mg/kg		
propan-2-ol (67-63-0)	oral	LD ₅₀	rat		> 2000 mg/kg		

Additional information: The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

Name	Species	Time	Result	Method	Remark
propan-2-ol (67-63-0)			Non-irritant.		

Additional information: Causes skin irritation.

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
propan-2-ol (67-63-0)			Moderately irritating.		
orange, sweet, ext. (8028-48-6)			Irritating to skin.		

Additional information: Causes serious eye irritation.

(d) Respiratory or skin sensitisation

Name	Exposure route	Species	Time	Result	Method	Remark
propan-2-ol (67-63-0)	-			According to known data the substance is not a chemical sensitizer.		
orange, sweet, ext. (8028-48-6)	dermal			May cause sensitisation by skin contact.		

Additional information: May cause an allergic skin reaction.

(e) (Germ cell) mutagenicity

Name	Type	Species	Time	Result	Method	Remark
propan-2-ol (67-63-0)				The chemical is not classified as mutagenic.		

(f) Carcinogenicity

Name	Exposure route	Type	Species	Time	Value	Result	Method	Remark
propan-2-ol (67-63-0)						Substance is not classified as carcinogenic.		

(g) Reproductive toxicity

Name	Reproductive toxicity type	Type	Species	Time	Value	Result	Method	Remark
propan-2-ol (67-63-0)						The chemical is not classified as toxic for reproduction.		

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**
Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

(h) STOT-single exposure

Additional information: May cause drowsiness or dizziness.

(i) STOT-repeated exposure

Additional information: STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

Name	Result	Method	Remark
orange, sweet, ext. (8028-48-6)	Aspiration into the lungs can cause lung damage.		
orange, sweet, ext. (8028-48-6)	May be fatal if swallowed and enters airways.		

Additional information: May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
propan-2-ol (67-63-0)	LC ₅₀ /EC ₅₀ /IC ₅₀	100 – 1000 mg/L		fish			
	LC ₅₀ /EC ₅₀ /IC ₅₀	> 1000 mg/L		invertebrates			
	LC ₅₀ /EC ₅₀ /IC ₅₀	> 1000 mg/L		algae			
	LC ₅₀ /EC ₅₀ /IC ₅₀	> 1000 mg/L		bacteria			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

For components

Substance (CAS Nr.)	Type	Rate	Time	Evaluation	Method	Remark
propan-2-ol (67-63-0)	biodegradability	84 %	28 days			closed cup
orange, sweet, ext. (8028-48-6)	-			readily biodegradable		

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

For components

Substance (CAS Nr.)	Media	Value	Temperature	pH	Concentration	Method
propan-2-ol (67-63-0)	Octanol-water	0,05				

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**
Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Harmful to aquatic life with long lasting effects.
Water hazard class (WGK): 3 (Self-assessment), very hazardous for water.
Do not allow to reach ground water, water courses or sewage system.

For components

Substance: propan-2-ol

Low bioaccumulation potential.
Soluble in water.
It evaporates or dissolves in water within 24 hours. Larger amounts can penetrate the soil and pollute groundwater.

Substance: orange, sweet, ext.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Water hazard class 3 (Self-assessment): extremely hazardous for water.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Avoid release to the environment. Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Product and container must be disposed of safely.

Waste codes / waste designations according to LoW

16 05 04* - gases in pressure containers (including halons) containing dangerous substances

Packaging

Uncleaned containers should not be perforated, cut or welded. Pressurized container. Do not pierce or burn, even after use. Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

Waste codes / waste designations according to LoW

15 01 11* - metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2

14.4. Packing group

Not applicable.

14.5. Environmental hazards

NO.

14.6. Special precautions for user

IATA:

PCA Excepted quantities: E0

PCA Limited quantities: Y203

PCA limited quantity max net quantity: 30kgG

PCA packing instructions: 203

PCA max net quantity: 75kg

CAO packing instructions: 203

CAO max net quantity: 150kg

Special provisions: A145, A167, A802

ERG code: 10L

Limited quantities

1 L

Tunnel restriction code

(D)

IMDG EmS

F-D, S-U



14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.1.2. Ingredients according to Regulation EC 648/2004 on detergents

≥ 30%: aliphatic hydrocarbons; perfumes (Limonene)

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **Etikettenlöser**

Creation date: **3.9.2019** · Revision: **29.9.2020** · Version: **1**

(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.