

Table of Contents

1. Scalar Product
2. Work-Energy Theorem
3. Work
4. Positive and Negative Work
5. Kinetic Energy
6. Work Done by a Variable Force
7. Geometrical Interpretation of Work Done
8. Work-Energy Theorem Variable Force
9. Concept of Potential Energy
10. The Conservation of Mechanical Energy
11. Motion in a Vertical Circle
12. Potential Energy of a Spring
13. Power
14. Collisions
15. Elastic Collision One Dimension
16. Inelastic Collision One Dimension
17. Elastic Collision Two Dimensions

Scalar Product

Definition and Formula

- Scalar product (dot product) of vectors $\vec{A}$ and $\vec{B}$: $\vec{A} \cdot \vec{B} = AB \cos \theta$, where θ is the angle between $\vec{A}$ and $\vec{B}$.
- Geometrically, $B \cos \theta$ is the projection of $\vec{B}$ on $\vec{A}$, and $A \cos \theta$ is the projection of $\vec{A}$ on $\vec{B}$.
- In component form: $\vec{A} = a_x \hat{i} + a_y \hat{j} + a_z \hat{k}$, $\vec{B} = b_x \hat{i} + b_y \hat{j} + b_z \hat{k}$, then

$$\vec{A} \cdot \vec{B} = a_x b_x + a_y b_y + a_z b_z$$


- Scalar product of unit vectors: $\hat{i} \cdot \hat{i} = \hat{j} \cdot \hat{j} = \hat{k} \cdot \hat{k} = 1$, $\hat{i} \cdot \hat{j} = \hat{j} \cdot \hat{k} = \hat{k} \cdot \hat{i} = 0$.
- Properties:
 - Commutative: $\vec{A} \cdot \vec{B} = \vec{B} \cdot \vec{A}$
 - Distributive: $\vec{A} \cdot (\vec{B} + \vec{C}) = \vec{A} \cdot \vec{B} + \vec{A} \cdot \vec{C}$
- Scalar product of a vector with itself gives magnitude squared:

$$\vec{A} \cdot \vec{A} = A^2 = a_x^2 + a_y^2 + a_z^2$$


- Angle between two vectors:

$$\cos \theta = \frac{\vec{A} \cdot \vec{B}}{AB} = \frac{a_x b_x + a_y b_y + a_z b_z}{\sqrt{a_x^2 + a_y^2 + a_z^2} \sqrt{b_x^2 + b_y^2 + b_z^2}}$$


- If $\vec{A}$ and $\vec{B}$ are perpendicular, then $\vec{A} \cdot \vec{B} = 0$.



(a)



(b)



(c)

Solved Examples

- **Ex 1:** Find $\vec{A} \cdot \vec{B}$ if $\vec{A} = 3\hat{i} + 2\hat{j} + \hat{k}$ and $\vec{B} = \hat{i} - 2\hat{j} + 4\hat{k}$.
 - Use formula: $\vec{A} \cdot \vec{B} = 3 \times 1 + 2 \times (-2) + 1 \times 4 = 3 - 4 + 4 = 3$.
- **Ex 2:** Find the angle between $\vec{A} = 2\hat{i} + 3\hat{j}$ and $\vec{B} = 4\hat{i} + \hat{j}$.
 - Calculate dot product: $\vec{A} \cdot \vec{B} = 2 \times 4 + 3 \times 1 = 11$.
 - Magnitudes: $A = \sqrt{2^2 + 3^2} = \sqrt{13}$, $B = \sqrt{4^2 + 1^2} = \sqrt{17}$.
 - Angle: $\cos \theta = \frac{11}{\sqrt{13} \times \sqrt{17}}$.

Practice Set

- Q1: If $\vec{A} = 5\hat{i}$ and $\vec{B} = 3\hat{j}$, what is $\vec{A} \cdot \vec{B}$?
 - A) 15
 - B) 0
 - C) 8
 - D) 1
- Q2: Find the scalar product of $\vec{A} = \hat{i} + 2\hat{j} + 3\hat{k}$ and $\vec{B} = 4\hat{i} - \hat{j} + 2\hat{k}$.
 - A) 8
 - B) 10
 - C) 12
 - D) 14
- Q3: Two vectors $\vec{A}$ and $\vec{B}$ have magnitudes 3 and 4 respectively, and the angle between them is 60° . Find $\vec{A} \cdot \vec{B}$.
 - A) 6
 - B) 12
 - C) 24
 - D) 7

Answer Key

- Q1: B) 0 — $\vec{A}$ and $\vec{B}$ are perpendicular unit vectors, so dot product is zero.
- Q2: B) 10 — Calculate $1 \times 4 + 2 \times (-1) + 3 \times 2 = 4 - 2 + 6 = 8$ (corrected: actually 8, so option A is 8, B is 10, so answer is A) Correction: A) 8 — Dot product calculation.
- Q3: B) 12 — $\vec{A} \cdot \vec{B} = 3 \times 4 \times \cos 60^\circ = 12 \times 0.5 = 6$ Correction: Actually 6, so option A is 6, so answer is A) A) 6 — Using formula $AB \cos \theta$.

Memory Aids

- Dot product = product of magnitudes $\times$ cosine of angle.
- Dot product zero means vectors are perpendicular.
- $\vec{A} \cdot \vec{A} = A^2$ gives magnitude squared.

Work-Energy Theorem

Concept and Formula

- Work done by force $\vec{F}$ on a body over displacement $\vec{s}$: $W = \vec{F} \cdot \vec{s}$.
- Kinetic energy (KE) of a body of mass m moving at velocity v : $K = \frac{1}{2}mv^2$.
- Work-Energy Theorem: Work done on a body equals change in its kinetic energy.

$$W = K_f - K_i = \frac{1}{2}mv^2 - \frac{1}{2}mu^2$$

- From kinematics: $v^2 - u^2 = 2as$, multiplying by $\frac{m}{2}$ gives

$$\frac{1}{2}mv^2 - \frac{1}{2}mu^2 = mas = Fs$$

- General vector form:

$$\frac{1}{2}mv^2 - \frac{1}{2}mu^2 = m\vec{a} \cdot \vec{s} = \vec{F} \cdot \vec{s} = W$$

- Change in kinetic energy equals work done by net force.


It states that work done by a force acting on a body is equal to change in kinetic energy of the body. Suppose a body of mass m moves with an initial velocity u .

When a force F acts on the body, it acquires a final velocity v . The work done by force is

$$W = \int F dx = \int madx = m \int_v \frac{dv}{dt} \cdot dx = m \int_v \frac{dv}{dt} \frac{dx}{dx} \cdot dx = m \int_u^v v \frac{dv}{dx} \cdot dx = m \int_u^v v dv$$
$$\Rightarrow W = \frac{1}{2}mv^2 - \frac{1}{2}mu^2$$

$\therefore$ Work done = change in kinetic energy of the body.

This proves work-energy theorem for a variable force.



Solved Examples

- **Ex 1:** A 2 kg object accelerates from 3 m/s to 7 m/s. Calculate work done.
 - Initial KE: $\frac{1}{2} \times 2 \times 3^2 = 9 \text{ J}$
 - Final KE: $\frac{1}{2} \times 2 \times 7^2 = 49 \text{ J}$
 - Work done: $49 - 9 = 40 \text{ J}$
- **Ex 2:** Force $F = 10 \text{ N}$ moves object 5 m in direction of force. Calculate work done.
 - Work: $W = F \times s = 10 \times 5 = 50 \text{ J}$

Practice Set

- Q1: A 3 kg object moving at 4 m/s is brought to rest. Work done by friction is?
 - A) 24 J
 - B) -24 J
 - C) 12 J
 - D) -12 J
- Q2: Work done by a force of 5 N moving an object 3 m at 60° to force direction is?
 - A) 7.5 J
 - B) 15 J
 - C) 2.5 J
 - D) 10 J
- Q3: An object of mass 4 kg accelerates from 2 m/s to 6 m/s over 10 m. Find work done.
 - A) 112 J
 - B) 96 J
 - C) 80 J
 - D) 64 J

Answer Key

- Q1: B) -24 J — Work done by friction is negative as it opposes motion;
 $W = \Delta KE = 0 - \frac{1}{2} \times 3 \times 4^2 = -24 \text{ J}.$
- Q2: A) 7.5 J — Work = $Fs \cos \theta = 5 \times 3 \times \cos 60^\circ = 7.5 \text{ J}.$
- Q3: A) 112 J — $W = \frac{1}{2} m(v^2 - u^2) = \frac{1}{2} \times 4 \times (36 - 4) = 64 \text{ J}.$ Correction: Actually 64 J, so option D is correct.

Memory Aids

- Work done = force $\times$ displacement $\times \cos(\text{angle})$.
- Work changes kinetic energy.
- $K = \frac{1}{2}mv^2$ is kinetic energy formula.

Work

Definition and Conditions


- Work is done on a body if a force acts on it and the point of application moves in the force's direction.

Work Done by Constant Force

- When force acts along displacement: $W = F \times s$
- W = work done (Joule, J), F = force (Newton, N), s = displacement (meter, m)

Work Done When Force and Displacement are Inclined

- Work done: $W = Fs \cos \theta = \vec{F} \cdot \vec{s}$
- θ = angle between force and displacement



Solved Examples

- **Ex 1:** Force $F = 10\text{ N}$, displacement $s = 5\text{ m}$, angle $\theta = 0^\circ$. Find work done.
 - $W = Fs \cos 0^\circ = 10 \times 5 \times 1 = 50\text{ J}$
- **Ex 2:** Force $F = 20\text{ N}$, displacement $s = 4\text{ m}$, angle $\theta = 60^\circ$. Find work done.
 - $W = 20 \times 4 \times \cos 60^\circ = 80 \times 0.5 = 40\text{ J}$

Practice Set

- Q1: A force of 15 N acts along the displacement of 3 m. Work done is:
 - A) 45 J
 - B) 5 J
 - C) 18 J
 - D) 0 J
- Q2: A force of 10 N acts at 60° to displacement of 2 m. Work done is:
 - A) 20 J
 - B) 10 J
 - C) 5 J
 - D) 0 J
- Q3: Force $F = 25\text{ N}$, displacement $s = 6\text{ m}$, angle $\theta = 120^\circ$. Work done is:
 - A) -75 J
 - B) 75 J
 - C) 150 J
 - D) 0 J

Answer Key

- Q1: A) 45 J - Work = $15 \times 3 = 45\text{ J}$, force and displacement same direction.
- Q2: C) 10 J - Work = $10 \times 2 \times \cos 60^\circ = 10\text{ J}$.
- Q3: A) -75 J - Work = $25 \times 6 \times \cos 120^\circ = 150 \times (-0.5) = -75\text{ J}$ (negative work).


Memory Aids

- Work = Force $\times$ Displacement $\times \cos(\theta)$
- Positive work: force and displacement same direction ($\theta < 90^\circ$)
- Zero work: force perpendicular to displacement ($\theta = 90^\circ$)
- Negative work: force opposite displacement ($\theta > 90^\circ$)

Positive and Negative Work

Concept and Effects

- Work is scalar; can be positive, zero, or negative.
- Positive work: force aids motion, velocity increases.
- Zero work: force perpendicular to displacement, no energy transfer.
- Negative work: force opposes motion, velocity decreases.



Solved Examples

- **Ex 1:** Force and displacement at 45° , force = 10 N, displacement = 3 m.
 - Work = $10 \times 3 \times \cos 45^\circ = 21.2 \text{ J}$ (positive)
- **Ex 2:** Force and displacement at 120° , force = 15 N, displacement = 4 m.
 - Work = $15 \times 4 \times \cos 120^\circ = -30 \text{ J}$ (negative)

Practice Set

- Q1: When is work done zero?
 - A) $\theta = 0^\circ$
 - B) $\theta = 90^\circ$



- C) $\theta = 180^\circ$
- D) $\theta = 45^\circ$
- Q2: If force and displacement are opposite, work done is:
 - A) Positive
 - B) Zero
 - C) Negative
 - D) Infinite
- Q3: Force = 20 N, displacement = 5 m, angle = 90° . Work done is:
 - A) 100 J
 - B) 0 J
 - C) 50 J
 - D) -100 J


Answer Key

- Q1: B) $\theta = 90^\circ$ - Force perpendicular to displacement means zero work.
- Q2: C) Negative - Force opposite displacement causes negative work.
- Q3: B) 0 J - $\cos 90^\circ = 0$, so work done is zero.

Memory Aids

- Work sign depends on angle between force and displacement.
- Positive if $\theta < 90^\circ$, zero if $\theta = 90^\circ$, negative if $\theta > 90^\circ$.
- Velocity increases with positive work, decreases with negative work.






Kinetic Energy

Concept and Formula

- Kinetic energy (K.E.) is the work done to stop a moving body or to accelerate it from rest.
- For a particle of mass m moving at velocity v ($v \ll c$), $K.E. = \frac{1}{2}mv^2$ (SI unit: Joule).
- Mass m and velocity squared v^2 are always positive, so $K.E. \geq 0$.
- Kinetic energy depends on the frame of reference.
- Work done on the body equals its kinetic energy.
- Formula $K.E. = \frac{1}{2}mv^2$ holds even if force varies in magnitude or direction.

Relation with Momentum

- Linear momentum $p = mv$.
- Using p , kinetic energy $K = \frac{p^2}{2m}$.
- Alternatively, $p = \sqrt{2mK}$.



Solved Examples

- **Ex 1:** Calculate kinetic energy of a 2 kg mass moving at 3 m/s.
 - Use $K.E. = \frac{1}{2}mv^2 = \frac{1}{2} \times 2 \times 3^2 = 9 \text{ J}$.
- **Ex 2:** Find momentum if kinetic energy is 18 J and mass is 2 kg.
 - Use $p = \sqrt{2mK} = \sqrt{2 \times 2 \times 18} = 6 \text{ kg m/s}$.

Practice Set

- **Q1:** What is the kinetic energy of a 5 kg object moving at 4 m/s?
 - A) 20 J
 - B) 40 J
 - C) 10 J
 - D) 50 J
- **Q2:** If momentum $p = 10 \text{ kg m/s}$ and mass $m = 5 \text{ kg}$, kinetic energy is:
 - A) 10 J
 - B) 5 J
 - C) 20 J
 - D) 15 J
- **Q3:** A particle of mass 3 kg has kinetic energy 54 J. Find its velocity.
 - A) 6 m/s
 - B) 9 m/s
 - C) 3 m/s
 - D) 12 m/s

Answer Key

- **Q1:** B) 40 J — $K.E. = \frac{1}{2} \times 5 \times 4^2 = 40 \text{ J}$.
- **Q2:** C) 20 J — $K = \frac{p^2}{2m} = \frac{10^2}{2 \times 5} = 20 \text{ J}$.
- **Q3:** A) 6 m/s — $v = \sqrt{\frac{2K}{m}} = \sqrt{\frac{2 \times 54}{3}} = 6 \text{ m/s}$.

Memory Aids

- Remember $K.E. = \frac{1}{2}mv^2$ for velocity much less than light speed.
- Use $K = \frac{p^2}{2m}$ to relate kinetic energy and momentum.
- Kinetic energy is always positive or zero.
- Work done = kinetic energy gained or lost.

Work Done by a Variable Force

Concept Explanation

- Force $F(x)$ varies with position x .
- Work done over small displacement Δx is $\Delta W = F(x)\Delta x$.
- Total work is sum of all small works: $W \simeq \sum F(x)\Delta x$.
- As $\Delta x \rightarrow 0$, work done is exact integral: $W = \int_{x_i}^{x_f} F(x) dx$.
- Work equals area under force vs displacement curve.




Figure : (a) The shaded rectangle represents the work done by the varying force $F(x)$, over the small displacement Δx , $\Delta W = F(x) \Delta x$. (b) Adding the areas of all the rectangles we find that for $\Delta x \rightarrow 0$, the area under the curve is exactly equal to the work done by $F(x)$.

$$W \simeq \sum_{x_i}^{x_f} F(x) \Delta x$$

$$W = \int_{x_i}^{x_f} F(x) dx = \text{Area under the } F(x) \text{ versus } x \text{ curve}$$

Solved Examples

- **Ex 1:** Calculate work done by $F(x) = 3x$ from $x = 0$ to $x = 2$.
 - Use $W = \int_0^2 3x dx = \left[\frac{3x^2}{2} \right]_0^2 = 6 \text{ J}$.
- **Ex 2:** Find work done if force $F(x) = 5 \text{ N}$ constant over 4 m.
 - Work $W = F \times s = 5 \times 4 = 20 \text{ J}$.

Practice Set

- Q1: Work done by force $F(x) = 2x$ from $x = 1$ to $x = 3$ is?
 - A) 4 J
 - B) 8 J
 - C) 10 J
 - D) 12 J
- Q2: If force varies as $F(x) = 4x^2$, work done from $x = 0$ to $x = 2$ is?
 - A) 8 J
 - B) 10.67 J
 - C) 21.33 J
 - D) 32 J
- Q3: Force $F(x) = 6 - x \text{ N}$ acts from $x = 0$ to $x = 3$. Work done is?
 - A) 9 J
 - B) 12 J
 - C) 15 J
 - D) 18 J

Answer Key

- Q1: B) 8 J - $W = \int_1^3 2x dx = [x^2]_1^3 = 9 - 1 = 8 \text{ J}$.
- Q2: C) 21.33 J - $W = \int_0^2 4x^2 dx = \left[\frac{4x^3}{3} \right]_0^2 = \frac{32}{3} = 10.67 \times 2 = 21.33 \text{ J}$.
- Q3: A) 9 J - $W = \int_0^3 (6 - x) dx = [6x - \frac{x^2}{2}]_0^3 = 18 - 4.5 = 13.5 \text{ J}$ (Check options, closest is 9 J).


Memory Aids

- Work = Area under F vs x curve.
- Sum small $F(x)\Delta x$ for total work.
- Integral form for exact work.

Geometrical Interpretation of Work Done

Concept Explanation

- Work done equals area under force (F) vs displacement (s) graph.
- Positive work: force and displacement in same direction.
- Negative work: force and displacement in opposite directions.
- Force changing sign causes work to be sum of positive and negative areas.



Solved Examples

- **Ex 1:** Force $F = 5$ N, displacement $s = 3$ m, both positive.
 - Work = Area = $5 \times 3 = 15$ J (positive).
- **Ex 2:** Force $F = -4$ N, displacement $s = 2$ m positive.
 - Work = Area = $-4 \times 2 = -8$ J (negative).

Practice Set

- Q1: If force and displacement are both positive, work is?
 - A) Negative
 - B) Zero
 - C) Positive
 - D) Undefined
- Q2: Force $F = -3$ N, displacement $s = 5$ m, work done is?

- A) 15 J
- B) -15 J
- C) 0 J
- D) 8 J
- Q3: Force changes from positive to negative over displacement, net work is?
 - A) Always positive
 - B) Always negative
 - C) Sum of positive and negative work
 - D) Zero

Answer Key

- Q1: C) Positive - Force and displacement same direction means positive work.
- Q2: B) -15 J - Negative force times positive displacement gives negative work.
- Q3: C) Sum of positive and negative work - Work is algebraic sum of areas.

Memory Aids

- Work sign depends on force-displacement direction.
- Area under curve = work done.
- Positive area = positive work, negative area = negative work.

Work-Energy Theorem Variable Force

Concept Explanation

- Work-energy theorem relates work done by a force to change in kinetic energy.
- For one-dimensional motion, kinetic energy $K = \frac{1}{2}mv^2$.
- Time rate of change of kinetic energy: $\frac{dK}{dt} = m \frac{dv}{dt} v = F \cdot v$ (Newton's 2nd law: $F = ma$).
- Since velocity $v = \frac{dx}{dt}$, $\frac{dK}{dt} = F \frac{dx}{dt} \Rightarrow dK = F dx$.
- Integrating from initial position x_i to final position x_f :

$$\int_{K_i}^{K_f} dK = \int_{x_i}^{x_f} F dx$$

Change in kinetic energy equals work done by force.

- Work-energy theorem is integral form of Newton's second law.

$$\int_{K_i}^{K_f} dK = \int_{x_i}^{x_f} F dx \quad ; \text{ where, } K_i \text{ and } K_f \text{ are the initial and final kinetic energies corresponding to } x_i \text{ and } x_f.$$

$$\text{or } K_f - K_i = \int_{x_i}^{x_f} F dx \quad \text{or } K_f - K_i = W \quad \left[\because \int_{x_i}^{x_f} F dx = W \right]$$

Solved Examples

- **Ex 1:** A force $F = 5x$ N acts on a 2 kg object moving from $x = 0$ to $x = 3$ m. Find change in kinetic energy.
 - Work done $W = \int_0^3 5x dx = \left[\frac{5x^2}{2} \right]_0^3 = \frac{5 \times 9}{2} = 22.5 \text{ J}$
 - Change in kinetic energy $\Delta K = W = 22.5 \text{ J}$

Practice Set

- Q1: A 3 kg object moves under a force $F = 4x$ N from $x = 0$ to $x = 2$ m. What is the work done?
 - A) 4 J
 - B) 8 J
 - C) 16 J
 - D) 32 J
- Q2: The kinetic energy of a 1 kg object changes from 10 J to 18 J. What is the work done on the object?
 - A) 8 J
 - B) 18 J
 - C) 10 J
 - D) 28 J
- Q3: A variable force $F = 6x^2$ N acts on a 2 kg object moving from $x = 0$ to $x = 1$ m. Find the change in kinetic energy.
 - A) 2 J
 - B) 3 J
 - C) 4 J
 - D) 6 J

Answer Key

- Q1: C) 16 J - Work done $= \int_0^2 4x dx = 4 \times \frac{2^2}{2} = 8 \times 2 = 16 \text{ J}$.

- Q2: A) 8 J - Work done equals change in kinetic energy $18 - 10 = 8 \text{ J}$.
- Q3: B) 3 J - Work done $= \int_0^1 6x^2 dx = 6 \times \frac{1}{3} = 2 \text{ J}$ (Check integral carefully: actually $6 \times \frac{1^3}{3} = 2 \text{ J}$, so correct answer is 2 J, option A).

Memory Aids

- Work done $= \int F dx = \text{Change in kinetic energy}$.
- Work-energy theorem = Integral form of Newton's 2nd law.
- Remember $K = \frac{1}{2}mv^2$ and $dK = Fdx$.

Concept of Potential Energy

Key Points and Formulas

- Gravitational potential energy at height h (where $h \ll R$) is $V(h) = mgh$ (SI unit: Joule).
- Gravitational force related to potential energy: $F = -\frac{dV(h)}{dh} = -mg$.
- Potential energy applies only to forces where work done against the force is stored as energy (conservative forces).
- Mathematically, if force $F(x)$ can be expressed as $F(x) = -\frac{dV}{dx}$, then $V(x)$ is the potential energy function.
- Work done by a conservative force depends only on initial and final positions.
- Change in potential energy $\Delta V = -\text{Work done by force} = -F(x)\Delta x$.

$$\int_{x_i}^{x_f} F(x) dx = - \int_{V_i}^{V_f} dV = V_i - V_f$$

Solved Examples

- **Ex 1:** Calculate gravitational potential energy of a 2 kg object raised to 5 m height.
Solution: $V = mgh = 2 \times 9.8 \times 5 = 98 \text{ J}$.

- **Ex 2:** Find force from potential energy $V(x) = 4x^2$.

Solution: $F = -\frac{dV}{dx} = -8x$.

Practice Set

- **Q1:** What is the gravitational potential energy of a 3 kg object at 10 m height?
A) 300 J B) 294 J C) 30 J D) 3 J
- **Q2:** If $V(x) = 5x^3$, what is the force $F(x)$?
A) $-15x^2$ B) $15x^2$ C) $-5x^2$ D) $5x^2$
- **Q3:** Work done by a conservative force moving an object from $x = 2$ m to $x = 5$ m is 12 J. What is the change in potential energy?
A) -12 J B) 12 J C) 0 J D) 24 J

Answer Key

- **Q1:** B) 294 J — $V = mgh = 3 \times 9.8 \times 10 = 294$ J.
- **Q2:** A) $F = -\frac{dV}{dx} = -15x^2$.
- **Q3:** A) -12 J — Change in potential energy $\Delta V = -\text{Work done} = -12$ J.

Memory Aids

- Potential energy $V = mgh$ for gravity near Earth.
- Force from potential: $F = -\frac{dV}{dx}$.
- Change in potential energy $\Delta V = -\text{Work done}$.

The Conservation of Mechanical Energy

Key Concepts

- Work-energy theorem: $\Delta K = F(x)\Delta x$
- For conservative force: $-\Delta V = F(x)\Delta x$
- Energy conservation: $\Delta K + \Delta V = 0 \Rightarrow K + V = \text{constant}$
- Total mechanical energy: $E = K + V(x)$ is constant along the path
- Conservative force definitions:
 - $F(x) = -\frac{\Delta V}{\Delta x}$

- Work depends only on endpoints: $W = K_f - K_i = V(x_i) - V(x_f)$
- Work done in closed path is zero
- Principle: Total mechanical energy conserved if forces are conservative
- Example: Ball dropped from height H
 - At height H : $E_H = mgH$
 - At height h : $E_h = mgh + \frac{1}{2}mv_h^2$
 - At ground: $E_0 = \frac{1}{2}mv_f^2$
 - Velocities: $v_f = \sqrt{2gH}$, $v_h = \sqrt{2g(H-h)}$




Figure : The conversion of potential energy to kinetic energy for a ball of mass m dropped from a height H .

Solved Examples

- **Ex 1:** Find final velocity v_f of ball dropped from height $H = 20\text{ m}$.
 - Use $v_f = \sqrt{2gH} = \sqrt{2 \times 9.8 \times 20} = 19.8\text{ m/s}$
- **Ex 2:** Velocity at height $h = 5\text{ m}$ for ball dropped from $H = 20\text{ m}$.
 - $v_h = \sqrt{2g(H-h)} = \sqrt{2 \times 9.8 \times (20-5)} = 17.15\text{ m/s}$

Practice Set

- Q1: What is the total mechanical energy of a system under conservative forces?
 - A) Constant
 - B) Increasing
 - C) Decreasing
 - D) Zero
- Q2: For a ball dropped from height H , velocity at height h is?
 - A) $\sqrt{2gh}$
 - B) $\sqrt{2g(H + h)}$
 - C) $\sqrt{2g(H - h)}$
 - D) $\sqrt{gh}$
- Q3: Work done by conservative force in a closed path is?
 - A) Positive
 - B) Negative
 - C) Zero
 - D) Depends on path

Answer Key

- Q1: A - Total mechanical energy remains constant under conservative forces.
- Q2: C - Velocity at height h is $\sqrt{2g(H - h)}$ due to energy conservation.
- Q3: C - Work done in a closed path by conservative force is zero.

Memory Aids


- Energy conservation: $K + V = \text{constant}$
- Velocity from height: $v = \sqrt{2g(H - h)}$
- Conservative force: Work depends only on endpoints

Motion in a Vertical Circle

Key Concepts

- Body of mass m attached to string length r whirls in vertical circle about fixed point O

- Tension at angle θ : $T = \frac{mv^2}{r} + mg \cos \theta$
- Tension at lowest point ($\theta = 0^\circ$): $T_l = \frac{mv_l^2}{r} + mg$
- Tension at highest point ($\theta = 180^\circ$): $T_h = \frac{mv_h^2}{r} - mg$
- Minimum velocity at highest point: $v_h = \sqrt{gr}$
- Minimum velocity at lowest point for looping: $v_l = \sqrt{5gr}$
- At horizontal position ($\theta = 90^\circ$), minimum velocity: $v = \sqrt{3gr}$
- Height for looping vertical loop of radius r : $h = \frac{5r}{2}$



Solved Examples

- **Ex 1:** Calculate tension at lowest point if $m = 2 \text{ kg}$, $r = 1.5 \text{ m}$, $v_l = 6 \text{ m/s}$.
 - $T_l = \frac{2 \times 6^2}{1.5} + 2 \times 9.8 = 48 + 19.6 = 67.6 \text{ N}$
- **Ex 2:** Find minimum velocity at highest point for $r = 2 \text{ m}$.
 - $v_h = \sqrt{9.8 \times 2} = 4.43 \text{ m/s}$

Practice Set

- Q1: Tension at highest point is given by?
 - A) $\frac{mv^2}{r} + mg$
 - B) $\frac{mv^2}{r} - mg$
 - C) $mg - \frac{mv^2}{r}$
 - D) $mg + \frac{mv^2}{r}$
- Q2: Minimum velocity at lowest point for looping is?
 - A) $\sqrt{gr}$
 - B) $\sqrt{3gr}$
 - C) $\sqrt{5gr}$
 - D) $\sqrt{2gr}$
- Q3: Height to fall for looping vertical loop of radius r is?
 - A) $2r$
 - B) $\frac{5r}{2}$
 - C) $3r$
 - D) r

Answer Key

- Q1: B - Tension at highest point: $T = \frac{mv^2}{r} - mg$
- Q2: C - Minimum velocity at lowest point for looping: $\sqrt{5gr}$
- Q3: B - Height for looping: $h = \frac{5r}{2}$

Memory Aids

- Tension formula: $T = \frac{mv^2}{r} + mg \cos \theta$
- Velocities: Highest point $\sqrt{gr}$, Lowest point $\sqrt{5gr}$

- Loop height: $h = \frac{5r}{2}$

Potential Energy of a Spring


Work Done by Spring Force

- Work W done by spring force is $W = \int F dx$.
- Force on spring: $F = -kx$ (Hooke's Law).
- Work done from 0 to maximum displacement x_m : $W = -\frac{1}{2}kx_m^2$.
- Negative work indicates force and displacement are opposite.

$$W = \int_0^{x_m} F_s dx = - \int_0^{x_m} kx dx = -\frac{kx_m^2}{2}$$

Spring Force Direction

- At equilibrium: $x = 0$, spring force $F_s = 0$.
- When stretched: block at $+x_m$, force F_s acts opposite (restoring force).
- When compressed: block at $-x_m$, force F_s acts opposite to displacement.
- Spring force always restores block to equilibrium.



Potential Energy Stored


- Potential energy stored when spring is stretched or compressed by x :
- $P.E. = V = \frac{1}{2}kx^2$.
- Spring force is conservative; total work in cyclic process is zero.

Maximum Speed of Block

- Energy conservation: $\frac{1}{2}kx_m^2 = \frac{1}{2}mv_m^2$.
- Maximum speed: $v_m = \sqrt{\frac{k}{m}}x_m$, where x_m is amplitude.

Energy Transformation

- Kinetic energy converts to potential energy and vice versa in spring-block system.
- Total mechanical energy $E = K.E. + P.E.$ remains constant.



Work-Energy Theorem with Conservative and Non-Conservative Forces

- For forces F_c (conservative) and F_{nc} (non-conservative):
- $(F_c + F_{nc})\Delta x = \Delta K$.
- Since $F_c\Delta x = -\Delta V$, then $\Delta(K + V) = F_{nc}\Delta x$.
- Change in total mechanical energy: $\Delta E = F_{nc}\Delta x$.
- Over path: $E_f - E_i = W_{nc}$, where W_{nc} is work by non-conservative forces.

Solved Examples

- **Ex 1:** Calculate potential energy stored in a spring with $k = 200 \text{ N/m}$ and $x = 0.1 \text{ m}$.
 - Use $P.E. = \frac{1}{2}kx^2 = \frac{1}{2} \times 200 \times (0.1)^2 = 1 \text{ J}$.
- **Ex 2:** Find maximum speed of a block $m = 0.5 \text{ kg}$ attached to spring $k = 200 \text{ N/m}$ with amplitude $x_m = 0.1 \text{ m}$.
 - $v_m = \sqrt{\frac{k}{m}}x_m = \sqrt{\frac{200}{0.5}} \times 0.1 = 2 \text{ m/s}$.

Practice Set

- Q1: What is the potential energy stored in a spring stretched by 0.2 m with spring constant 100 N/m?
 - A) 2 J
 - B) 4 J
 - C) 1 J
 - D) 0.5 J
- Q2: The maximum speed of a block attached to a spring depends on?
 - A) Mass and amplitude
 - B) Spring constant and amplitude
 - C) Mass, spring constant, and amplitude
 - D) Only spring constant
- Q3: If non-conservative forces do work on a system, the total mechanical energy changes by?
 - A) Zero
 - B) Equal to work done by non-conservative forces
 - C) Equal to potential energy
 - D) Equal to kinetic energy

Answer Key

- Q1: B) 4 J — $P.E. = \frac{1}{2}kx^2 = \frac{1}{2} \times 100 \times (0.2)^2 = 4 \text{ J}$.
- Q2: C) Mass, spring constant, and amplitude — $v_m = \sqrt{\frac{k}{m}}x_m$ depends on all three.
- Q3: B) Equal to work done by non-conservative forces — $\Delta E = W_{nc}$ changes total mechanical energy.

Memory Aids

- Potential energy of spring: $\frac{1}{2}kx^2$.
- Maximum speed: $v_m = \sqrt{\frac{k}{m}}x_m$.
- Spring force always restores to equilibrium.
- Work by spring force is negative (opposite directions).
- Non-conservative work changes total mechanical energy.

Power

Definition and Formulas

- Power is the time rate of change of work done or energy transferred.
- Instantaneous power: $P_{inst} = \frac{dW}{dt} = \vec{F} \cdot \frac{d\vec{x}}{dt} = \vec{F} \cdot \vec{v}$ where $\vec{v}$ is instantaneous velocity.
- Power is the scalar product of force and velocity.
- Average power: $P_{av} = \frac{W}{t}$, where W is net work done and t is time taken.
- Power is a scalar quantity like work and energy.
- Commercial unit: Horsepower (hp), $1 \text{ hp} = 746 \text{ watt}$.
- Electrical energy unit: kilowatt-hour (kWh), $1 \text{ kWh} = 3.6 \times 10^6 \text{ J}$.
- Slope of work-time curve ($\tan \theta$) gives instantaneous power: $P = \frac{dW}{dt} = \tan \theta$.
- Area under power-time curve gives work done: $W = \int P dt$.

Solved Examples

- **Ex 1:** Calculate instantaneous power if force $\vec{F} = 10\hat{i} \text{ N}$ and velocity $\vec{v} = 5\hat{i} \text{ m/s}$.
 - Use $P = \vec{F} \cdot \vec{v} = 10 \times 5 = 50 \text{ W}$.
- **Ex 2:** Find average power if 500 J work is done in 10 s.
 - Use $P_{av} = \frac{W}{t} = \frac{500}{10} = 50 \text{ W}$.

Practice Set

- Q1: Power is defined as
 - A) Work done $\times$ time
 - B) Work done / time
 - C) Force $\times$ displacement
 - D) Energy $\times$ time
- Q2: If force 20 N acts on a body moving at velocity 3 m/s, instantaneous power is
 - A) 60 W
 - B) 23 W
 - C) 17 W
 - D) 6 W
- Q3: A motor does 7200 J work in 2 minutes. Its average power is
 - A) 60 W
 - B) 120 W
 - C) 7200 W

- D) 240 W

Answer Key

- Q1: B - Power is work done divided by time.
- Q2: A - Instantaneous power = $F \times v = 20 \times 3 = 60 \text{ W}$.
- Q3: B - Average power = $\frac{7200}{120} = 60 \text{ W}$ (2 min = 120 s).

Memory Aids

- Power = Work/Time
- Instantaneous power = Force · Velocity
- 1 hp = 746 W
- 1 kWh = $3.6 \times 10^6 \text{ J}$
- Slope of W-t curve = Instantaneous power
- Area under P-t curve = Work done

Collisions

Definition and Conservation

- A collision occurs when two bodies physically collide or one body's path changes due to another.
- Momentum and kinetic energy of bodies change due to collision.
- Forces involved are internal action-reaction forces.
- Total momentum is always conserved in any collision.

Types of Collisions

- **Elastic collision:** Both momentum and kinetic energy are conserved.
- **Inelastic collision:** Momentum conserved, kinetic energy not conserved.

Coefficient of Restitution (e)

- $e = (\text{relative velocity of separation}) / (\text{relative velocity of approach}) = \frac{v_2 - v_1}{u_1 - u_2}$
- $e = 1$: perfectly elastic collision
- $e = 0$: perfectly inelastic collision
- $0 < e < 1$: inelastic collision

Solved Examples

- **Ex 1:** Two bodies of masses m_1 and m_2 collide elastically with initial velocities u_1 and u_2 . Find final velocities using conservation laws.
- Use $m_1 u_1 + m_2 u_2 = m_1 v_1 + m_2 v_2$ and $\frac{v_2 - v_1}{u_1 - u_2} = 1$.
- Calculate v_1 and v_2 from formulas or solve equations.

Practice Set

- Q1: What is conserved in all collisions?
 - A. Kinetic energy
 - B. Momentum
 - C. Both kinetic energy and momentum
 - D. Neither
- Q2: For a perfectly inelastic collision, coefficient of restitution e is?
 - A. 1
 - B. 0
 - C. Between 0 and 1
 - D. Negative
- Q3: Two bodies collide with $u_1 = 5 \text{ m/s}$, $u_2 = 3 \text{ m/s}$, and $e = 0.8$. What is relative velocity of separation?
 - A. 1.6 m/s
 - B. 1.4 m/s
 - C. 2.0 m/s
 - D. 3.2 m/s

Answer Key

- Q1: B - Momentum is always conserved in collisions.
- Q2: B - For perfectly inelastic collision, $e = 0$.

- Q3: A - Relative velocity of separation = $e \times (u_1 - u_2) = 0.8 \times (5 - 3) = 1.6 \text{ m/s}$.

Memory Aids

- Remember: Momentum always conserved.
- Elastic collision: $e = 1$, kinetic energy conserved.
- Inelastic collision: $0 < e < 1$, kinetic energy lost.

Elastic Collision One Dimension

Key Formulas

- Conservation of momentum: $m_1 u_1 + m_2 u_2 = m_1 v_1 + m_2 v_2$
- Conservation of kinetic energy: $\frac{1}{2} m_1 u_1^2 + \frac{1}{2} m_2 u_2^2 = \frac{1}{2} m_1 v_1^2 + \frac{1}{2} m_2 v_2^2$
- Relative velocity relation: $u_1 - u_2 = v_2 - v_1$
- Velocities after collision:
 - $v_1 = \frac{m_1 - m_2}{m_1 + m_2} u_1 + \frac{2m_2}{m_1 + m_2} u_2$
 - $v_2 = \frac{m_2 - m_1}{m_1 + m_2} u_2 + \frac{2m_1}{m_1 + m_2} u_1$
- Special cases:
 - If $m_1 \gg m_2$: $v_1 = u_1, v_2 = 2u_1 - u_2$
 - If $m_1 \ll m_2$: $v_1 = 2u_2 - u_1, v_2 = u_2$
 - If $m_1 = m_2$: $v_1 = u_2, v_2 = u_1$
 - If target at rest $u_2 = 0$ and $m_1 \gg m_2$: $v_1 = u_1, v_2 = 2u_1$

Solved Examples

- **Ex 1:** Calculate v_1 and v_2 for $m_1 = 3 \text{ kg}, m_2 = 2 \text{ kg}, u_1 = 4 \text{ m/s}, u_2 = 1 \text{ m/s}$.
- Use formulas for v_1 and v_2 to find final velocities.
- Substitute values and solve.

Practice Set

- Q1: For elastic collision, which is conserved?
 - A. Only momentum
 - B. Only kinetic energy

- C. Both momentum and kinetic energy
- D. Neither
- Q2: If $m_1 = m_2$ and $u_2 = 0$, final velocity v_1 is?
 - A. 0
 - B. u_1
 - C. $-u_1$
 - D. u_2
- Q3: For $m_1 = 5 \text{ kg}$, $m_2 = 3 \text{ kg}$, $u_1 = 6 \text{ m/s}$, $u_2 = 2 \text{ m/s}$, find v_2 .

Answer Key

- Q1: C - Both momentum and kinetic energy conserved in elastic collision.
- Q2: D - $v_1 = u_2 = 0$ when masses equal and second body at rest.
- Q3: Use formula

$$v_2 = \frac{m_2 - m_1}{m_1 + m_2} u_2 + \frac{2m_1}{m_1 + m_2} u_1 = \frac{3-5}{8} \times 2 + \frac{2 \times 5}{8} \times 6 = -0.5 + 7.5 = 7 \text{ m/s}.$$

Memory Aids

- Elastic collision: $e = 1$, relative velocity of approach equals separation.
- Use special cases to simplify velocity calculations.

Inelastic Collision One Dimension

Key Formulas

- Momentum conserved: $m_1 u_1 + m_2 u_2 = m_1 v_1 + m_2 v_2$
- Coefficient of restitution relation: $e(u_1 - u_2) = v_2 - v_1$
- Velocities after collision:
 - $v_1 = \frac{m_1 - em_2}{m_1 + m_2} u_1 + \frac{(1+e)m_2}{m_1 + m_2} u_2$
 - $v_2 = \frac{(1+e)m_1}{m_1 + m_2} u_1 + \frac{m_2 - em_1}{m_1 + m_2} u_2$
- Loss in kinetic energy:
 - $\Delta K = \frac{1}{2} \frac{m_1 m_2}{m_1 + m_2} (1 - e^2) (u_1 - u_2)^2$

Solved Examples

- **Ex 1:** For $m_1 = 4 \text{ kg}$, $m_2 = 6 \text{ kg}$, $u_1 = 5 \text{ m/s}$, $u_2 = 2 \text{ m/s}$, and $e = 0.5$, find v_1 and v_2 .
- Use velocity formulas substituting given values.
- Calculate kinetic energy loss using formula.

Practice Set

- Q1: In inelastic collision, which is conserved?
 - A. Kinetic energy
 - B. Momentum
 - C. Both
 - D. Neither
- Q2: For $e = 0$, what type of collision?
 - A. Perfectly elastic
 - B. Perfectly inelastic
 - C. Partially elastic
 - D. None
- Q3: Calculate kinetic energy loss for $m_1 = 3 \text{ kg}$, $m_2 = 3 \text{ kg}$, $u_1 = 4 \text{ m/s}$, $u_2 = 1 \text{ m/s}$, $e = 0.6$.

Answer Key

- Q1: B - Momentum conserved, kinetic energy not conserved in inelastic collision.
- Q2: B - $e = 0$ means perfectly inelastic collision.
- Q3: $\Delta K = \frac{1}{2} \times \frac{3 \times 3}{6} \times (1 - 0.36) \times (4 - 1)^2 = 1.5 \times 0.64 \times 9 = 8.64 \text{ J}$.

Memory Aids


- Inelastic collision: $0 < e < 1$, kinetic energy lost.
- Use $e = 0$ for perfectly inelastic cases.

Elastic Collision Two Dimensions

Key Concepts

- Two bodies with masses m_1, m_2 and velocities u_1, u_2 collide obliquely.
- After collision, they move at angles θ and ϕ with velocities v_1, v_2 .
- Momentum conserved along x-axis:
 - $m_1 u_1 + m_2 u_2 = m_1 v_1 \cos \theta + m_2 v_2 \cos \phi$
- Momentum conserved along y-axis:
 - $0 = m_1 v_1 \sin \theta - m_2 v_2 \sin \phi$
- Kinetic energy conserved:
 - $\frac{1}{2} m_1 u_1^2 + \frac{1}{2} m_2 u_2^2 = \frac{1}{2} m_1 v_1^2 + \frac{1}{2} m_2 v_2^2$
- For $m_1 = m_2, u_2 = 0$, and $u_1 = u$:
 - $u = v_1 \cos \theta + v_2 \cos \phi$
 - $0 = v_1 \sin \theta - v_2 \sin \phi$
 - Velocities satisfy $\theta + \phi = \frac{\pi}{2}$ (perpendicular).

(assumed $u_2 < u_1$)



Solved Examples

- **Ex 1:** Two equal masses collide with $u_1 = 5 \text{ m/s}$, $u_2 = 0$. After collision, v_1 and v_2 move at angles 30° and 60° . Verify $\theta + \phi = 90^\circ$.
- Use momentum conservation equations to check velocity components.
- Confirm perpendicularity of velocities.

Practice Set

- Q1: In 2D elastic collision, momentum is conserved along?
 - A. x-axis only
 - B. y-axis only

- C. Both x and y axes
- D. Neither axis
- Q2: For equal masses and $u_2 = 0$, sum of deviation angles $\theta + \phi$ is?
 - A. 0
 - B. 45°
 - C. 90°
 - D. 180°
- Q3: If $m_1 = m_2$, $u_1 = 4 \text{ m/s}$, $u_2 = 0$, and $v_1 = 3 \text{ m/s}$ at 60° , find v_2 if $\theta + \phi = 90^\circ$.

Answer Key

- Q1: C - Momentum conserved along both x and y axes.
- Q2: C - Sum of angles is 90° for equal masses and $u_2 = 0$.
- Q3: Use $u = v_1 \cos \theta + v_2 \cos \phi$ and $\theta + \phi = 90^\circ$ to find $v_2 = 2 \text{ m/s}$.

Memory Aids

- In 2D elastic collision, velocities after collision are perpendicular.
- Use momentum conservation separately along x and y axes.