

Splitter Panels

Standard and Customised Solutions




PRODUCT FEATURES

- Customised
- Wall-, floor-, combiner- and 19" rackmounted
- For FM, DAB, VHF and UHF
- Easy-switched links

PRODUCT PROFILE

Exir Broadcasting offers patch splitter panels with various numbers of ports, and in most types and dimensions. A number of standard models are available as listed below, but normally units are unique and designed according to customer specifications. The panels are constructed with sturdy frames for mounting either on the floor, on combiner units, on the wall or in a 19" rack. Available with directional couplers and micro switch (interlock).



SPLITTER PANELS. All versions are available with interlocking on request. Customised versions on request.

ARTICLE	DIMENSION	PORTS	POWER @max freq.	SPLITTER	FRAME / RACK	RETURN LOSS	FREQUENCIES
BAND II							
PPS2158R-6301A	1 5/8" unflange	6-ports	15 kW	T-splitter	19" rack mounted	-32 dB	87 - 108 MHz
PPS2158R-7301A	1 5/8" unflange	7-ports	15 kW	T-splitter	19" rack mounted	-32 dB	87 - 108 MHz
PPS2158R-7301B	1 5/8" unflange	7-ports	15 kW	T-splitter	19" rack mounted	-32 dB	87 - 108 MHz
ULS2-158R-AA00	1 5/8" unflange	11-ports	15 kW	3dB-coupler	Frame mounted	-32 dB	87 - 108 MHz
ULS2-318R-AA00	3 1/8" unflange	6-ports	48 kW	T-splitter	19" rack mounted	-32 dB	87 - 108 MHz
ULS2-318R-AB00	3 1/8" unflange	6-ports	48 kW	T-splitter (8 MHz BW)	19" rack mounted	-32 dB	87 - 108 MHz
PPS2318R-6301A	3 1/8" unflange	6-ports	48 kW	T-splitter (compact)	19" rack mounted	-32 dB	87 - 108 MHz
PPS2412R-631A	4 1/2" unflange	6-ports	78 kW	3dB-coupler	19" rack mounted	-32 dB	87 - 108 MHz
ULS2-412R-AA00	4 1/2" unflange	6-ports	78 kW	T-splitter	19" rack mounted	-32 dB	87 - 108 MHz
ULS2-618R-AA00	6 1/8" unflange	6-ports	168 kW	T-splitter	Frame mounted	-32 dB	87 - 108 MHz
BAND III							
ULS3-158R-AA00	1 5/8" unflange	6-ports	10 kW	T-splitter	19" rack mounted	-32 dB	174 - 240 MHz
ULS3-158R-AB00	1 5/8" unflange	6-ports	10 kW	M-splitter	19" rack mounted	-32 dB	174 - 240 MHz
ULS3-318R-AA00	3 1/8" unflange	6-ports	30 kW	T-splitter	19" rack mounted	-32 dB	174 - 240 MHz
ULS3-318R-AC00	3 1/8" unflange	7-ports	30 kW	T-splitter	19" rack mounted	-32 dB	174 - 240 MHz
BAND IV/V							
ULS4-R158-AA00	1 5/8" unflange	6-ports	5 kW	3dB-coupler	Frame mounted	-30 dB	470 - 862 MHz
ULS4-158R-AE00	1 5/8" unflange	6-ports	5 kW	3dB-coupler	19" rack mounted	-30 dB	470 - 862 MHz
ULS4-158R-AG00	1 5/8" unflange	6-ports	5 kW	T-splitter	19" rack mounted	-30 dB	470 - 862 MHz
ULS4-158R-AF00	1 5/8" unflange	7-ports	5 kW	T-splitter	19" rack mounted	-30 dB	470 - 862 MHz
ULS4-R318-AA00	3 1/8" unflange	6-ports	17 kW	T-splitter	19" rack mounted	-30 dB	470 - 862 MHz
ULS4-318R-AB00	3 1/8" unflange	7-ports	17 kW	T-splitter	19" rack mounted	-30 dB	470 - 862 MHz
ULS4-412R-AC00	4 1/2" unflange	6-ports	29 kW	T-splitter	19" rack mounted	-30 dB	470 - 862 MHz
ULS4-412R-AA00	4 1/2" unflange	8-ports	29 kW	T-splitter	Frame mounted	-30 dB	470 - 862 MHz
ULS4-R120-A0	NAX120 unflange	6-ports	36 kW	3dB-coupler	Combiner mounted	-30 dB	470 - 862 MHz
ULS4-R120-AC00	NAX120 unflange	6-ports	36 kW	T-splitter	Frame mounted	-30 dB	470 - 862 MHz
ULS4-120R-AF00	NAX120 unflange	6-ports	36 kW	T-splitter	27" rack mounted	-30 dB	470 - 862 MHz
ULS4-120R-AD00	NAX120 unflange	8-ports	36 kW	T-splitter	Frame mounted	-30 dB	470 - 862 MHz