

DIN 24154	Innen Ø	Tolerance Ø	Breite x Stärke	Lochkreis Ø	Loch*	Loch Ø	Gewicht
Reihe 2	Vnitřní Ø		Šířka x Síla	Roztečná kr. Ø	Počet děr	Otvor Ø	Váha
NW	di [mm]	[mm]	b x s [mm]	dk [mm]	z	d [mm]	[kg]
71	73	+1,0	30x6	110	4	9,5	0,44
80	82	+1,0	30x6	118	4	9,5	0,48
90	92	+1,0	30x6	128	4	9,5	0,53
100	102	+1,0	30x6	139	4	9,5	0,55
112	114	+1,0	30x6	151	4	9,5	0,63
125	127	+1,0	30x6	165	4	9,5	0,68
140	142	+1,5	35x6	182	8	11,5	0,87
150	152	+1,5	35x6	191	8	11,5	0,92
160	162	+1,5	35x6	200	8	11,5	0,98
180	182	+1,5	35x6	219	8	11,5	1,08
200	203	+1,5	35x6	241	8	11,5	1,19
224	227	+1,5	35x6	265	8	11,5	1,32
250	253	+1,5	35x6	292	8	11,5	1,45
280	283	+1,5	40x8	332	8	11,5	2,51
300	303	+1,5	40x8	352	8	11,5	2,75
315	318	+1,5	40x8	366	8	11,5	2,98
355	358	+1,5	40x8	405	8	11,5	3,10
400	404	+1,5	40x8	448	12	11,5	3,44
450	454	+1,5	40x8	497	12	11,5	3,84
500	504	+1,5	40x8	551	12	11,5	4,13
560	564	+2,0	50x8	629	16	14,0	5,90
600	604	+2,0	50x8	669	16	14,0	6,24
630	634	+2,0	50x8	698	16	14,0	6,59
710	714	+2,0	50x8	775	16	14,0	7,38
800	804	+2,0	50x8	861	24	14,0	8,19
900	904	+2,0	50x8	958	24	14,0	9,17
1000	1005	+2,0	50x8	1067	24	14,0	10,20
1120	1125	+2,0	60x10	1200	32	18,0	16,90
1250	1255	+2,0	60x10	1337	32	18,0	18,80
1400	1405	+2,0	60x10	1475	32	18,0	21,00
1600	1605	+2,0	60x10	1675	40	18,0	23,80
1800	1805	+2,0	60x10	1875	40	18,0	26,80
2000	2005	+2,0	60x10	2073	40	18,0	29,70

