

DIN 24154	Innen Ø	Tolerance Ø	Breite x Stärke	Lochkreis Ø	Loch*	Loch Ø	Gewicht
Reihe 4	Vnitřní Ø		Šířka x Síla	Roztečná kr. Ø	Počet děr	Otvor Ø	Váha
NW	di [mm]	[mm]	b x s [mm]	dk [mm]	z	d [mm]	[kg]
63	68	+1,0	30x6	102	4	9,5	0,44
71	76	+1,0	30x6	110	4	9,5	0,47
80	84	+1,0	30x6	118	4	9,5	0,51
90	94	+1,0	30x6	128	4	9,5	0,55
100	105	+1,0	30x6	139	4	9,5	0,60
112	117	+1,0	30x6	151	4	9,5	0,65
125	131	+1,0	30x6	165	4	9,5	0,71
140	146	+1,5	35x6	182	8	11,5	0,93
150	155	+1,5	35x6	191	8	11,5	0,97
160	164	+1,5	35x6	200	8	11,5	1,02
180	183	+1,5	35x6	219	8	11,5	1,12
200	205	+1,5	35x6	241	8	11,5	1,24
224	229	+1,5	35x6	265	8	11,5	1,36
250	256	+1,5	35x6	292	8	11,5	1,50
280	288	+1,5	40x8	332	8	11,5	2,58
300	308	+1,5	40x8	352	8	11,5	2,70
315	322	+1,5	40x8	366	8	11,5	2,85
355	361	+1,5	40x8	405	8	11,5	3,16
400	404	+1,5	40x8	448	12	11,5	3,49
450	453	+1,5	40x8	497	12	11,5	3,89
500	507	+1,5	40x8	551	12	11,5	4,30
560	569	+2,0	50x8	629	16	14,0	6,10
600	609	+2,0	50x8	669	16	14,0	6,44
630	638	+2,0	50x8	698	16	14,0	6,78
710	715	+2,0	50x8	775	16	14,0	7,53
800	801	+2,0	50x8	861	24	14,0	8,40
900	902	+2,0	50x8	958	24	14,0	9,30
1000	1007	+2,0	50x8	1067	24	14,0	10,40
1120	1130	+2,0	60x10	1200	32	18,0	17,60
1250	1267	+2,0	60x10	1337	32	18,0	19,60
1400	1421	+2,0	60x10	1491	32	18,0	21,90
1600	1593	+2,0	60x10	1663	40	18,0	24,40
1800	1786	+2,0	60x10	1856	40	18,0	27,30
2000	2003	+2,0	60x10	2073	40	18,0	30,50

