

XP-370B

Thermal Barcode Printer

Key features

- Thermal sensitive resistance, photoelectric sensor
- Serial+ USB interface
- Labels peel off, tear off automatically
- Support PDF417, QR CODE, Data matrix 2D Printing
- Embedded with internet default IP
- 100MB Ethernet interface connection, data transfer efficiency
- Black mark supported



Specifications

Model	XP-370B	XP-370BM
Printing method	Direct thermal	
Resolution	203dpi (8dots/mm)	
Paper width	16mm ~ 82mm	
Paper roll diameter	25mm (Min) for internal, 100mm (Max) for external	
Printing length (Max.)	1000mm	
Paper thickness	0.06mm ~ 0.19mm	
Printing speed	Min: 50.8mm/s Max: 152mm/s	
Print head temperature sensor	Thermal sensitive resistance	
Linear Bar Codes	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14	
Print head position sensor	Micro switch	
Media type	Paper roll, sticker, label fold, etc.	
2-Dimensional	PDF417、QR CODE、Data Matrix	
Paper off type	Tear off	Tear off or Peel off
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts	
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation	
Gross weight	1.50 kg	
Dimension	231(D) x 163(W) x 150.7(H)mm	
Work	5~45℃, 20~80%RH	
Storage	-40~55℃, ≤93%RH(40℃)	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Android/IOS	
Input	24VDC, 2.5A	
Paper exists detection	Photoelectric sensor	
Interface	USB	
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM	