

Product datasheet

Specifications



APC Easy UPS, 2200VA, Tower,
230V, 4x CEE 7/3 Schuko outlets,
AVR

BVX2200LI-GR

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Rated power in W	1200 W
Rated power in VA	2200 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	Schuko
output connection type	4 Schuko
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery life	2...3 year(s)
Replacement battery	APCRBC177
Extended runtime	0

General

Max runtime	240 min
Number of power module free slots	0
Number of power module filled slots	0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Redundant	No
UPS size	WS

Physical

Colour	Black
Height	19 cm
Width	14 cm
Depth	39 cm
Net weight	12.2 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.54

Output

Maximum configurable power in W	1200 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Graph display	1
Half load runtime	00:08:30 600 W
Maximum configurable power in VA	2200 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m

Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	49.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.2 kg
SCC14	10731304404627

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **Ef3b165e-8e1d-4ef1-89c3-03b78b282225**

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery **User replaceable**

Take-back **No**

Image of product / Alternate images

Alternative

