

WASTE WATER PUMPS

FEATURES	BENEFITS	COMPETITIVE ADVANTAGES
Single chamber	No In-line filter necessary	Run dry without damaging pump
Non-choke valve	Quiet operation	Market leading quiet operation
Low pulse muffled rubber bracket	Easy diaphragm replacement	Easy installation
Reinforced nitrile rubber diaphragm	Protected against ignition of flammable gases	Less expense to maintain
Multifunctional	Multiple application use	
ISO 8846 ignition protected motor	Rotating motor allows multi-configurable installation	
Rotating motor		

AVAILABLE SIZES

Viking Power 16 – 16L/min – 12 & 24V

Viking Power 32 – 32L/min – 12 & 24V

Viking Power Vacuum – 24L/min – 12 & 24V



Viking Power 16



Viking Power 32



Viking Power Vacuum

TECHNICAL SPECIFICATIONS

PART NUMBER	DESCRIPTION	CAPACITY AT OPEN FLOW	CAPACITY AT 0.1 BAR	MAX LIFT	MAX HEAD	CONNECTION
10-13350-03	Viking Power 16, 12V	16 l/min (4.2 GPM)	15 l/min (4.0 GPM)	3 m (9.8 ft)	3 m (9.8 ft)	KlickTite XL connectors for 1» hose or 3/4» hose and 1/2» BSP threads; straight and 90° (optional)
10-13350-04	Viking Power 16, 24V	16 l/min (4.2 GPM)	15 l/min (4.0 GPM)	3 m (9.8 ft)	3 m (9.8 ft)	
10-13373-03	Viking Power 32, 12V	32 l/min (8.5 GPM)	30 l/min (7.9 GPM)	2.5 m (8.2 ft)	4 m (13.1 ft)	38 mm (1 1/2)
10-13373-04	Viking Power 32, 24V	32 l/min (8.5 GPM)	30 l/min (7.9 GPM)	2.5 m (8.2 ft)	4 m (13.1 ft)	38 mm (1 1/2)
10-13373-07	Viking Power Vacuum, 12V	24 l/min (6.3 GPM)	22 l/min (5.8 GPM)	5 m (16.4 ft)	4 m (13.1 ft)	38 mm (1 1/2)
10-13373-08	Viking Power Vacuum, 24V	24 l/min (6.3 GPM)	22 l/min (5.8 GPM)	5 m (16.4 ft)	4 m (13.1 ft)	38 mm (1 1/2)



	VIKING POWER 16	VIKING POWER 32	VIKING POWER VACUUM
MOTOR	2.3 amp (12V), 1.2 amp (24V) at 0.1 bar 12/24V DC (with built-in thermal protection)	3.3 amp (12V), 1.6 amp (24V) at 0.1 bar 12/24V DC (with built-in thermal protection)	3.3 amp (12V), 1.6 amp (24V) at 0.1 bar 12/24V DC (with built-in thermal protection)
BODY	Nylon, glass-fiber reinforced	Nylon	Nylon
VALVES	Nitrile rubber	Nitrile rubber	Nitrile rubber
DIAPHRAGM	Reinforced nitrile rubber	Reinforced nitrile rubber	Reinforced nitrile rubber
LENGTH	186 mm (7.3")	277 mm (10.9")	357 mm (14")
WIDTH	235/181 mm (9.3"/7.1")	264 mm (10.4")	271 mm (10.7")
HEIGHT	118/204 mm (4.6"/8")	192 mm (7.6")	192 mm (7.6")
WEIGHT	2.6 kg (5.7 lbs)	5.0 kg (11.0 lbs)	5.1 kg (11.2 lbs)

SPXFLOW®

SPX FLOW, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. The green "➤" is a trademark of SPX FLOW, Inc.

For more information, visit www.spxflow.com/johnson-pump-marine