

Part Numbering System

Dual Outlet Stops


Example:



K	T	C	R	1	9	0	1	L	R	C	1
Stop Style	Stop Type	Riser Outlet	Inlet	Dual Outlet	Side Outlet	Option	Finish	Packaging			
1/4 Turn Ball Stop	Compression Inlet	3/8" OD (1/4" Nom)	1/2" Nominal Copper, Angle		3/8" OD (1/4" Nom)	Outlet Either Side	Chrome	Individually Boxed			



Stop Style

Handle
(Modifier)Stem
(Modifier)

Stop Type



Outlet




Inlet



Dual Outlet



Side Outlet

Option
(Modifier)

Finish



Packaging

Stop Style

KT Multi-Turn, Tee-Handle 1/4 Turn Ball Stop

Handle*

*Available w/Multi-Turn Only

S Loose Key, Lock Shield
 SS Screw Driver Slot, Lock Shield

X Cross
 XX Round

Stem*

*Available w/Multi-Turn Only

T Stuffing Box

Stop Type

CR Compression Inlet
 FR Flare Outlet
 PR CPVC Inlet

R Iron Pipe or Sweat Inlet
 BRPX Barbed PEX Inlet

Riser Outlet

1 3/8" OD (1/4" Nom)
 2 7/16" OD

3 1/2" OD (3/8" Nom)

Inlet

7 1/2" Female Iron Pipe, Angle

9 1/2" Nominal Copper, Angle

Dual Outlet

0 Dual Outlet

Side Outlet

0 1/4" OD
 1 3/8" OD (1/4" Nom)

2 7/16" OD
 3 1/2" OD (3/8" Nom)

Option

L Left Side Outlet
 LR Outlet Either Side
 R Right Side Outlet

For Dual Shut-Offs:

DV Dual Shut-Off
 DVS Dual Shut-Off, Straight


Finish

C Chrome Plated, Trayed

R Rough/Unplated, Trayed

Packaging

1 Individually Bagged (These stops are highlighted in **bold print** in this catalog).



A



B

PART NO.	UPC	INLET	OUTLETS	FINISH	QTY.	LBS.
Dual Outlet, Dual Shut-Off Stops – Compression Inlet						
CR1900DV C	026613024844	1/2" Nom Comp (DRWG. A)	3/8" OD Comp x 1/4" OD Comp	Chrome	30	15
CR1900DV R	026613024851	1/2" Nom Comp (DRWG. A)	3/8" OD Comp x 1/4" OD Comp	Rough	30	15
CR1900DVS R	026613083940	1/2" Nom Comp (DRWG. B)	3/8" OD Comp x 1/4" OD Comp	Rough	30	15
CR1901DV C	026613024882	1/2" Nom Comp (DRWG. A)	3/8" OD Comp x 3/8" OD Comp	Chrome	30	15
CR1901DV R	026613024899	1/2" Nom Comp (DRWG. A)	3/8" OD Comp x 3/8" OD Comp	Rough	30	15
CR1901DVS C	026613093499	1/2" Nom Comp (DRWG. B)	3/8" OD Comp x 3/8" OD Comp	Chrome	30	15
CR1901DVS R	026613024875	1/2" Nom Comp (DRWG. B)	3/8" OD Comp x 3/8" OD Comp	Rough	30	15
CR1903DV R	026613003696	1/2" Nom Comp (DRWG. A)	3/8" OD Comp x 1/2" OD Comp	Rough	30	16

Δ Dual Outlet, Dual Shut-Off Stop – CPVC Solvent Weld Inlet




PR1901DV R	026613105444	1/2" Nom CPVC	3/8" OD Comp x 3/8" OD Comp	Rough	30	15
------------	--------------	---------------	--------------------------------	-------	----	----

Dual Outlet, Dual Shut-Off Stops – FIP Inlet



A



B

R1700DV R	026613083889	1/2" FIP (DRWG. A)	3/8" OD Comp x 1/4" OD Comp	Rough	30	15
R1700DVS R	026613083872	1/2" FIP (DRWG. B)	3/8" OD Comp x 1/4" OD Comp	Rough	30	15
R1701DV R	026613083919	1/2" FIP (DRWG. A)	3/8" OD Comp x 3/8" OD Comp	Rough	30	15
R1701DVS R	026613083957	1/2" FIP (DRWG. B)	3/8" OD Comp x 3/8" OD Comp	Rough	30	15

Dual Outlet, Dual Shut-Off Stops – Sweat Inlet



A



B

R1900DV R	026613028750	1/2" Nom Sweat (DRWG. A)	3/8" OD Comp x 1/4" OD Comp	Rough	30	16
R1901DV R	026613028767	1/2" Nom Sweat (DRWG. A)	3/8" OD Comp x 3/8" OD Comp	Rough	30	16
R1901DVS R	026613083964	1/2" Nom Sweat (DRWG. B)	3/8" OD Comp x 3/8" OD Comp	Rough	30	16

Δ CPVC pre-torqued fittings eliminate the need for tightening on the job
See **page 103** for material specifications.