For Residential and Commercial Applications					
Job Name	Engineer / Architect				
Job Location	Wholesaler				
Submittal Date	Contractor				

SWB00 3/4" ID Coated Stainless Steel Water Heater Connector – Female Iron Pipe x Female Iron Pipe

Use: For use in exposed locations only to connect water heaters, water softeners and other water connected devices to the water supply

Design Features:

- **Proprietary ProCoat® clear coat** provides unrivaled corrosion protection from harsh chemicals that can cause surface deterioration and pinhole leaks.
- Full flow, maximum performance. ¾" internal diameter provides greater water flow without obstruction
- Integrated dielectric sleeve effectively isolates dissimilar metals within the waterway to help prevent galvanic and electrolytic corrosion
- **No dielectric union needed** with installation. Dielectric is built-in to the design of the connector
- Less torque to seal against the pliable rubber washer, especially on rough nipple surfaces
- Longer connector nuts allow a greater number of thread-to-thread contacts and a better seal
- 100% leak tested prior to coating application to ensure connector performance and reliability
- 100% Compliant

Operating Specifications:

Temperature: 40° - 180° F *Water Pressure:* 125 PSI maximum

MATERIAL SPECIFICATIONS					
Tubing Stainless steel					
Dielectric Sleeve	Polypropylene				
Nut	Brass				
Washer	Rubber				

Part Listing:

SWB00-12N	3/4" ID X 12" connector with 3/4" FIP x 3/4" FIP end fittings
SWB00-15N	3/4" ID X 15" connector with 3/4" FIP x 3/4" FIP end fittings
SWB00-18N	3/4" ID X 18" connector with 3/4" FIP x 3/4" FIP end fittings
SWB00-24N	3/4" ID X 24" connector with 3/4" FIP x 3/4" FIP end fittings

This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft Mfg. This specification must be returned to BrassCraft Mfg if requested.



300.41 SWB00 Coated Stainless Steel Water Heater Connectors REV 10/12



U		J
4	<u> </u>	7
Ć	$ \rightarrow $	
Ć		
Ć		
Ć	$ \rightarrow $	
Ć		
Ć		
Ć	$ \rightarrow $	
¢	$ \rightarrow $	
Ċ	$ \rightarrow $	
Ċ	$ \rightarrow $	
Ċ	$ \longrightarrow $	
Ċ	$ \rightarrow $	
Č	$ \rightarrow $	
5	$ \rightarrow $	
5	$ \rightarrow $	
5	\rightarrow	
5	\rightarrow	
5	$ \rightarrow $	
3	\rightarrow	
5	\rightarrow	
5	\rightarrow	
3	\rightarrow	
3		
3		
3		
3		
3		
5		
]		
\cap	\square)
\sim		ſ
		1

SWB00 3/4" ID Coated Stainless Steel Water Heater Connector – Female Iron Pipe x Female Iron Pipe



PART DIMENSIONS (Inches)						
Connector Length – Nut by Nut						
Model	Dim.	12″	15″	18″	24″	
SWB00	Α	12.00 min.	15.00 min.	18.00 min.	24.00 min.	

Listings & Certifications:

- CSA listed to ASME A112.18.6 and CSA B125.6
- IAPMO listed to ASME A112.18.6 and CSA B125.6 (File # 0452)
- Compliant product CSA listed to Low Lead Content Certification Program – Plumbing Products Class 6853-01



