Mixing Metering Handwash Faucet



DELTA

 Specification: (example) HEAVY-DUTY CAST BRASS Two handle mixing metering faucet Vandal resistant handle actuator Vandal resistant spout outlet Polished chrome plated finish Delta[®] metering slow close cartridge Total flow not to exceed 0.25 gallon per handle activation and with (add product variation required) with (add handle required) 	86T1153 B6T1153 Engineer/Archit Model Specified: Approval:	
DESCRIPTION Mixing Metering Handwash Faucet	PRODUCT NO.	
PRODUCT VARIATION	OUTLET	HANDLE
102mm (4")		
O Centerser with Open Grid Strainer	0	0
102mm (4") Centerset less Pop-up	1	1
2	2	2
3	3	3 Vandal Resistant ADA Lever Handle
4	4	4
5	5 Vandal Resistant 0.5 gpm (1.9 L/min) Non-Aerating Spray Outlet	5
6	6	6
7	7	7
8	8	8
9	9 Vandal Resistant 0.35 gpm (1.32 L/min) Non-Aerating Spray Outlet	9

Refer to www.specselect.com for individual models.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability. Flow Rates are at 60 PSI.

Note: Use this page front and back as a product submittal sheet.



Approvals:

- CSA certified
- Complies to ASME A112.18.1/CSA B125.1
- Lindicates compliance to ICC/ANSI A117.1
- Verified compliant with 0.25% weighted average Pb content regulation

(Contact Delta Representative for State and/or Local Approvals.)





Mixing Metering Handwash Faucet



Note: Measurements may vary ± 6mm (0.25")

Refer to www.specselect.com for individual models.

Note: Use this page front and back as a product submittal sheet.

DSP-86T Rev. E

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.