

# Submitted Model No.:

Specific Features:



▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do<sup>.</sup>

# H<sub>2</sub>OKINETIC RAINCAN SHOWER HEAD

## **FEATURES:**

- Touch-Clean<sup>®</sup> Nozzles
- H<sub>2</sub>Okinetic<sup>®</sup> UltraSoak<sup>™</sup> Spray
- Lumicoat<sup>™</sup> Finish (-PR models only)
- Lumicoat<sup>™</sup> Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

### **STANDARD SPECIFICATIONS**

- Max flow rate 1.75 gpm at 80 psi, 6.6 L/min @ 550 kPa (52161-▲)
- Max flow rate 2.5 gpm at 80 psi, 9.5 L/min @ 550 kPa (52161-▲25)
- Ball connector swivel angle is 44° (22° per side)
- Metal ball connector for durability, easy installation
- Standard 1/2"-14 NPT pipe fitting

### WARRANTY

- · Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
  EPA WaterSense<sup>®</sup> applies to 52161-▲ and 52161-▲-PR only

Delta Faucet Company 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2021 Delta Faucet Company