

TECHNICAL DATA SHEET

Clear Vinyl Tubing

PRODUCT

Clear Vinyl Tubing

APPLICATION

Air conditioning and refrigeration condensate drains, condensate pump discharge lines and humidifier overflows.

ADVANTAGES

Made of high-quality vinyl with smooth interior and exterior that allows easy flow and flushing and prevents sediment accumulation. Its walls are thick enough to resist kinks but are lightweight, flexible, can withstand rough handling, and multiple usage while maintaining dimensional stability. DiversiTech® clear vinyl tubing is easy to shape, bend, and install.

GENERAL CHARACTERISTICS

- Seven sizes from 3/16" to 1" Diameters •
- Clear Vinyl Chloride (PVC)
- Resists crimping and kinking with a • Durometer Value of 86 (Shore A)
- Service Temperature 140° F (60° C)



-ID



1	_	 	 _	_
]D				
ľ				

ITEM #	Nominal Size (in)	Weight (lbs)	Length (ft)	Inner Diameter (in)	Outer Diameter (in)	Wall Thickness (in)
7-316	3/16	1.46	100	0.188	0.264	0.038
7-14	1/4	2.15	100	0.250	0.336	0.043
7-38	7/38	3.59	100	0.371	0.471	0.050
7-12	1/2	5.84	100	0.485	0.610	0.063
7-58	5/8	8.43	100	0.598	0.745	0.074
7-34	3/4	13.06	100	0.705	0.896	0.096
7-78	7/8	9.29	50	0.800	1.037	0.119
7-10	1	12.44	50	0.923	1.198	0.137

TDSCVT Date: October 2021