

Protector+ Filter Fluid 500ml

62234

- Unique inhibitor package with dispersant designed to lift and deliver circulating debris in the system to a system filter for safe collection and removal
- Must be used only in conjunction with a system filter - provides premium protection against corrosion and scale in mixed metal heating and cooling systems, including aluminium
- Designed to be left in the system permanently. Treats up to 130 litres of system water (16 radiators) and the equivalent of 250m² of underfloor systems.
- Prevents scale and corrosion formation
- Innovative, best-in-class formulation-optimises efficiency and extends system lifespan



Designed for use with Fernox TF1 in-line system filters or other similar filters, this unique inhibitor package includes an active dispersant which is proven to aid the safe collection of corrosion, debris and scale via a filter. The Protector+ Filter Fluid enhances the performance of a system filter whilst offering full protection against corrosion and scale formation. This innovative, proven formulation also extends system life and maintains optimum efficiency, while still being an environmentally friendly formulation. Concentration levels should be checked as part of the annual maintenance system service.

Application

The recommended 'in use' concentration of Protector+ Filter Fluid is 0.385%. A single dose treats and protects a larger sized property with a heating system of 130 litres, up to 16 radiators or 250 sqm of underfloor heating. For open vented systems add via the feed and expansion tank. For sealed systems add via a suitable dosing point (e.g. a towel rail, or an in-line system filter). Alternatively, use a suitable dosing vessel to inject the product into the system. In single feed indirect cylinders, e.g. 'Primatic' or similar, potable water chemicals must be used. We recommend that untreated, or sludged systems are thoroughly cleaned and flushed in accordance with BS 7593:2019 and Benchmark using Fernox Cleaner F3/F8, before treating with Fernox Protector+ Filter Fluid, as existing debris can damage the installation.

Fernox Protector+ Filter Fluid must be used with the Fernox TF1 Filter range, or other in-line system filters. Use in microbore systems is not recommended. Fernox Protector+ Filter Fluid is an enhanced corrosion inhibitor, combining corrosion inhibition with dispersant properties. It is specifically formulated to prevent settling and aggregation of corrosion deposits and contaminants within central heating systems, to deliver the debris directly to an in-line filter (such as one from the Fernox TF1 Filter range) for fast removal and containment. This function allows systems to run more efficiently by minimising the settling of debris in low flow areas such as radiators, which causes cold spots, and facilitates further corrosion underneath the debris.

Protector+ Filter Fluid gives long-term protection of domestic central heating systems against internal corrosion and limescale formation. It is suitable for all types of boiler, radiators and pipework systems. Protector+ Filter Fluid is compatible with all metals and materials commonly used in central heating systems. It is suitable for use with all types of water, including softened water and deionised water.

Protector+ Filter Fluid has been formulated to have best-in-class pH buffering ability, which keeps system water pH between 6.5-8.5, providing optimum protection for mixed-metal systems. To comply with BS 7593:2019, Protector+ Filter Fluid levels should be checked annually. The concentration of the product can be easily measured on-site using a Fernox Protector Test Kit, or by using the Fernox Water Quality Test postal service. BS 7593:2019 also states that after five years, systems should either be re-dosed, or a laboratory test performed, such as the Fernox Water Quality Test.

Package, Handling & Safety

Fernox Protector+ Filter Fluid is supplied in 500 ml bottles.

Fernox Protector+ Filter Fluid is classified as non-hazardous for human health, but as with all chemicals, keep out of reach of children. In case of contact with eyes or skin, rinse immediately with plenty of water.

Specification

Fernox Protector+ Filter Fluid is a blend of corrosion and scale inhibitors and dispersants.

Form: Liquid Odour: Aromatic

Colour: Light Yellow

pH (conc): 8.3

pH (in use): 7.8-8.5

SG: 1.135 at 20°C

Single Item

Height mm	182
Width mm	88
Depth mm	52
Weight kg	0.600
Barcode EAN	5014551622340

Outer Carton

Outer Height mm	195
Outer Width mm	265
Outer Depth mm	180
Outer Weight kg	6.130
Transit Type	CP1 1200 x 1000
OCU Barcode	05014551001251

Last modification 18-02-2021 (d/m/y)