

Buy it for looks. Buy it for life.®

DESCRIPTION

- Reflex® System offer smooth operation, easy movement and secure docking
- Power Clean[™] spray technology
- · Metal construction with various finishes identified by suffix
- Pullout spray with 68" braided hose with Duralock™ Quick Connect installation
- 3/8" compression connections will accept standard ball nose connection for 3/8" tubing
- High arc spout provides height and reach to fill or clean large pots while the pullout wand provides the maneuverability for cleaning and rinsing 100° spout rotation

OPERATION

- · Lever style handle
- · Operates with less than 5 lbs. of force
- Operates in spray or stream mode in the pullout or retracted position

FLOW

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- 1255™ Duralast™ cartridge for Single-Handle Faucets
- Engineered polymers, non-ferrous and stainless steel materials


STANDARDS

- Third party certified to IAPMO Green ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow



WARRANTY


- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
 5 year limited warranty when used in a commercial installation
 Visit www.moen.com/support for complete details and limitations



CRITICAL DIMENSIONS

(DO NOT SCALE)

Specifications



BRANTFORD™ Single Handle Pullout Kitchen Faucet

Model: 7295 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1, 2 OR 3 HOLES, 1-1/2" (38mm) MIN. DIA.

