

MrPEX® F1960 RING SUBMITTAL



5300 Alpine Drive NW, Suite 210
Ramsey, MN 55303
support@mrpexsystems.com

Project Name _____ Date _____
Submitted By _____ Phone _____
Project Location _____ MrPEX® Rep. _____
Engineer _____ Contractor _____
Approval _____ P.O. Number _____

MrPEX® F1960 Rings

MrPEX® F1960 Ring can be used with both PPSU and brass F1960 fitting

MrPEX® F1960 Rings come with stop for ease of installation

Technical Data	
Material	Cross-Linked Polyethylene
Max temperature	200°F



Size	Part #	Height	ID	OD
1/2"	4600500	0.64"	0.62"	0.87"
3/4"	4600750	0.86"	0.87"	1.11"
1"	4601000	1.11"	1.13"	1.41"
1 1/4"	4601250	1.37"	1.38"	1.66"
1 1/2"	4601500	1.62"	1.65"	1.94"
2"	4602000	2.00"	2.15"	2.65"

Standards

- ASTM F1960
- ASTM F877
- NSF/ANSI 14
- NSF/ANSI 61
- NSF/ANSI 61 Annex G
- CSA B137.5

Listings

- IAPMO UPC
- cNSFuspw
- CSA