

THIS SPACE FOR DESIGNER/ENGINEER APPROVAL

Job/Customer _____	Date _____	Contractor _____
Model Specified _____	Qty _____	Approved By _____
Designer/Engineer _____	Date _____	Contractor's PO# _____
Submitted By _____	Date _____	Other _____


H-2640W Series

Forged Dezincification Resistant Brass Push Fittings


200 PSI / 200° F Max




Lead-free products are certified to ASSE 1061 & NSF/ANSI 61 G



NO.	DESCRIPTION	MATERIAL
1	BODY	BRASS
2	O-RING	EPDM
3	PROTECTOR	PLASTIC
4	GRIP RING	STAINLESS STEEL
5	RELEASE COLLAR	PLASTIC
6	NUT	BRASS
7	INNER LINING	PLASTIC




Push x Push 90 Elbow				Size	A	B	C
Item #	Ctn/Case	Item#	Ctn/Case				
26402*	10/100	26402W	20/200	½"	1/2	1 3/8	1/2
26403	10/100	26403W	12/120	¾"	3/4	1 5/8	3/4
--	--	26432W	12/120	¾" x ½"	1/2	1 7/16	3/4
26404	5/50	26404W	10/100	1"	1	1 15/16	1




Push x FIP 90 Elbow							
ITEM # Lead Free	Ctn/Case	Size	A	B	C	D	E
26422W	20/200	½"	1 1/16	1 3/8	1/2	1/2	1 1/16


Push x MIP 90 Elbow							
ITEM # Lead Free	Ctn/Case	Size	A	B	C	D	E
26222W	20/200	½"	1 1/4	1 3/8	1/2	1/2	1 1/16



Push x FIP 90 Drop Ear Elbow							
ITEM # Lead Free	Ctn/Case	Size	A	B	C	D	E
26412W	9/90	½"	1 1/16	1 1/4	1/2	1 1/16	1 1/16



Push x Push 90 Drop Ear Elbow						
ITEM # Lead Free	Ctn/Case	Size	A	B	C	D
26462W	9/90	½"	1 5/16	1 5/16	1/2	1



Quality and Commitment Since 1954

www.webstonevalves.com • Tel: (800) 225-9529 • Fax (800) 336-5133

Webstone product specifications in U.S. customary units are approximate and are provided for reference only. Webstone reserves the right to change or modify product design, construction, specifications or materials without prior notice and without incurring any obligation to make such changes and modifications on Webstone products previously or subsequently sold.

2610-2610Wspec_0814144