



H-x406W Series

E-X-P E2 Tankless Water Heater Service Valve Kit
Hot & Cold Set of Full Port Forged DZR Brass Ball Valves
w/ Hi-Flow Hose Drains
& Adjustable Packing Glands

Certifications

Certified to NSF/ANSI 61 & 372
Lead-Free



Patented Technology



NO.	DESCRIPTION	MATERIAL
1	Body	Lead Free DZR Brass
2	Union Fitting	Lead Free DZR Brass
3	Packing Gland	Brass
4	Packing Gland	Brass
5	Union Nut	Brass
6	Stem	Lead Free DZR Brass
7	Stem	Lead Free DZR Brass
8	End Cap	Lead Free DZR Brass
9	Cap & Strap	Brass & PVC
10	Ball	Brass HCP
11	Ball	Brass HCP
12	Handle	Steel CP
13	Handle	Aluminum
14	Screw	Stainless Steel
15	Handle Nut	Stainless Steel
16	Retainer Ring	Stainless Steel
17	Gasket	EPDM
18	Gasket	EPDM
19	Seat	PTFE
20	Seat	PTFE
21	Stem Seal	PTFE
22	Stem Seal	PTFE
23	End Cap	Lead Free DZR Brass
24	Lock Washer	Stainless Steel

Designed for residential or commercial use with potable water. This approved Webstone valve is actuated by a blowout proof stem.
Threaded ends comply with ANSI B1.20.1. *Certified to NSF/ANSI 14. +Certified to ASSE 1061

ITEM#	Connection Type	SIZE (in)	Pressure Rating	Max. Temp.	A	B	C	D	E	F
* H-14063W	FIP Union x ASTM F1807 PEX	3/4	400 PSI CWP Max	200°F Max	4.50	4.53	2.00	2.63	3.11	0.50
* H-34063W	FIP Union x ASTM F1960 PEX	3/4	400 PSI CWP Max	200°F Max	4.50	4.88	2.00	2.63	3.11	0.50
H-44063W	FIP Union x FIP	3/4	500 PSI CWP Max	200°F Max	4.50	4.25	2.00	2.63	3.11	0.50
H-54063W	FIP Union x SWT	3/4	500 PSI CWP Max	200°F Max	4.50	4.75	2.00	2.63	3.11	0.50
*+ H-64063W	FIP Union x Push	3/4	200 PSI CWP Max	200°F Max	4.50	4.83	2.00	2.63	3.11	0.50
H-84063W	FIP Union x Press	3/4	250 PSI CWP Max	200°F Max	4.50	5.25	2.00	2.63	3.11	0.50



