


STEP SAVING VALVES FOR

NEW SPACE-SAVING WEBSTONE EXCLUSIVES




- Eliminates assemblies needed to isolate and drain any portion of a piped system
- Integrated Y-strainer saves space and protects system from debris
- · Creates cleaner-looking, more efficient installations
- Suitable for vertical or horizontal installation
- · Replaceable 20 mesh screen
- O-ring sealed and plugged strainer port for easy removal of filter and installation of drain valve
- 1/2 2" FIP and Press system connections




EXCLUSIVE






SIMPLIFIES SYSTEM SERVICE



SIMPLIFIES STRAINER SERVICE



Flushing w/ Reverse Flow

Flushing w/

OPTIONS FOR EVERY JOB



Webstone®

a brand of **NIBCO®**

VALVE INNOVATION INSTALLATION SOLUTIONS

webstonevalves.com/pro-pal









Webstone Y-STRAINER PRODUCTS a brand of NIBCO®





- Eliminates assemblies needed to isolate and drain any portion of a piped system
- Integrated Y-strainer saves space and protects system from debris
- Creates cleaner-looking, more efficient installations
- Suitable for vertical or horizontal installation
- · Replaceable 20 mesh screen
- O-ring sealed and plugged strainer port for easy removal of filter and installation of drain valve







Diverts fluid into the drain from either side of the ball and isolates strainer from upstream flow for service



Full Port Forged DZR Brass Ball Valve w/ Hi-Flow Multi-Function Hose Drain, Integral Y-Strainer (20 Mesh), 1/2" Plugged NPT Port & Adjustable Packing Glands

	. or carrajaotao	o r doming didirdo			
	LEAD-FREE BRASS				
	Certified to NSF/ANSI 61 & 372				
SIZE	ITEM#	CTN/CASE	CASE WT		
FIP	250 PSI CWP Max/200°F Max				
1/2"	H-41562W	4/32	35		
3/4"	H-41563W	2/24	40		
1"	H-41564W	2/20	44		
1 1/4"	H-41565W	2/12	42		
Press	250 PSI CWP Max/200°F Max				
1/2"	H-81562W	2/24	29		
3/4"	H-81563W	2/20	36		
1"	H-81564W	2/12	28		
1 1 //!!	LI 01EGEW	2/0	20		

Y-STRAINER

- Lead-free forged DZR brass construction
- Replaceable 20 mesh screen
- O-ring sealed and plugged strainer port for easy removal of filter and installation of drain valve

	GO.	
		×

FORGED DZR BRASS Y-STRAINER (20 MESH) w/ 1/2" Plugged NPT Port

W/ 1/2" PIL	igged NPT Port			
	LEAD-FREE BRASS			
	Certified to NSF/ANSI 61 & 372			
SIZE	ITEM#	CTN/CASE	CASE WT	
FIP		250 PSI CWP Ma	x/200°F Max	
1/2"	H-40562W	8/80	40	
3/4"	H-40563W	6/60	42	
1"	H-40564W	4/40	35	
1 1/4"	H-40565W	4/24	35	
1 1/2"	H-40566W	2/20	41	
2"	H-40567W	2/10	34	
Press	250 PSI CWP Max/200°F Max			
1/2"	H-80562W	12/72	40	
3/4"	H-80563W	6/48	38	
1"	H-80564W	5/40	38	
1 1/4"	H-80565W	4/24	34	
1 1/2"	H-80566W	2/12	28	
2"	H-80567W	2/8	29	



ALSO AVAILABLE



- Connect a Y-strainer directly to any standard circulator pump
- Rotating flange provides versatility
- 1/2" plugged NPT strainer port for installation of drain valve

Y-STRAINER W/ROTATING FLANGE						
		STANDARD BRASS				
SIZE	ITEM#	CTN/CASE	CASE WT			
SWT × Rotating Flange		60	O PSI CWP Max			
1"	H-FSTR4-54	6/24	39			
1 1/4"	H-FSTR5-55	6/24	47			