



# RAIN COLLAR FOR NO-CALK ROOF FLASHING

## TECHNICAL SPECIFICATION

Job Name	_____	Item #	_____
Location	_____		
Engineer	_____	Contractor	_____
PO #	_____	Tag	_____
Representative	_____		

### SPECIFICATIONS

Oatey Rain Collar for No-Calk Roof Flashings can be used as a secondary seal for commercial and residential applications where a watertight seal for roof penetrations around the plumbing vent pipe is required.

### DESCRIPTION

- Non-fading sealing collar.
- Not for hot-mopped or built-up roofs.
- Do not use paint or petroleum based products on rubber collars.
- Slides over existing roof flashing.



### PRODUCT SELECTOR

RAIN COLLAR FOR NO-CALK ROOF FLASHING				
✓	Product Number	Description	Pack	Carton Weight
	14122	1-¼" - 1-½" Rain Collar for No-Calk Roof Flashing	36	2 lbs.
	14205	1-¼" - 1-½" Collar - Carded	6	0.3 lbs.
	14135	2" Rain Collar for No-Calk Roof Flashing	24	2 lbs.
	14206	2" Collar Carded	6	0.6 lbs.
	14193	3" Rain Collar for No-Calk Roof Flashing	24	3 lbs.
	14207	3" Collar Carded	6	0.6 lbs.
	14203	4" Rain Collar for No-Calk Roof Flashing	12	5 lbs.
	14208	4" Collar Carded	6	1.2 lbs.
	14136	1-½" – 3" Rain Collar for No-Calk Roof Flashing	24	3 lbs.
	14137	3" - 4" All-Flash Rain Collar for No-Calk Roof Flashing	24	10 lbs.